

ASN1C

ASN.1 Compiler
Version 6.5
C# BER/DER/PER/XER/XML
Reference Manual

The software described in this document is furnished under a license agreement and may be used only in accordance with the terms of this agreement.

Copyright Notice

Copyright ©1997–2012 Objective Systems, Inc. All rights reserved.

This document may be distributed in any form, electronic or otherwise, provided that it is distributed in its entirety and that the copyright and this notice are included.

Author's Contact Information

Comments, suggestions, and inquiries regarding ASN1C may be submitted via electronic mail to info@obj-sys.com.

Contents

1	Class Documentation	1
1.1	Asn1BerDecodeBuffer Class Reference	1
1.1.1	Detailed Description	2
1.1.2	Constructor & Destructor Documentation	2
1.1.2.1	Asn1BerDecodeBuffer	2
1.1.2.2	Asn1BerDecodeBuffer	2
1.1.3	Member Function Documentation	2
1.1.3.1	CalcIndefLen	2
1.1.3.2	DecodeEnumValue	2
1.1.3.3	DecodeEnumValue	3
1.1.3.4	DecodeLength	3
1.1.3.5	DecodeOpenType	3
1.1.3.6	DecodeOpenType	3
1.1.3.7	DecodeTag	3
1.1.3.8	DecodeTagAndLength	4
1.1.3.9	MatchTag	4
1.1.3.10	MatchTag	4
1.1.3.11	MatchTag	4
1.1.3.12	MovePastEOC	5
1.1.3.13	Parse	5
1.1.3.14	PeekTag	5
1.1.3.15	PeekTag	5
1.1.3.16	ReadByte	5
1.1.4	Property Documentation	5
1.1.4.1	LastTag	5
1.2	Asn1BerDecodeContext Class Reference	6
1.2.1	Detailed Description	6
1.2.2	Constructor & Destructor Documentation	6

1.2.2.1	Asn1BerDecodeContext	6
1.2.3	Member Function Documentation	6
1.2.3.1	Expired	6
1.2.3.2	MatchElemTag	6
1.2.3.3	MatchElemTag	7
1.2.4	Member Data Documentation	7
1.2.4.1	mDecBufByteCount	7
1.2.4.2	mDecodeBuffer	7
1.2.4.3	mElemLength	7
1.2.4.4	mExplicitTagging	7
1.2.4.5	mTagHolder	7
1.3	Asn1BerEncodeBuffer Class Reference	8
1.3.1	Detailed Description	8
1.3.2	Constructor & Destructor Documentation	8
1.3.2.1	Asn1BerEncodeBuffer	8
1.3.2.2	Asn1BerEncodeBuffer	9
1.3.3	Member Function Documentation	9
1.3.3.1	BinDump	9
1.3.3.2	BinDump	9
1.3.3.3	CheckSize	9
1.3.3.4	Copy	9
1.3.3.5	Copy	9
1.3.3.6	Copy	10
1.3.3.7	Copy	10
1.3.3.8	EncodeIdentifier	10
1.3.3.9	EncodeIntValue	10
1.3.3.10	EncodeLength	10
1.3.3.11	EncodeTag	11
1.3.3.12	EncodeTagAndLength	11
1.3.3.13	EncodeTagAndLength	11
1.3.3.14	EncodeUnsignedBinaryNumber	11
1.3.3.15	GetInputStream	12
1.3.3.16	Reset	12
1.3.3.17	ToString	12
1.3.3.18	TrimBitString	12
1.3.3.19	Write	12
1.3.4	Property Documentation	12

1.3.4.1	ByteArrayInputStream	12
1.3.4.2	MsgCopy	13
1.3.4.3	MsgLength	13
1.4	Asn1BerInputStream Class Reference	14
1.4.1	Detailed Description	14
1.4.2	Constructor & Destructor Documentation	14
1.4.2.1	Asn1BerInputStream	14
1.4.3	Member Function Documentation	14
1.4.3.1	Available	14
1.4.3.2	Close	15
1.4.3.3	Mark	15
1.4.3.4	MarkSupported	15
1.4.3.5	Reset	15
1.4.3.6	Skip	15
1.5	Asn1BerMessageDumpHandler Class Reference	16
1.5.1	Detailed Description	16
1.5.2	Constructor & Destructor Documentation	16
1.5.2.1	Asn1BerMessageDumpHandler	16
1.5.2.2	Asn1BerMessageDumpHandler	16
1.5.3	Member Function Documentation	16
1.5.3.1	Contents	16
1.5.3.2	EndElement	16
1.5.3.3	StartElement	17
1.6	Asn1BerOutputStream Class Reference	18
1.6.1	Detailed Description	18
1.6.2	Constructor & Destructor Documentation	18
1.6.2.1	Asn1BerOutputStream	18
1.6.2.2	Asn1BerOutputStream	18
1.6.3	Member Function Documentation	19
1.6.3.1	Encode	19
1.6.3.2	EncodeBitString	19
1.6.3.3	EncodeBMPString	19
1.6.3.4	EncodeCharString	20
1.6.3.5	EncodeEOC	20
1.6.3.6	EncodeIdentifier	20
1.6.3.7	EncodeIntValue	20
1.6.3.8	EncodeLength	21

1.6.3.9	EncodeOctetString	21
1.6.3.10	EncodeTag	21
1.6.3.11	EncodeTag	21
1.6.3.12	EncodeTagAndIndefLen	22
1.6.3.13	EncodeTagAndIndefLen	22
1.6.3.14	EncodeTagAndLength	22
1.6.3.15	EncodeUnivString	22
1.6.3.16	EncodeUnsignedBinaryNumber	23
1.7	Asn1CerInputStream Class Reference	24
1.7.1	Detailed Description	24
1.7.2	Constructor & Destructor Documentation	24
1.7.2.1	Asn1CerInputStream	24
1.8	Asn1CerOutputStream Class Reference	25
1.8.1	Detailed Description	25
1.8.2	Constructor & Destructor Documentation	25
1.8.2.1	Asn1CerOutputStream	25
1.8.2.2	Asn1CerOutputStream	25
1.8.3	Member Function Documentation	26
1.8.3.1	Encode	26
1.8.3.2	EncodeBitString	26
1.8.3.3	EncodeBMPString	26
1.8.3.4	EncodeCharString	27
1.8.3.5	EncodeOctetString	27
1.8.3.6	EncodeStringTag	27
1.8.3.7	EncodeStringTag	28
1.8.3.8	EncodeUnivString	28
1.9	Asn1DerDecodeBuffer Class Reference	29
1.9.1	Detailed Description	29
1.9.2	Constructor & Destructor Documentation	29
1.9.2.1	Asn1DerDecodeBuffer	29
1.9.2.2	Asn1DerDecodeBuffer	29
1.10	Asn1DerEncodeBuffer Class Reference	30
1.10.1	Detailed Description	30
1.10.2	Constructor & Destructor Documentation	30
1.10.2.1	Asn1DerEncodeBuffer	30
1.10.2.2	Asn1DerEncodeBuffer	30
1.10.3	Member Function Documentation	30

1.10.3.1	TrimBitString	30
1.11	Asn1DerInputStream Class Reference	31
1.11.1	Detailed Description	31
1.11.2	Constructor & Destructor Documentation	31
1.11.2.1	Asn1DerInputStream	31
1.11.3	Member Function Documentation	31
1.11.3.1	Available	31
1.11.3.2	Close	31
1.11.3.3	Mark	32
1.11.3.4	MarkSupported	32
1.11.3.5	Reset	32
1.11.3.6	Skip	32
1.12	Asn1NotInSetException Class Reference	33
1.12.1	Detailed Description	33
1.12.2	Constructor & Destructor Documentation	33
1.12.2.1	Asn1NotInSetException	33
1.13	Asn1PerBitField Class Reference	34
1.13.1	Detailed Description	34
1.13.2	Constructor & Destructor Documentation	34
1.13.2.1	Asn1PerBitField	34
1.13.3	Member Function Documentation	34
1.13.3.1	SetBitCountAndOffset	34
1.13.4	Property Documentation	34
1.13.4.1	BitCount	34
1.13.4.2	BitOffset	35
1.13.4.3	Name	35
1.14	Asn1PerBitFieldList Class Reference	36
1.14.1	Detailed Description	36
1.14.2	Member Function Documentation	36
1.14.2.1	AddElemName	36
1.14.2.2	Iterator	36
1.14.2.3	NewBitField	36
1.14.2.4	RemoveLastElemName	37
1.14.2.5	Reset	37
1.14.3	Property Documentation	37
1.14.3.1	BitOffset	37
1.14.3.2	CurrBitField	37

1.15	Asn1PerBitFieldPrinter Class Reference	38
1.15.1	Detailed Description	38
1.15.2	Constructor & Destructor Documentation	38
1.15.2.1	Asn1PerBitFieldPrinter	38
1.15.3	Member Function Documentation	38
1.15.3.1	Print	38
1.15.4	Member Data Documentation	38
1.15.4.1	mBitMask	38
1.15.4.2	mByteIndex	39
1.15.4.3	mCurrOctet	39
1.15.4.4	mEncodedMessage	39
1.15.4.5	mFmtBitCharIdx	39
1.15.4.6	mFormatBuffer	39
1.15.4.7	mPerMessageBuffer	39
1.16	Asn1PerDecodeBuffer Class Reference	40
1.16.1	Detailed Description	41
1.16.2	Constructor & Destructor Documentation	41
1.16.2.1	Asn1PerDecodeBuffer	41
1.16.2.2	Asn1PerDecodeBuffer	41
1.16.3	Member Function Documentation	41
1.16.3.1	BinDump	41
1.16.3.2	BinDump	41
1.16.3.3	ByteAlign	41
1.16.3.4	DecodeBit	42
1.16.3.5	DecodeBit	42
1.16.3.6	DecodeBitsToInt	42
1.16.3.7	DecodeBitsToInt	42
1.16.3.8	DecodeBitsToLong	43
1.16.3.9	DecodeBitsToLong	43
1.16.3.10	DecodeBitsToOctetArray	43
1.16.3.11	DecodeBitsToOctetArray	43
1.16.3.12	DecodeCharString	44
1.16.3.13	DecodeConsWholeNumber	44
1.16.3.14	DecodeConsWholeNumber	44
1.16.3.15	DecodeExtLength	44
1.16.3.16	DecodeInt	45
1.16.3.17	DecodeInt	45

1.16.3.18 DecodeLength	45
1.16.3.19 DecodeLength	45
1.16.3.20 DecodeSmallNonNegWholeNumber	46
1.16.3.21 IsAligned	46
1.16.3.22 MoveBitCursor	46
1.16.3.23 ReadByte	46
1.16.3.24 SetAligned	46
1.16.3.25 SetBuffer	46
1.16.3.26 SetInputStream	47
1.16.4 Member Data Documentation	47
1.16.4.1 mTraceHandler	47
1.16.5 Property Documentation	47
1.16.5.1 BitOffset	47
1.16.5.2 MsgBitCnt	47
1.16.5.3 TraceHandler	47
1.17 Asn1PerDecodeTraceHandler Class Reference	48
1.17.1 Detailed Description	48
1.17.2 Constructor & Destructor Documentation	48
1.17.2.1 Asn1PerDecodeTraceHandler	48
1.17.3 Member Function Documentation	48
1.17.3.1 Enable	48
1.17.3.2 Print	48
1.17.3.3 Reset	48
1.18 Asn1PerEncodeBuffer Class Reference	49
1.18.1 Detailed Description	50
1.18.2 Constructor & Destructor Documentation	50
1.18.2.1 Asn1PerEncodeBuffer	50
1.18.2.2 Asn1PerEncodeBuffer	50
1.18.3 Member Function Documentation	50
1.18.3.1 BinDump	50
1.18.3.2 ByteAlign	51
1.18.3.3 CheckSize	51
1.18.3.4 Copy	51
1.18.3.5 Copy	51
1.18.3.6 EncodeBit	51
1.18.3.7 EncodeBit	51
1.18.3.8 EncodeBits	52

1.18.3.9	EncodeBits	52
1.18.3.10	EncodeBits	52
1.18.3.11	EncodeCharString	52
1.18.3.12	EncodeConsWholeNumber	53
1.18.3.13	EncodeConsWholeNumber	53
1.18.3.14	EncodeInt	53
1.18.3.15	EncodeInt	53
1.18.3.16	EncodeInt	54
1.18.3.17	EncodeInt	54
1.18.3.18	EncodeLength	54
1.18.3.19	EncodeLength	54
1.18.3.20	EncodeLengthEOM	54
1.18.3.21	EncodeOctetString	55
1.18.3.22	EncodeOIDLengthAndValue	55
1.18.3.23	EncodeOpenType	55
1.18.3.24	EncodeOpenType	55
1.18.3.25	EncodeRelOIDLengthAndValue	55
1.18.3.26	EncodeSmallNonNegWholeNumber	56
1.18.3.27	GetInputStream	56
1.18.3.28	HexDump	56
1.18.3.29	IsAligned	56
1.18.3.30	Reset	56
1.18.3.31	ReverseBytes	56
1.18.3.32	SetAligned	57
1.18.3.33	ToString	57
1.18.3.34	Write	57
1.18.4	Member Data Documentation	57
1.18.4.1	mTraceHandler	57
1.18.5	Property Documentation	57
1.18.5.1	Buffer	57
1.18.5.2	ByteArrayInputStream	57
1.18.5.3	ByteIndex	57
1.18.5.4	MsgBitCnt	58
1.18.5.5	MsgByteCnt	58
1.18.5.6	MsgCopy	58
1.18.5.7	MsgLength	58
1.18.5.8	TraceHandler	58

1.19	Asn1PerEncodeTraceHandler Class Reference	59
1.19.1	Detailed Description	59
1.19.2	Constructor & Destructor Documentation	59
1.19.2.1	Asn1PerEncodeTraceHandler	59
1.19.3	Member Function Documentation	59
1.19.3.1	Enable	59
1.19.3.2	Print	59
1.19.3.3	Reset	59
1.20	Asn1PerInputStream Class Reference	60
1.20.1	Detailed Description	60
1.20.2	Constructor & Destructor Documentation	60
1.20.2.1	Asn1PerInputStream	60
1.20.3	Member Function Documentation	60
1.20.3.1	Available	60
1.20.3.2	Close	61
1.20.3.3	Mark	61
1.20.3.4	MarkSupported	61
1.20.3.5	Reset	61
1.20.3.6	Skip	61
1.21	Asn1PerMessageBuffer Interface Reference	62
1.21.1	Detailed Description	62
1.21.2	Member Function Documentation	62
1.21.2.1	ByteAlign	62
1.21.2.2	GetInputStream	62
1.21.2.3	IsAligned	62
1.21.3	Property Documentation	63
1.21.3.1	MsgBitCnt	63
1.21.3.2	TraceHandler	63
1.22	Asn1PerOutputStream Class Reference	64
1.22.1	Detailed Description	65
1.22.2	Constructor & Destructor Documentation	65
1.22.2.1	Asn1PerOutputStream	65
1.22.2.2	Asn1PerOutputStream	65
1.22.3	Member Function Documentation	65
1.22.3.1	AddCaptureBuffer	65
1.22.3.2	BinDump	65
1.22.3.3	BinDump	66

1.22.3.4	ByteAlign	66
1.22.3.5	Close	66
1.22.3.6	EncodeBit	66
1.22.3.7	EncodeBit	66
1.22.3.8	EncodeBits	66
1.22.3.9	EncodeBits	67
1.22.3.10	EncodeBits	67
1.22.3.11	EncodeCharString	67
1.22.3.12	EncodeConsWholeNumber	68
1.22.3.13	EncodeConsWholeNumber	68
1.22.3.14	EncodeInt	68
1.22.3.15	EncodeInt	69
1.22.3.16	EncodeInt	69
1.22.3.17	EncodeInt	69
1.22.3.18	EncodeLength	70
1.22.3.19	EncodeLength	70
1.22.3.20	EncodeLengthEOM	70
1.22.3.21	EncodeOctetString	71
1.22.3.22	EncodeOIDLengthAndValue	71
1.22.3.23	EncodeOpenType	71
1.22.3.24	EncodeRelOIDLengthAndValue	71
1.22.3.25	EncodeSmallNonNegWholeNumber	72
1.22.3.26	Flush	72
1.22.3.27	RemoveCaptureBuffer	72
1.22.3.28	Write	72
1.22.3.29	Write	73
1.22.3.30	WriteByte	73
1.22.3.31	WriteByte	73
1.22.4	Member Data Documentation	73
1.22.4.1	mTraceHandler	73
1.22.5	Property Documentation	73
1.22.5.1	Aligned	73
1.22.5.2	TraceHandler	74
1.23	Asn1PerOutputStreamTraceHandler Class Reference	75
1.23.1	Detailed Description	75
1.23.2	Constructor & Destructor Documentation	75
1.23.2.1	Asn1PerOutputStreamTraceHandler	75

1.23.3	Member Function Documentation	75
1.23.3.1	Enable	75
1.23.3.2	Print	75
1.23.3.3	Reset	75
1.23.3.4	ResetTrace	76
1.24	Asn1PerTraceHandler Class Reference	77
1.24.1	Detailed Description	77
1.24.2	Constructor & Destructor Documentation	77
1.24.2.1	Asn1PerTraceHandler	77
1.24.3	Member Function Documentation	77
1.24.3.1	AddElemName	77
1.24.3.2	Enable	78
1.24.3.3	NewBitField	78
1.24.3.4	Print	78
1.24.3.5	RemoveLastElemName	78
1.24.3.6	Reset	78
1.24.3.7	SetBitCount	78
1.24.3.8	SetBitOffset	79
1.24.4	Member Data Documentation	79
1.24.4.1	mBitFieldList	79
1.24.5	Property Documentation	79
1.24.5.1	BitFieldList	79
1.25	Asn1PerUtil Class Reference	80
1.25.1	Detailed Description	80
1.25.2	Member Function Documentation	80
1.25.2.1	GetMsgBitCnt	80
1.26	Asn1SetDuplicateException Class Reference	81
1.26.1	Detailed Description	81
1.26.2	Constructor & Destructor Documentation	81
1.26.2.1	Asn1SetDuplicateException	81
1.27	Asn1TaggedEventHandler Interface Reference	82
1.27.1	Detailed Description	82
1.27.2	Member Function Documentation	82
1.27.2.1	Contents	82
1.27.2.2	EndElement	82
1.27.2.3	StartElement	82
1.28	Asn1TagMatchFailedException Class Reference	84

1.28.1	Detailed Description	84
1.28.2	Constructor & Destructor Documentation	84
1.28.2.1	Asn1TagMatchFailedException	84
1.28.2.2	Asn1TagMatchFailedException	84
1.29	Asn1XerBase64OctetString Class Reference	85
1.29.1	Detailed Description	85
1.29.2	Constructor & Destructor Documentation	85
1.29.2.1	Asn1XerBase64OctetString	85
1.29.2.2	Asn1XerBase64OctetString	85
1.29.2.3	Asn1XerBase64OctetString	85
1.29.2.4	Asn1XerBase64OctetString	86
1.29.3	Member Function Documentation	86
1.29.3.1	DecodeXML	86
1.29.3.2	Encode	86
1.29.3.3	Encode	86
1.30	Asn1XerDecodeBuffer Class Reference	87
1.30.1	Detailed Description	87
1.30.2	Constructor & Destructor Documentation	87
1.30.2.1	Asn1XerDecodeBuffer	87
1.30.3	Member Data Documentation	87
1.30.3.1	mInputSource	87
1.30.4	Property Documentation	87
1.30.4.1	InputSource	87
1.31	Asn1XerElemInfo Class Reference	88
1.31.1	Detailed Description	88
1.31.2	Constructor & Destructor Documentation	88
1.31.2.1	Asn1XerElemInfo	88
1.31.3	Member Function Documentation	88
1.31.3.1	Equals	88
1.31.3.2	GetHashCode	88
1.31.4	Property Documentation	89
1.31.4.1	ID	89
1.31.4.2	Optional	89
1.32	Asn1XerEncodeBuffer Class Reference	90
1.32.1	Detailed Description	90
1.32.2	Constructor & Destructor Documentation	91
1.32.2.1	Asn1XerEncodeBuffer	91

1.32.2.2	Asn1XerEncodeBuffer	91
1.32.2.3	Asn1XerEncodeBuffer	91
1.32.3	Member Function Documentation	91
1.32.3.1	BinDump	91
1.32.3.2	CheckSize	91
1.32.3.3	Copy	92
1.32.3.4	Copy	92
1.32.3.5	Copy	92
1.32.3.6	Copy	92
1.32.3.7	DecrLevel	92
1.32.3.8	EncodeBinStrValue	92
1.32.3.9	EncodeByte	93
1.32.3.10	EncodeData	93
1.32.3.11	EncodeEmptyElement	93
1.32.3.12	EncodeEndDocument	93
1.32.3.13	EncodeEndElement	93
1.32.3.14	EncodeHexStrValue	93
1.32.3.15	EncodeNamedValue	94
1.32.3.16	EncodeNamedValueElement	94
1.32.3.17	EncodeObjectId	94
1.32.3.18	EncodeRealValue	94
1.32.3.19	EncodeStartDocument	94
1.32.3.20	EncodeStartElement	95
1.32.3.21	GetInputStream	95
1.32.3.22	IncrLevel	95
1.32.3.23	Indent	95
1.32.3.24	Reset	95
1.32.3.25	Write	95
1.32.4	Property Documentation	95
1.32.4.1	Buffer	95
1.32.4.2	Canonical	96
1.32.4.3	MsgCopy	96
1.32.4.4	MsgLength	96
1.32.4.5	State	96
1.33	Asn1XerEncoder Interface Reference	97
1.33.1	Detailed Description	97
1.33.2	Member Function Documentation	97

1.33.2.1	EncodeEmptyElement	97
1.33.2.2	EncodeEndElement	97
1.33.2.3	EncodeNamedValue	98
1.33.2.4	EncodeRealValue	98
1.33.2.5	EncodeStartElement	98
1.33.3	Property Documentation	98
1.33.3.1	State	98
1.34	Asn1XerEncoder_Fields Struct Reference	99
1.34.1	Detailed Description	99
1.34.2	Member Data Documentation	99
1.34.2.1	XERDATA	99
1.34.2.2	XEREND	99
1.34.2.3	XERINDENT	99
1.34.2.4	XERINIT	99
1.34.2.5	XERSTART	99
1.35	Asn1XerOpenType Class Reference	100
1.35.1	Detailed Description	100
1.35.2	Constructor & Destructor Documentation	100
1.35.2.1	Asn1XerOpenType	100
1.35.2.2	Asn1XerOpenType	100
1.35.2.3	Asn1XerOpenType	101
1.35.2.4	Asn1XerOpenType	101
1.35.3	Member Function Documentation	101
1.35.3.1	Decode	101
1.35.3.2	Decode	101
1.35.3.3	Encode	101
1.35.3.4	Encode	101
1.35.3.5	Encode	102
1.35.3.6	Encode	102
1.35.3.7	Encode	102
1.35.3.8	GetSaxHandler	102
1.35.3.9	GetSaxHandler	103
1.35.3.10	ToString	103
1.35.4	Member Data Documentation	103
1.35.4.1	named	103
1.36	Asn1XerOutputStream Class Reference	104
1.36.1	Detailed Description	104

1.36.2	Constructor & Destructor Documentation	104
1.36.2.1	Asn1XerOutputStream	104
1.36.2.2	Asn1XerOutputStream	105
1.36.3	Member Function Documentation	105
1.36.3.1	Copy	105
1.36.3.2	Copy	105
1.36.3.3	Copy	105
1.36.3.4	Copy	106
1.36.3.5	DecrLevel	106
1.36.3.6	EncodeBinStrValue	106
1.36.3.7	EncodeByte	106
1.36.3.8	EncodeData	107
1.36.3.9	EncodeEmptyElement	107
1.36.3.10	EncodeEndDocument	107
1.36.3.11	EncodeEndElement	107
1.36.3.12	EncodeHexStrValue	108
1.36.3.13	EncodeNamedValue	108
1.36.3.14	EncodeNamedValueElement	108
1.36.3.15	EncodeObjectId	108
1.36.3.16	EncodeRealValue	109
1.36.3.17	EncodeStartDocument	109
1.36.3.18	EncodeStartElement	109
1.36.3.19	IncrLevel	109
1.36.3.20	Indent	109
1.36.3.21	Write	110
1.36.4	Property Documentation	110
1.36.4.1	Canonical	110
1.36.4.2	State	110
1.37	Asn1XerSaxHandler Class Reference	111
1.37.1	Detailed Description	111
1.37.2	Constructor & Destructor Documentation	111
1.37.2.1	Asn1XerSaxHandler	111
1.37.3	Member Function Documentation	112
1.37.3.1	Error	112
1.37.3.2	FatalError	112
1.37.3.3	Init	112
1.37.3.4	Warning	112

1.37.4	Member Data Documentation	113
1.37.4.1	mCurrElemID	113
1.37.4.2	mCurrState	113
1.37.4.3	mLevel	113
1.37.4.4	XERDATA	113
1.37.4.5	XEREND	113
1.37.4.6	XERINIT	113
1.37.4.7	XERSTART	113
1.37.4.8	XERUNKNOWN	113
1.37.5	Property Documentation	113
1.37.5.1	Complete	113
1.37.5.2	State	113
1.38	Asn1XerUtil Class Reference	114
1.38.1	Detailed Description	114
1.38.2	Member Function Documentation	114
1.38.2.1	EncodeReal	114
1.38.2.2	NormalizedRealValueToString	114
1.39	Asn1XmlEncodeBuffer Class Reference	115
1.39.1	Detailed Description	116
1.39.2	Constructor & Destructor Documentation	116
1.39.2.1	Asn1XmlEncodeBuffer	116
1.39.2.2	Asn1XmlEncodeBuffer	116
1.39.3	Member Function Documentation	116
1.39.3.1	BinDump	116
1.39.3.2	CheckSize	116
1.39.3.3	Copy	116
1.39.3.4	Copy	117
1.39.3.5	Copy	117
1.39.3.6	Copy	117
1.39.3.7	DecrLevel	117
1.39.3.8	EncodeAttr	117
1.39.3.9	EncodeBinStrValue	117
1.39.3.10	EncodeByte	118
1.39.3.11	EncodeData	118
1.39.3.12	EncodeDoubleValue	118
1.39.3.13	EncodeEmptyElement	118
1.39.3.14	EncodeEndDocument	118

1.39.3.15	EncodeEndElement	119
1.39.3.16	EncodeEndElement	119
1.39.3.17	EncodeHexStrValue	119
1.39.3.18	EncodeNamedValue	119
1.39.3.19	EncodeNamedValueElement	119
1.39.3.20	EncodeObjectId	120
1.39.3.21	EncodeStartDocument	120
1.39.3.22	EncodeStartElement	120
1.39.3.23	EncodeXSIAttrs	120
1.39.3.24	GetInputStream	120
1.39.3.25	IncrLevel	120
1.39.3.26	Indent	120
1.39.3.27	Reset	121
1.39.3.28	SetXSIAttrs	121
1.39.3.29	Write	121
1.39.4	Property Documentation	121
1.39.4.1	Buffer	121
1.39.4.2	Helper	121
1.39.4.3	MsgCopy	121
1.39.4.4	MsgLength	121
1.39.4.5	State	121
1.40	Asn1XmlOutputStream Class Reference	122
1.40.1	Detailed Description	122
1.40.2	Constructor & Destructor Documentation	123
1.40.2.1	Asn1XmlOutputStream	123
1.40.2.2	Asn1XmlOutputStream	123
1.40.2.3	Asn1XmlOutputStream	123
1.40.3	Member Function Documentation	123
1.40.3.1	Copy	123
1.40.3.2	Copy	123
1.40.3.3	Copy	124
1.40.3.4	Copy	124
1.40.3.5	DecrLevel	124
1.40.3.6	EncodeAttr	124
1.40.3.7	EncodeBinStrValue	124
1.40.3.8	EncodeByte	125
1.40.3.9	EncodeData	125

1.40.3.10 EncodeDoubleValue	125
1.40.3.11 EncodeEmptyElement	125
1.40.3.12 EncodeEndDocument	126
1.40.3.13 EncodeEndElement	126
1.40.3.14 EncodeEndElement	126
1.40.3.15 EncodeHexStrValue	126
1.40.3.16 EncodeNamedValue	126
1.40.3.17 EncodeNamedValueElement	127
1.40.3.18 EncodeObjectId	127
1.40.3.19 EncodeStartDocument	127
1.40.3.20 EncodeStartElement	127
1.40.3.21 EncodeXSIAttrs	127
1.40.3.22 IncrLevel	127
1.40.3.23 Indent	128
1.40.3.24 SetXSIAttrs	128
1.40.3.25 Write	128
1.40.4 Property Documentation	128
1.40.4.1 Helper	128
1.40.4.2 State	128
1.41 Asn1XmlUtil Class Reference	129
1.41.1 Detailed Description	129
1.41.2 Member Function Documentation	129
1.41.2.1 EncodeDouble	129
1.41.2.2 EncodeDouble	129
1.41.2.3 EncodeNSAttrs	129
1.41.2.4 GetMinusZero	130
1.41.2.5 GetXMLString	130
1.41.2.6 IsMinusZero	130
1.41.2.7 KeepNullsInString	130
1.41.2.8 TokenizeXsdList	131
1.42 SaxHandler Class Reference	132
1.42.1 Detailed Description	132
1.42.2 Member Function Documentation	132
1.42.2.1 Characters	132
1.42.2.2 EndElement	132
1.42.2.3 StartElement	132
1.43 XmlAttribute Class Reference	134

1.43.1	Detailed Description	134
1.43.2	Constructor & Destructor Documentation	134
1.43.2.1	XmlAttribute	134
1.43.3	Member Data Documentation	134
1.43.3.1	att_fullName	134
1.43.3.2	att_localName	134
1.43.3.3	att_type	134
1.43.3.4	att_URI	135
1.43.3.5	att_value	135
1.44	XmlAttribute Class Reference	136
1.44.1	Detailed Description	136
1.44.2	Constructor & Destructor Documentation	136
1.44.2.1	XmlAttribute	136
1.44.2.2	XmlAttribute	137
1.44.3	Member Function Documentation	137
1.44.3.1	Add	137
1.44.3.2	Clear	137
1.44.3.3	GetFullName	137
1.44.3.4	GetIndex	137
1.44.3.5	GetIndex	138
1.44.3.6	GetLength	138
1.44.3.7	GetLocalName	138
1.44.3.8	GetQName	138
1.44.3.9	GetType	138
1.44.3.10	GetType	139
1.44.3.11	GetType	139
1.44.3.12	GetURI	139
1.44.3.13	GetValue	139
1.44.3.14	GetValue	140
1.44.3.15	GetValue	140
1.44.3.16	RemoveAttribute	140
1.44.3.17	RemoveAttribute	140
1.44.3.18	SetAttribute	140
1.44.3.19	SetAttributes	141
1.44.3.20	SetFullName	141
1.44.3.21	SetLocalName	141
1.44.3.22	SetType	141

1.44.3.23	SetURI	141
1.44.3.24	SetValue	141
1.45	XmlSaxContentHandler Interface Reference	142
1.45.1	Detailed Description	142
1.45.2	Member Function Documentation	142
1.45.2.1	Characters	142
1.45.2.2	EndDocument	142
1.45.2.3	EndElement	142
1.45.2.4	EndPrefixMapping	143
1.45.2.5	IgnorableWhitespace	143
1.45.2.6	ProcessingInstruction	143
1.45.2.7	SetDocumentLocator	143
1.45.2.8	SkippedEntity	144
1.45.2.9	StartDocument	144
1.45.2.10	StartElement	144
1.45.2.11	StartPrefixMapping	144
1.46	XmlSaxDefaultHandler Class Reference	145
1.46.1	Detailed Description	145
1.46.2	Member Function Documentation	145
1.46.2.1	Characters	145
1.46.2.2	EndDocument	145
1.46.2.3	EndElement	146
1.46.2.4	EndPrefixMapping	146
1.46.2.5	Error	146
1.46.2.6	FatalError	146
1.46.2.7	IgnorableWhitespace	146
1.46.2.8	ProcessingInstruction	147
1.46.2.9	ResolveEntity	147
1.46.2.10	SetDocumentLocator	147
1.46.2.11	SkippedEntity	147
1.46.2.12	StartDocument	148
1.46.2.13	StartElement	148
1.46.2.14	StartPrefixMapping	148
1.46.2.15	Warning	148
1.47	XmlSaxEntityResolver Interface Reference	149
1.47.1	Detailed Description	149
1.47.2	Member Function Documentation	149

1.47.2.1	ResolveEntity	149
1.48	XmlSaxErrorHandler Interface Reference	150
1.48.1	Detailed Description	150
1.48.2	Member Function Documentation	150
1.48.2.1	Error	150
1.48.2.2	FatalError	150
1.48.2.3	Warning	150
1.49	XmlSaxLexicalHandler Interface Reference	151
1.49.1	Detailed Description	151
1.49.2	Member Function Documentation	151
1.49.2.1	Comment	151
1.49.2.2	EndCDATA	151
1.49.2.3	EndDTD	151
1.49.2.4	EndEntity	151
1.49.2.5	StartCDATA	151
1.49.2.6	StartDTD	152
1.49.2.7	StartEntity	152
1.50	XmlSaxLocator Interface Reference	153
1.50.1	Detailed Description	153
1.50.2	Member Function Documentation	153
1.50.2.1	GetColumnNumber	153
1.50.2.2	GetLineNumber	153
1.50.2.3	GetPublicId	153
1.50.2.4	GetSystemId	154
1.51	XmlSaxLocatorImpl Class Reference	155
1.51.1	Detailed Description	155
1.51.2	Constructor & Destructor Documentation	155
1.51.2.1	XmlSaxLocatorImpl	155
1.51.2.2	XmlSaxLocatorImpl	155
1.51.3	Member Function Documentation	155
1.51.3.1	GetColumnNumber	155
1.51.3.2	GetLineNumber	156
1.51.3.3	GetPublicId	156
1.51.3.4	GetSystemId	156
1.51.3.5	SetColumnNumber	156
1.51.3.6	SetLineNumber	156
1.51.3.7	SetPublicId	157

1.51.3.8	SetSystemId	157
1.52	XmlSaxParser Class Reference	158
1.52.1	Detailed Description	158
1.52.2	Constructor & Destructor Documentation	159
1.52.2.1	XmlSaxParser	159
1.52.3	Member Function Documentation	159
1.52.3.1	CloneInstance	159
1.52.3.2	GetContentHandler	159
1.52.3.3	GetEntityResolver	159
1.52.3.4	GetErrorHandler	159
1.52.3.5	NewInstance	159
1.52.3.6	Parse	160
1.52.3.7	Parse	160
1.52.3.8	Parse	160
1.52.3.9	Parse	160
1.52.3.10	Parse	160
1.52.3.11	Parse	160
1.52.3.12	Parse	161
1.52.3.13	Parse	161
1.52.3.14	Parse	161
1.52.3.15	Parse	161
1.52.3.16	SetContentHandler	161
1.52.3.17	SetDocumentHandler	162
1.52.3.18	SetEntityResolver	162
1.52.3.19	SetErrorHandler	162
1.52.4	Member Data Documentation	162
1.52.4.1	callBackHandler	162
1.52.4.2	entityResolver	162
1.52.4.3	errorHandler	162
1.52.4.4	lexical	162
1.52.4.5	locator	162
1.52.4.6	namespaceAllowed	162
1.52.4.7	parserFileName	163
1.52.4.8	reader	163
1.52.5	Property Documentation	163
1.52.5.1	NamespaceAllowed	163
1.53	XmlSaxParserAdapter Class Reference	164

1.53.1	Detailed Description	164
1.53.2	Member Function Documentation	164
1.53.2.1	Characters	164
1.53.2.2	EndDocument	164
1.53.2.3	EndElement	164
1.53.2.4	EndPrefixMapping	165
1.53.2.5	IgnorableWhitespace	165
1.53.2.6	ProcessingInstruction	165
1.53.2.7	SetDocumentLocator	165
1.53.2.8	SkippedEntity	166
1.53.2.9	StartDocument	166
1.53.2.10	StartElement	166
1.53.2.11	StartPrefixMapping	166
1.54	XmlSource Class Reference	167
1.54.1	Detailed Description	167
1.54.2	Constructor & Destructor Documentation	167
1.54.2.1	XmlSource	167
1.54.2.2	XmlSource	167
1.54.2.3	XmlSource	167
1.54.2.4	XmlSource	167
1.54.3	Property Documentation	168
1.54.3.1	Bytes	168
1.54.3.2	Characters	168
1.54.3.3	Uri	168

Chapter 1

Class Documentation

1.1 Asn1BerDecodeBuffer Class Reference

Inherited by [Asn1BerInputStream](#), and [Asn1DerDecodeBuffer](#).

Public Member Functions

- [Asn1BerDecodeBuffer](#) (System.IO.Stream istream)
- [Asn1BerDecodeBuffer](#) (byte[] msgdata)
- int [DecodeEnumValue](#) (Asn1Tag tag, bool explicitTagging, int implicitLength)
- int [DecodeEnumValue](#) (bool explicitTagging, int implicitLength)
- virtual int [DecodeLength](#) ()
- virtual byte[] [DecodeOpenType](#) (bool saveData)
- virtual byte[] [DecodeOpenType](#) ()
- virtual void [DecodeTag](#) (Asn1Tag tag)
- virtual int [DecodeTagAndLength](#) (Asn1Tag tag)
- virtual bool [MatchTag](#) (Asn1Tag tag)
- virtual bool [MatchTag](#) (Asn1Tag tag, Asn1Tag parsedTag, IntHolder parsedLen)
- virtual bool [MatchTag](#) (short tagClass, short tagForm, int tagIDCode, Asn1Tag parsedTag, IntHolder parsedLen)
- virtual void [Parse](#) ([Asn1TaggedEventHandler](#) handler)
- virtual Asn1Tag [PeekTag](#) ()
- virtual void [PeekTag](#) (Asn1Tag parsedTag)
- override int [ReadByte](#) ()

Static Public Member Functions

- static int [CalcIndefLen](#) (byte[] data, int offset, int len)

Protected Member Functions

- internal void [MovePastEOC](#) (bool saveData)

Properties

- virtual Asn1Tag [LastTag](#) [get]

1.1.1 Detailed Description

This class handles the decoding of ASN.1 messages as specified in the Basic Encoding Rules (BER) as documented in the ITU-T X.690 standard.

1.1.2 Constructor & Destructor Documentation

1.1.2.1 Asn1BerDecodeBuffer (byte[] *msgdata*)

This constructor creates a BER Decode buffer object that references an encoded ASN.1 message.

Parameters

msgdata Byte array containing an encoded ASN.1 message.

1.1.2.2 Asn1BerDecodeBuffer (System.IO.Stream *istream*)

This constructor creates a BER Decode buffer object that references an encoded ASN.1 message. In this case, the message is passed in using an System.IO.Stream object.

Parameters

istream Input stream containing an encoded ASN.1 message.

1.1.3 Member Function Documentation

1.1.3.1 static int CalcIndefLen (byte[] *data*, int *offset*, int *len*) [static]

This function calculates the actual length of an indefinite length message component.

Parameters

data Buffer with the indefinite length message component.

offset The start offset in the array

len Length of the buffer (beginning from the offset)

Returns

calculated length

1.1.3.2 int DecodeEnumValue (Asn1Tag *tag*, bool *explicitTagging*, int *implicitLength*)

This method decodes an enumerated value from the buffer.

Parameters

tag An Asn1Tag value for enumerated values that are tagged other than UNIVERSAL 10.

explicitTagging A flag that indicates the element is explicitly tagged.

implicitLength The length of the contents if implicitly tagged.

Returns

The decoded integer value.

1.1.3.3 int DecodeEnumValue (bool *explicitTagging*, int *implicitLength*)

This method decodes an enumerated value from the buffer.

Parameters

explicitTagging A flag that indicates the element is explicitly tagged.

implicitLength The length of the contents if implicitly tagged.

Returns

The decoded integer value.

1.1.3.4 virtual int DecodeLength () [virtual]

This method decodes a length value.

Returns

Decoded length value

1.1.3.5 virtual byte [] DecodeOpenType (bool *saveData*) [virtual]

This method decodes an ASN.1 BER open type value. This is a fully encoded message component of any type. This version of the method allows the option of saving or discarding the open type data.

Parameters

saveData True if data should be captured and returned

Returns

Reference to byte array containing component.

1.1.3.6 virtual byte [] DecodeOpenType () [virtual]

This method decodes an ASN.1 BER open type value. This is a fully encoded message component of any type. The component is captured in the Decode capture buffer and a reference to a byte array is returned containing the component.

Returns

Reference to byte array containing component.

1.1.3.7 virtual void DecodeTag (Asn1Tag *tag*) [virtual]

This method decodes a tag value.

Parameters

tag Tag object to receive decoded tag fields.

Returns

status value (see Asn1Status.java)

1.1.3.8 virtual int DecodeTagAndLength (Asn1Tag *tag*) [virtual]

This method decodes a tag and length value.

Parameters

tag Tag object to receive decoded tag fields.

Returns

Decoded length value.

1.1.3.9 virtual bool MatchTag (Asn1Tag *tag*) [virtual]

This overloaded version of MatchTag will just test for a match and not return parsed tag and length values

Parameters

tag Tag value to be matched.

Returns

True if given tag matches tag at Decode cursor

1.1.3.10 virtual bool MatchTag (Asn1Tag *tag*, Asn1Tag *parsedTag*, IntHolder *parsedLen*) [virtual]

This overloaded version of MatchTag allows the tag value to be matched to be passed using an Asn1Tag object.

Parameters

tag Tag value to be matched.

parsedTag Holder object to receive parsed tag value

parsedLen Holder object to receive parsed length value

Returns

True if given tag matches tag at Decode cursor

1.1.3.11 virtual bool MatchTag (short *tagClass*, short *tagForm*, int *tagIDCode*, Asn1Tag *parsedTag*, IntHolder *parsedLen*) [virtual]

This method decodes the next tag value and checks for a match with the given tag value. If the match is successful, the Decode cursor will be positioned at the contents field; otherwise, it will be reset to point to the start of the tag field.

Parameters

tagClass Class value of tag to match

tagForm Form value of tag to match

tagIDCode ID code of tag to match

parsedTag Holder object to receive parsed tag value

parsedLen Holder object to receive parsed length value

Returns

True if given tag matches tag at Decode cursor

1.1.3.12 internal void MovePastEOC (bool *saveData*) [protected]

This method skips or saves the data/bytes of the current tag in this DecodeBuffer. If current tag has indefinite length, than index will moved to end of the indifinite length. If tag has definite length, than that many bytes are moved.

Parameters

saveData True if data should be captured

1.1.3.13 virtual void Parse (Asn1TaggedEventHandler *handler*) [virtual]

This method parses the complete message and invokes the event handler callback methods as various items are encountered.

Parameters

handler Object implementing the Asn1EventHandler interface.

Returns

Status value

1.1.3.14 virtual Asn1Tag PeekTag () [virtual]

This overloaded version of the PeekTag method will return a reference to a newly created tag object.

Returns

Parsed tag object value reference

1.1.3.15 virtual void PeekTag (Asn1Tag *parsedTag*) [virtual]

This method will Parse and return the next tag in the Decode stream without advancing the Decode cursor.

Parameters

parsedTag Holder object to receive parsed tag value

1.1.3.16 override int ReadByte ()

This method returns the next available 8-bit value from the input stream. It is implemented differently for BER/DER and PER to take into account odd alignments in PER.

Returns

Next 8-bit byte value from input stream

1.1.4 Property Documentation

1.1.4.1 virtual Asn1Tag LastTag [get]

Gets the last tag parsed within this decode buffer object.

Value: Last parsed tag object reference

1.2 Asn1BerDecodeContext Class Reference

Public Member Functions

- [Asn1BerDecodeContext](#) ([Asn1BerDecodeBuffer](#) decodeBuffer, int elemLength)
- virtual bool [Expired](#) ()
- virtual bool [MatchElemTag](#) ([Asn1Tag](#) tag, [IntHolder](#) parsedLen, bool advance)
- virtual bool [MatchElemTag](#) (short tagClass, short tagForm, int tagIDCode, [IntHolder](#) parsedLen, bool advance)

Protected Attributes

- internal int [mDecBufByteCount](#)
- internal [Asn1BerDecodeBuffer](#) [mDecodeBuffer](#)
- internal int [mElemLength](#)
- internal bool [mExplicitTagging](#)
- internal [Asn1Tag](#) [mTagHolder](#)

1.2.1 Detailed Description

This class is mainly for internal use by the compiler to keep track of where nested constructed elements (SEQUENCE, SET, CHOICE, etc.) begin and end.

1.2.2 Constructor & Destructor Documentation

1.2.2.1 [Asn1BerDecodeContext](#) ([Asn1BerDecodeBuffer](#) *decodeBuffer*, int *elemLength*)

The constructor initializes all internal working variables.

Parameters

decodeBuffer Reference to current Decode buffer method.

elemLength Length of the element being tracked.

1.2.3 Member Function Documentation

1.2.3.1 virtual bool [Expired](#) () [virtual]

This method will determine if a decoding context is expired. A context is defined to be the wrapper in which a set of elements or a primitive data type resides..

Returns

True if at the end of the context block

1.2.3.2 virtual bool [MatchElemTag](#) ([Asn1Tag](#) *tag*, [IntHolder](#) *parsedLen*, bool *advance*) [virtual]

This method will attempt to match the next element tag in a constructed type with the expected value. It will check to see if the context is expired and, if not, will match the given tag with the expected tag. The Decode cursor is advanced if the boolean advance argument is true.

Parameters

tag Tag object representing tag to be matched.
parsedLen Holder object to receive parsed length value
advance True if Decode cursor to be advanced.

Returns

True, if the tag is matched

1.2.3.3 virtual bool MatchElemTag (short tagClass, short tagForm, int tagIDCode, IntHolder parsedLen, bool advance) [virtual]

This method will attempt to match the next element tag in a constructed type with the expected value. It will check to see if the context is expired and, if not, will match the given tag with the expected tag. The Decode cursor is advanced if the boolean advance argument is true.

Parameters

tagClass Class value of tag to match
tagForm Form value of tag to match
tagIDCode ID code of tag to match
parsedLen Holder object to receive parsed length value
advance True if Decode cursor to be advanced.

Returns

True, if the tag is matched

1.2.4 Member Data Documentation

1.2.4.1 internal int mDecBufByteCount [protected]

This variable is used to keep track of the current byte count in the Decode buffer.

1.2.4.2 internal Asn1BerDecodeBuffer mDecodeBuffer [protected]

This variable holds a reference to the BER Decode buffer object that is being used to Decode the entire message component.

1.2.4.3 internal int mElemLength [protected]

This variable holds the constructed element length for the context component.

1.2.4.4 internal bool mExplicitTagging [protected]

This boolean flag variable indicates if explicit tagging is in effect for this element.

1.2.4.5 internal Asn1Tag mTagHolder [protected]

This variable holds the current parsed tag for matching operations.

1.3 Asn1BerEncodeBuffer Class Reference

Inherited by [Asn1DerEncodeBuffer](#).

Public Member Functions

- [Asn1BerEncodeBuffer](#) (int sizeIncrement)
- [Asn1BerEncodeBuffer](#) ()
- virtual void [BinDump](#) ()
- override void [BinDump](#) (System.IO.StreamWriter outs, System.String varName)
- virtual void [Copy](#) (System.String data)
- virtual void [Copy](#) (byte[] data, int startOffset, int length)
- override void [Copy](#) (byte[] data)
- override void [Copy](#) (byte data)
- virtual int [EncodeIdentifier](#) (int ident)
- virtual int [EncodeIntValue](#) (long ivalue)
- virtual int [EncodeLength](#) (int len)
- virtual int [EncodeTag](#) (Asn1Tag tag)
- virtual int [EncodeTagAndLength](#) (short tagClass, short tagForm, int tagIDCode, int len)
- virtual int [EncodeTagAndLength](#) (Asn1Tag tag, int len)
- virtual int [EncodeUnsignedBinaryNumber](#) (long ivalue)
- override System.IO.Stream [GetInputStream](#) ()
- override void [Reset](#) ()
- override System.String [ToString](#) ()
- virtual int [TrimBitString](#) (Asn1BitString bitstr)
- override void [Write](#) (System.IO.Stream outs)

Protected Member Functions

- internal override void [CheckSize](#) (int bytesRequired)

Properties

- virtual System.IO.MemoryStream [ByteArrayInputStream](#) [get]
- override byte[] [MsgCopy](#) [get]
- override int [MsgLength](#) [get]

1.3.1 Detailed Description

This class handles the encoding of ASN.1 messages as specified in the Basic Encoding Rules (BER) as specified in the ITU-T X.690 standard. A reference to an object of this type is passed to each of the ASN.1 type encode methods involved in encoding a particular message type.

1.3.2 Constructor & Destructor Documentation

1.3.2.1 Asn1BerEncodeBuffer ()

This constructor creates a BER encode buffer object with the default size increment. Whenever the buffer becomes full, the buffer will be expanded by the sizeIncrement size.

1.3.2.2 Asn1BerEncodeBuffer (int sizeIncrement)

This constructor creates a BER encode buffer object with the given size increment. Whenever the buffer becomes full, the buffer will be expanded by the sizeIncrement size. This size should be large enough to prevent resizing in normal operation.

Parameters

sizeIncrement The initial size in bytes of an encode buffer. If the buffer becomes full, it will be expanded by the amount.

1.3.3 Member Function Documentation

1.3.3.1 virtual void BinDump () [virtual]

This method invokes an overloaded version of BinDump to dump the encoded message to standard output.

1.3.3.2 override void BinDump (System.IO.StreamWriter outs, System.String varName)

This method dumps the encoded message in a human-readable format showing tags and contents to the given output stream.

Parameters

outs StreamWriter where dump will be printed

varName Name of the Decoded ASN1 Type

1.3.3.3 internal override void CheckSize (int bytesRequired) [protected]

This method determines if the encode buffer can hold the requested number of bytes. If not, the buffer is expanded.

Parameters

bytesRequired Number of required bytes.

1.3.3.4 virtual void Copy (System.String data) [virtual]

This method copies a character string into the encode buffer

Parameters

data String to copy to the encode buffer

1.3.3.5 virtual void Copy (byte[] data, int startOffset, int length) [virtual]

This method copies multiple bytes to the encode buffer

Parameters

data Array of bytes to copy to the encode buffer

startOffset The byte offset in array at which to begin copy.

length Number of bytes to copy

1.3.3.6 **override void Copy (byte[] data)**

This method copies multiple bytes to the encode buffer

Parameters

data Array of bytes to copy to the encode buffer

1.3.3.7 **override void Copy (byte data)**

This method copies a single byte to the encode buffer.

Parameters

data The byte value to copy

1.3.3.8 **virtual int EncodeIdentifier (int ident) [virtual]**

This method encodes an ASN.1 identifier value such as the ones used in a tags or object identifiers.

Parameters

ident The identifier to be encoded.

Returns

Length of the encoded component in octets.

1.3.3.9 **virtual int EncodeIntValue (long ivalue) [virtual]**

This method encodes an ASN.1 integer value's contents according to the ASN.1 Basic Encoding Rules (BER)..

Parameters

ivalue Integer value to encode

Returns

Length of encoded component

1.3.3.10 **virtual int EncodeLength (int len) [virtual]**

This method encodes a length value.

Parameters

len The length to be encoded.

Returns

Length of encoded component

1.3.3.11 virtual int EncodeTag (Asn1Tag tag) [virtual]

This method encodes a tag value.

Parameters

tag The tag to be encoded.

Returns

Length of component or negative status value

1.3.3.12 virtual int EncodeTagAndLength (short tagClass, short tagForm, int tagIDCode, int len) [virtual]

This overloaded version of encodeTagAndLength allows tag value components to be specified instead of an Asn1Tag object

Parameters

tagClass The class of the tag to be encoded.

tagForm The form of the tag to be encoded.

tagIDCode The ID code of the tag to be encoded.

len The length to be encoded.

Returns

status value (see Asn1Status.java)

1.3.3.13 virtual int EncodeTagAndLength (Asn1Tag tag, int len) [virtual]

This method encodes both a tag and length value.

Parameters

tag The tag to be encoded.

len The length to be encoded.

Returns

Length of encoded component

1.3.3.14 virtual int EncodeUnsignedBinaryNumber (long ivalue) [virtual]

This method encodes an integer value as unsigned binary number according to the ASN.1 Basic Encoding Rules (BER)..

Parameters

ivalue Integer value to encode

Returns

Length of encoded component

1.3.3.15 override System.IO.Stream GetInputStream ()

This method returns an input stream representing the encoded message. This is a method defined as abstract in the base class that must be implemented by all derived classes. In this case, a byte array input stream is returned.

Returns

Input stream containing encoded message

1.3.3.16 override void Reset ()

This method resets the buffer to allow a new record to be encoded into it. Any previously encoded data is lost.

1.3.3.17 override System.String ToString ()

This method will return a string representation of the data in the encode buffer. The format is hex characters.

Returns

Stringified representation of the value

1.3.3.18 virtual int TrimBitString (Asn1BitString *bitstr*) [virtual]

This method will trim a BIT STRING for DER encoding by removing all zero trailing bits. The default implementation in [Asn1BerEncodeBuffer](#) does nothing. The overridden version in [Asn1DerEncodeBuffer](#) will trim the string.

<param name="bitstr"> ASN.1 BIT STRING object <return> Adjusted bit count </return>

Reimplemented in [Asn1DerEncodeBuffer](#).

1.3.3.19 override void Write (System.IO.Stream *outs*)

This method writes the encoded record to the given output stream.

Parameters

outs Output stream to which record is to be written

1.3.4 Property Documentation

1.3.4.1 virtual System.IO.MemoryStream ByteArrayInputStream [get]

This method returns a reference to a byte array input stream representing the encoded message. This is the preferred way to access the contents of the encoded message as it is the most efficient.

Returns

byte array input stream containing encoded message

1.3.4.2 override byte [] MsgCopy [get]

This method returns the encoded message in a byte array. This is less efficient than the `ByteArrayInputStream` property because the message contents must be copied to a newly created byte array.

Returns

byte array containing encoded message

1.3.4.3 override int MsgLength [get]

This method returns the length of the encoded message component.

Returns

length of encoded message component

1.4 Asn1BerInputStream Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1BerDecodeBuffer](#).

Inherited by [Asn1CerInputStream](#).

Public Member Functions

- [Asn1BerInputStream](#) (System.IO.Stream istream)
- virtual int [Available](#) ()
- virtual void [Close](#) ()
- override void [Mark](#) ()
- virtual bool [MarkSupported](#) ()
- override void [Reset](#) ()
- override long [Skip](#) (long nbytes)

1.4.1 Detailed Description

This class handles the input stream for the decoding of ASN.1 messages as specified in the Basic Encoding Rules (BER) as documented in the ITU-T X.690 standard.

1.4.2 Constructor & Destructor Documentation

1.4.2.1 Asn1BerInputStream (System.IO.Stream *istream*)

This constructor creates a BER input stream object that references an encoded ASN.1 message.

Parameters

istream Input stream containing an encoded ASN.1 message.

1.4.3 Member Function Documentation

1.4.3.1 virtual int Available () [virtual]

Returns the number of bytes that can be read (or skipped over) from this input stream without blocking by the next caller of a method for this input stream. The next caller might be the same thread or or another thread.

Returns

the number of bytes that can be read from this input stream without blocking.

Exceptions

System.SystemException if an I/O error occurs.

1.4.3.2 virtual void Close () [virtual]

Closes this input stream and releases any system resources associated with the stream.

Exceptions

System.SystemException if an I/O error occurs.

1.4.3.3 override void Mark ()

This method is used to mark the current position in the input stream for retry processing or resetting the input stream position to current position.

1.4.3.4 virtual bool MarkSupported () [virtual]

Tests if this input stream supports the seeking. This method is equivalent to C# `CanSeek` method of `System.IO.Stream`.

Returns

`true` if input stream supports seeking; Otherwise `false`.

1.4.3.5 override void Reset ()

This method is used to reset the current position in the input stream back to the location of the last 'mark' call. It is equivalent to calling 'Stream.Position' to marked location.

1.4.3.6 override long Skip (long nbytes)

This method will skip over the requested number of bytes in the input stream.

Parameters

nbytes Number of bytes to skip

Exceptions

System.SystemException if an I/O error occurs.

Returns

Skipped number of bytes

1.5 Asn1BerMessageDumpHandler Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1TaggedEventHandler](#).

Public Member Functions

- [Asn1BerMessageDumpHandler](#) (System.IO.StreamWriter outs)
- [Asn1BerMessageDumpHandler](#) ()
- virtual void [Contents](#) (byte[] data)
- virtual void [EndElement](#) (Asn1Tag tag)
- virtual void [StartElement](#) (Asn1Tag tag, int len, byte[] tagLenBytes)

1.5.1 Detailed Description

This class implements the [Asn1EventHandler](#) interface to provide a formatted dump of a BER message to the given print output stream. An object of this type is used in conjunction with the [Asn1BerDecodeBuffer](#) *Parse* method to generically parse a BER message.

1.5.2 Constructor & Destructor Documentation

1.5.2.1 Asn1BerMessageDumpHandler ()

The constructor will print the dump result on the standard output stream.

1.5.2.2 Asn1BerMessageDumpHandler (System.IO.StreamWriter outs)

The constructor sets the StreamWriter object to which the formatted output should be written.

Parameters

outs Output stream for formatted data

1.5.3 Member Function Documentation

1.5.3.1 virtual void Contents (byte[] data) [virtual]

This method is invoked after each contents field is parsed. It formats and prints the contents in a hex/ascii format.

Parameters

data Array containing the encoded contents bytes

Implements [Asn1TaggedEventHandler](#).

1.5.3.2 virtual void EndElement (Asn1Tag tag) [virtual]

This method is invoked after parsing is complete on each tag/length/value (TLV) in the message.

Parameters

tag Array containing the encoded contents bytes

Implements [Asn1TaggedEventHandler](#).

1.5.3.3 virtual void StartElement (Asn1Tag tag, int len, byte[] tagLenBytes) [virtual]

This method is invoked after each tag/length value is parsed in the message being dumped. It formats and prints the tag/length values.

Parameters

tag Parsed tag value

len Parsed length value

tagLenBytes Array containing the encoded tag/length bytes

Implements [Asn1TaggedEventHandler](#).

1.6 Asn1BerOutputStream Class Reference

Inherited by [Asn1CerOutputStream](#).

Public Member Functions

- [Asn1BerOutputStream](#) (System.IO.Stream os, int bufSize)
- [Asn1BerOutputStream](#) (System.IO.Stream os)
- virtual void [Encode](#) (Asn1Type type, bool explicitTagging)
- virtual void [EncodeBitString](#) (byte[] data, int numbits, bool explicitTagging, Asn1Tag tag)
- virtual void [EncodeBMPString](#) (System.String data, bool explicitTagging, Asn1Tag tag)
- virtual void [EncodeCharString](#) (System.String data, bool explicitTagging, Asn1Tag tag)
- virtual void [EncodeEOC](#) ()
- virtual void [EncodeIdentifier](#) (long ident)
- virtual void [EncodeIntValue](#) (long data, bool encodeLen)
- virtual void [EncodeLength](#) (int len)
- virtual void [EncodeOctetString](#) (byte[] data, bool explicitTagging, Asn1Tag tag)
- virtual void [EncodeTag](#) (short tagClass, short tagForm, int tagIDCode)
- virtual void [EncodeTag](#) (Asn1Tag tag)
- virtual void [EncodeTagAndIndefLen](#) (short tagClass, short tagForm, int tagIDCode)
- virtual void [EncodeTagAndIndefLen](#) (Asn1Tag tag)
- virtual void [EncodeTagAndLength](#) (Asn1Tag tag, int len)
- virtual void [EncodeUnivString](#) (int[] data, bool explicitTagging, Asn1Tag tag)
- virtual void [EncodeUnsignedBinaryNumber](#) (long data)

1.6.1 Detailed Description

This class implements the output stream to encode ASN.1 messages as specified in the Basic Encoding Rules (BER) as specified in the ITU-T X.690 standard. A reference to an object of this type is passed to each of the ASN.1 type encode methods involved in encoding a particular message type.

1.6.2 Constructor & Destructor Documentation

1.6.2.1 Asn1BerOutputStream (System.IO.Stream os)

This constructor creates a buffered BER output stream object with default size of buffer. Whenever the buffer becomes full, the buffer will be flushed to the stream.

Parameters

os The underlying System.IO.Stream object.

1.6.2.2 Asn1BerOutputStream (System.IO.Stream os, int bufSize)

This constructor creates a buffered BER output stream object. Whenever the buffer becomes full, the buffer will be flushed to the stream.

Parameters

os The underlying System.IO.Stream object.

bufSize The buffer size. If it is 0 then the output stream is used as unbuffered one.

1.6.3 Member Function Documentation

1.6.3.1 virtual void Encode (Asn1Type type, bool explicitTagging) [virtual]

This method encodes and writes to the stream ASN.1 types. The UNIVERSAL tag value and length is also encoded if explicit tagging is specified (the universal identifier must be provided by the caller).

Throws, exception thrown by the underlying System.IO.Stream object.

Parameters

type The object to be written

explicitTagging Flag indicating explicit tagging should be done

Reimplemented in [Asn1CerOutputStream](#).

1.6.3.2 virtual void EncodeBitString (byte[] data, int numbits, bool explicitTagging, Asn1Tag tag) [virtual]

This method writes the given array of bytes as bit string value.

Throws, exception thrown by the underlying System.IO.Stream object.

Parameters

data Byte array containing data to encode.

numbits Number of bits to encode

explicitTagging Flag indicating explicit tagging should be done

tag Universal tag to apply

Exceptions

Asn1Exception Thrown, if operation is failed.

Reimplemented in [Asn1CerOutputStream](#).

1.6.3.3 virtual void EncodeBMPString (System.String data, bool explicitTagging, Asn1Tag tag) [virtual]

This method writes the given string as BMP string value.

Throws, exception thrown by the underlying System.IO.Stream object.

Parameters

data String containing data to encode.

explicitTagging Flag indicating explicit tagging should be done

tag Universal tag to apply

Exceptions

Asn1Exception Thrown, if operation is failed.

Reimplemented in [Asn1CerOutputStream](#).

1.6.3.4 virtual void EncodeCharString (System.String *data*, bool *explicitTagging*, Asn1Tag *tag*) [virtual]

This method encodes and writes to the stream an ASN.1 8-bit character string types including IA5String, PrintableString, NumericString, etc. The UNIVERSAL tag value and length is also encoded if explicit tagging is specified (the universal identifier must be provided by the caller).

Throws, exception thrown by the underlying System.IO.Stream object.

Parameters

data The string object to be written

explicitTagging Flag indicating explicit tagging should be done

tag Universal tag to apply

Exceptions

Asn1Exception Thrown, if operation is failed.

Reimplemented in [Asn1CerOutputStream](#).

1.6.3.5 virtual void EncodeEOC () [virtual]

This method encodes and writes an End-Of-Contents marker to the stream.

Throws, exception thrown by the underlying System.IO.Stream object.

1.6.3.6 virtual void EncodeIdentifier (long *ident*) [virtual]

This method encodes and writes to the stream an ASN.1 identifier value such as the ones used in a tags or object identifiers.

Throws, exception thrown by the underlying System.IO.Stream.

Parameters

ident The identifier to be encoded.

1.6.3.7 virtual void EncodeIntValue (long *data*, bool *encodeLen*) [virtual]

This method encodes and writes to the stream an ASN.1 integer value's contents according to the ASN.1 Basic Encoding Rules (BER).

Throws, exception thrown by the underlying System.IO.Stream object.

Parameters

data Integer value to encode.

encodeLen Flag indicating length determinant should be encoded before encoding integer value.

1.6.3.8 virtual void EncodeLength (int *len*) [virtual]

This method encodes and writes a length value to the stream.

Throws, exception thrown by the underlying System.IO.Stream object.

Parameters

len The length to be encoded.

1.6.3.9 virtual void EncodeOctetString (byte[] *data*, bool *explicitTagging*, Asn1Tag *tag*) [virtual]

This method writes the given array of bytes as octet string value.

Throws, exception thrown by the underlying System.IO.Stream object.

Parameters

data Byte array containing data to encode.

explicitTagging Flag indicating explicit tagging should be done

tag Universal tag to apply

Exceptions

Asn1Exception Thrown, if operation is failed.

Reimplemented in [Asn1CerOutputStream](#).

1.6.3.10 virtual void EncodeTag (short *tagClass*, short *tagForm*, int *tagIDCode*) [virtual]

This method encodes and writes a tag value to the stream.

Throws, exception thrown by the underlying System.IO.Stream object.

Parameters

tagClass The class of the tag to be encoded.

tagForm The form of the tag to be encoded.

tagIDCode The ID code of the tag to be encoded.

1.6.3.11 virtual void EncodeTag (Asn1Tag *tag*) [virtual]

This method encodes and writes a tag value to the stream.

Throws, exception thrown by the underlying System.IO.Stream object.

Parameters

tag The tag to be encoded.

1.6.3.12 virtual void EncodeTagAndIndefLen (short *tagClass*, short *tagForm*, int *tagIDCode*) [virtual]

This overloaded version of EncodeTagAndIndefLen allows tag value components to be specified instead of an Asn1Tag object.

Throws, exception thrown by the underlying System.IO.Stream object.

Parameters

tagClass The class of the tag to be encoded.

tagForm The form of the tag to be encoded.

tagIDCode The ID code of the tag to be encoded.

1.6.3.13 virtual void EncodeTagAndIndefLen (Asn1Tag *tag*) [virtual]

This method encodes and writes both a tag and an indefinite length indicator to the stream.

Throws, exception thrown by the underlying System.IO.Stream object.

Parameters

tag The tag to be encoded.

1.6.3.14 virtual void EncodeTagAndLength (Asn1Tag *tag*, int *len*) [virtual]

This method encodes and writes both a tag and length value to the stream.

Throws, exception thrown by the underlying System.IO.Stream object.

Parameters

tag The tag to be encoded.

len The length to be encoded.

1.6.3.15 virtual void EncodeUnivString (int[] *data*, bool *explicitTagging*, Asn1Tag *tag*) [virtual]

This method writes the given array of integers as UniversalString value.

Throws, exception thrown by the underlying System.IO.Stream object.

Parameters

data Array containing data to encode.

explicitTagging Flag indicating explicit tagging should be done

tag Universal tag to apply

Exceptions

Asn1Exception Thrown, if operation is failed.

Reimplemented in [Asn1CerOutputStream](#).

1.6.3.16 virtual void EncodeUnsignedBinaryNumber (long *data*) [virtual]

This method encodes an integer value as unsigned binary number according to the ASN.1 Basic Encoding Rules (BER).. and writes to the stream

Throws, exception thrown by the underlying System.IO.Stream object.

Parameters

data Integer value to encode.

1.7 Asn1CerInputStream Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1BerInputStream](#).

Public Member Functions

- [Asn1CerInputStream](#) (System.IO.Stream *istream*)

1.7.1 Detailed Description

This class handles the input stream for the decoding of ASN.1 messages as specified in the Canonical Encoding Rules (CER) as documented in the ITU-T X.690 standard.

1.7.2 Constructor & Destructor Documentation

1.7.2.1 Asn1CerInputStream (System.IO.Stream *istream*)

This constructor creates a CER input stream object that references an encoded ASN.1 message.

Parameters

istream Input stream containing an encoded ASN.1 message.

1.8 Asn1CerOutputStream Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1BerOutputStream](#).

Public Member Functions

- [Asn1CerOutputStream](#) (System.IO.Stream os, int bufSize)
- [Asn1CerOutputStream](#) (System.IO.Stream os)
- override void [Encode](#) (Asn1Type type, bool explicitTagging)
- override void [EncodeBitString](#) (byte[] value, int numbits, bool explicitTagging, Asn1Tag tag)
- override void [EncodeBMPString](#) (System.String value, bool explicitTagging, Asn1Tag tag)
- override void [EncodeCharString](#) (System.String value, bool explicitTagging, Asn1Tag tag)
- override void [EncodeOctetString](#) (byte[] value, bool explicitTagging, Asn1Tag tag)
- virtual void [EncodeStringTag](#) (int nbytes, short tagClass, short tagForm, int tagIDCode)
- virtual void [EncodeStringTag](#) (int nbytes, Asn1Tag tag)
- override void [EncodeUnivString](#) (int[] value, bool explicitTagging, Asn1Tag tag)

1.8.1 Detailed Description

This class implements the output stream to encode ASN.1 messages as specified in the Canonical Encoding Rules (CER) as specified in the ITU-T X.690 standard. A reference to an object of this type is passed to each of the ASN.1 type encode methods involved in encoding a particular message type.

1.8.2 Constructor & Destructor Documentation

1.8.2.1 Asn1CerOutputStream (System.IO.Stream os)

This constructor creates a buffered CER output stream object with default size of buffer. Whenever the buffer becomes full, the buffer will be flushed to the stream.

Parameters

os The underlying System.IO.Stream object.

1.8.2.2 Asn1CerOutputStream (System.IO.Stream os, int bufSize)

This constructor creates a buffered CER output stream object. Whenever the buffer becomes full, the buffer will be flushed to the stream.

Parameters

os The underlying System.IO.Stream object.

bufSize The buffer size. If it is 0 then the output stream is used as unbuffered one.

1.8.3 Member Function Documentation

1.8.3.1 override void Encode (Asn1Type *type*, bool *explicitTagging*) [virtual]

This method encodes and writes to the stream ASN.1 types. The UNIVERSAL tag value and length is also encoded if explicit tagging is specified (the universal identifier must be provided by the caller).

Throws, exception thrown by the underlying System.IO.Stream object.

Parameters

type The object to be written

explicitTagging Flag indicating explicit tagging should be done

Reimplemented from [Asn1BerOutputStream](#).

1.8.3.2 override void EncodeBitString (byte[] *value*, int *numbits*, bool *explicitTagging*, Asn1Tag *tag*) [virtual]

This method writes the given array of bytes as bit string value.

Throws, exception thrown by the underlying System.IO.Stream object.

Parameters

value Byte array containing data to encode.

numbits Number of bits to encode

explicitTagging Flag indicating explicit tagging should be done

tag Universal tag to apply

Exceptions

Asn1Exception Thrown, if operation is failed.

Reimplemented from [Asn1BerOutputStream](#).

1.8.3.3 override void EncodeBMPString (System.String *value*, bool *explicitTagging*, Asn1Tag *tag*) [virtual]

This method writes the given string as BMP string value.

Throws, exception thrown by the underlying System.IO.Stream object.

Parameters

value String containing data to encode.

explicitTagging Flag indicating explicit tagging should be done

tag Universal tag to apply

Exceptions

Asn1Exception Thrown, if operation is failed.

Reimplemented from [Asn1BerOutputStream](#).

1.8.3.4 override void EncodeCharString (System.String value, bool explicitTagging, Asn1Tag tag) [virtual]

This method encodes and writes to the stream an ASN.1 8-bit character string types including IA5String, PrintableString, NumericString, etc. The UNIVERSAL tag value and length is also encoded if explicit tagging is specified (the universal identifier must be provided by the caller).

Throws, exception thrown by the underlying System.IO.Stream object.

Parameters

- value* The string object to be written
- explicitTagging* Flag indicating explicit tagging should be done
- tag* Universal tag to apply

Exceptions

- Asn1Exception* Thrown, if operation is failed.

Reimplemented from [Asn1BerOutputStream](#).

1.8.3.5 override void EncodeOctetString (byte[] value, bool explicitTagging, Asn1Tag tag) [virtual]

This method writes the given array of bytes as octet string value.

Throws, exception thrown by the underlying System.IO.Stream object.

Parameters

- value* Byte array containing data to encode.
- explicitTagging* Flag indicating explicit tagging should be done
- tag* Universal tag to apply

Exceptions

- Asn1Exception* Thrown, if operation is failed.

Reimplemented from [Asn1BerOutputStream](#).

1.8.3.6 virtual void EncodeStringTag (int nbytes, short tagClass, short tagForm, int tagIDCode) [virtual]

This method encodes and writes both a tag and length value to the stream.

Throws, exception thrown by the underlying System.IO.Stream object.

Parameters

- nbytes* The number of bytes in string to be encoded.
- tagClass* The class of the tag to be encoded.
- tagForm* The form of the tag to be encoded.
- tagIDCode* The ID code of the tag to be encoded.

1.8.3.7 virtual void EncodeStringTag (int *nbytes*, Asn1Tag *tag*) [virtual]

This method encodes and writes both a tag and length value to the stream.

Throws, exception thrown by the underlying System.IO.Stream object.

Parameters

nbytes The number of bytes in string to be encoded.

tag The tag to be encoded.

1.8.3.8 override void EncodeUnivString (int[] *value*, bool *explicitTagging*, Asn1Tag *tag*) [virtual]

This method writes the given array of integers as UniversalString value.

Throws, exception thrown by the underlying System.IO.Stream object.

Parameters

value Array containing data to encode.

explicitTagging Flag indicating explicit tagging should be done

tag Universal tag to apply

Exceptions

Asn1Exception Thrown, if operation is failed.

Reimplemented from [Asn1BerOutputStream](#).

1.9 Asn1DerDecodeBuffer Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1BerDecodeBuffer](#).

Inherited by [Asn1DerInputStream](#).

Public Member Functions

- [Asn1DerDecodeBuffer](#) (System.IO.Stream *istream*)
- [Asn1DerDecodeBuffer](#) (byte[] *msgdata*)

1.9.1 Detailed Description

This class handles the decoding of ASN.1 messages as specified in the Distinguished Encoding Rules (DER) as documented in the ITU-T X.690 standard.

1.9.2 Constructor & Destructor Documentation

1.9.2.1 Asn1DerDecodeBuffer (byte[] *msgdata*)

This constructor creates a DER Decode buffer object that references an encoded ASN.1 message.

Parameters

msgdata Byte array containing an encoded ASN.1 message.

1.9.2.2 Asn1DerDecodeBuffer (System.IO.Stream *istream*)

This constructor creates a DER Decode buffer object that references an encoded ASN.1 message. In this case, the message is passed in using an System.IO.Stream object.

Parameters

istream Input stream containing an encoded ASN.1 message.

1.10 Asn1DerEncodeBuffer Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1BerEncodeBuffer](#).

Public Member Functions

- [Asn1DerEncodeBuffer](#) (int sizeIncrement)
- [Asn1DerEncodeBuffer](#) ()
- override int [TrimBitString](#) (Asn1BitString bitstr)

1.10.1 Detailed Description

This class handles the encoding of ASN.1 messages as specified in the Distinguished Encoding Rules (DER) as specified in the ITU-T X.690 standard.

1.10.2 Constructor & Destructor Documentation

1.10.2.1 Asn1DerEncodeBuffer ()

This constructor creates a DER encode buffer object with the default size increment. Whenever the buffer becomes full, the buffer will be expanded by the sizeIncrement size.

1.10.2.2 Asn1DerEncodeBuffer (int *sizeIncrement*)

This constructor creates a DER encode buffer object with the given size increment. Whenever the buffer becomes full, the buffer will be expanded by the sizeIncrement size. This size should be large enough to prevent resizing in normal operation.

Parameters

sizeIncrement The initial size in bytes of an encode buffer. If the buffer becomes full, it will be expanded by this amount.

1.10.3 Member Function Documentation

1.10.3.1 override int TrimBitString (Asn1BitString *bitstr*) [virtual]

This method will trim a BIT STRING for DER encoding by removing all zero trailing bits.

<param name="bitstr"> ASN.1 BIT STRING object <return> Adjusted bit count </return>

Reimplemented from [Asn1BerEncodeBuffer](#).

1.11 Asn1DerInputStream Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1DerDecodeBuffer](#).

Public Member Functions

- [Asn1DerInputStream](#) (System.IO.Stream istream)
- virtual int [Available](#) ()
- virtual void [Close](#) ()
- override void [Mark](#) ()
- virtual bool [MarkSupported](#) ()
- override void [Reset](#) ()
- override long [Skip](#) (long nbytes)

1.11.1 Detailed Description

This class handles the input stream for the decoding of ASN.1 messages as specified in the Distinguished Encoding Rules (DER) as documented in the ITU-T X.690 standard.

1.11.2 Constructor & Destructor Documentation

1.11.2.1 Asn1DerInputStream (System.IO.Stream *istream*)

This constructor creates a DER decode buffer object that references an encoded ASN.1 message. In this case, the message is passed in using an System.IO.Stream object.

Parameters

istream Input stream containing an encoded ASN.1 message.

1.11.3 Member Function Documentation

1.11.3.1 virtual int Available () [virtual]

Returns the number of bytes that can be read (or skipped over) from this input stream without blocking by the next caller of a method for this input stream. The next caller might be the same thread or or another thread.

Throws, Exception thrown by C# System.IO.Stream for I/O error

Returns

the number of bytes that can be read from this input stream without blocking.

1.11.3.2 virtual void Close () [virtual]

Closes this input stream and releases any system resources associated with the stream.

Throws, Exception thrown by C# System.IO.Stream for I/O error

1.11.3.3 **override void Mark ()**

This method is used to mark the current position in the input stream for retry processing or resetting the input stream position to current position.

1.11.3.4 **virtual bool MarkSupported () [virtual]**

Tests if this input stream supports the seeking. This method is equivalent to C# `CanSeek` method of `System.IO.Stream`.

Returns

`true` if input stream supports seeking; Otherwise `false`.

1.11.3.5 **override void Reset ()**

This method is used to reset the current position in the input stream back to the location of the last 'mark' call. It is equivalent to calling 'Stream.Position' to marked location.

1.11.3.6 **override long Skip (long *nbytes*)**

This method will skip over the requested number of bytes in the input stream.

Parameters

nbytes Number of bytes to skip

Returns

Skipped number of bytes

1.12 Asn1NotInSetException Class Reference

Public Member Functions

- [Asn1NotInSetException](#) ([Asn1BerDecodeBuffer](#) buffer, [Asn1Tag](#) tag)

1.12.1 Detailed Description

This class defines the 'ASN.1 element not in set' exception that is thrown from BER/DER methods when an element is parsed within the context of a SET that does not belong to the set.

1.12.2 Constructor & Destructor Documentation

1.12.2.1 Asn1NotInSetException ([Asn1BerDecodeBuffer](#) *buffer*, [Asn1Tag](#) *tag*)

This constructor creates an exception object with a textual message describing the tag of the duplicate element.

Parameters

- buffer* BER decode buffer object reference
- tag* Tag value of element that is not in the set

1.13 Asn1PerBitField Class Reference

Public Member Functions

- [Asn1PerBitField](#) (System.String name, int bitOffset, int bitCount)
- virtual void [SetBitCountAndOffset](#) (int count, int offset)

Properties

- virtual int [BitCount](#) [get, set]
- virtual int [BitOffset](#) [get, set]
- virtual System.String [Name](#) [get]

1.13.1 Detailed Description

This class is used to store information on an individual bit field within a PER message. The information can be used to print a bit trace of the components of a message. It is used in conjunction with the [Asn1PerBitFieldList](#) class to map all bits in a message.

1.13.2 Constructor & Destructor Documentation

1.13.2.1 Asn1PerBitField (System.String name, int bitOffset, int bitCount)

This constructor initializes all of the variables used to track the bit fields.

Parameters

- name* Name of the bit field.
- bitOffset* Offset within buffer to the bit field
- bitCount* Number of bits in the bit field

1.13.3 Member Function Documentation

1.13.3.1 virtual void SetBitCountAndOffset (int count, int offset) [virtual]

This method sets the count of bits in the bit field and the offset to the bit field in the message buffer.

Parameters

- count* Number of bits in the bit field
- offset* Offset within buffer to the bit field

1.13.4 Property Documentation

1.13.4.1 virtual int BitCount [get, set]

Gets and Sets the number of bits in the bit field.

Value: Number of bits.

1.13.4.2 virtual int BitOffset [get, set]

Gets and Sets the offset to the bit field in the message buffer.

Value: Offset of the bitfield

1.13.4.3 virtual System.String Name [get]

This method returns the name assigned to the bit field.

Value: Bitfield name

1.14 Asn1PerBitFieldList Class Reference

Public Member Functions

- virtual void [AddElemName](#) (System.String name, int arrayx)
- virtual System.Collections.IEnumerator [Iterator](#) ()
- virtual [Asn1PerBitField NewBitField](#) (System.String nameSuffix, int bitOffset, int bitCount)
- virtual void [RemoveLastElemName](#) ()
- virtual void [Reset](#) ()

Properties

- virtual int [BitOffset](#) [set]
- virtual [Asn1PerBitField CurrBitField](#) [get]

1.14.1 Detailed Description

This class is used to map all of the bit fields in a PER message. After encoding or decoding is complete, this object can be used to provide a formatted printout of all of the message fields.

1.14.2 Member Function Documentation

1.14.2.1 virtual void AddElemName (System.String name, int arrayx) [virtual]

This method adds an element name to the current fully qualified name. The fully qualified name is a string of name components separated by dots (ex. a.b.c).

Parameters

name Name component to append to string

arrayx Array index if named item is an element in an array (set to -1 otherwise)

1.14.2.2 virtual System.Collections.IEnumerator Iterator () [virtual]

This method returns an iterator to the encapsulated bit field linked list object.

Returns

System.Collections.IEnumerator value of this list

1.14.2.3 virtual Asn1PerBitField NewBitField (System.String nameSuffix, int bitOffset, int bitCount) [virtual]

This method creates a new bit field object with the given properties and appends it to the bit field list. Also sets as current bit field.

Parameters

nameSuffix Suffix to add to fully qualified name for this field (for example, 'length')

bitOffset Offset to the start of this field in bits from the beginning of the encode buffer.

bitCount Number of bits in the field.

Returns

Created bit field

1.14.2.4 virtual void RemoveLastElemName () [virtual]

This method removes the last element name in the current fully qualified name string. For example, if the current string is 'a.b.c', it will be 'a.b' after calling this method.

1.14.2.5 virtual void Reset () [virtual]

This method resets the object.

1.14.3 Property Documentation

1.14.3.1 virtual int BitOffset [set]

Set the current bit offset in the bit field.

Value: The bit offset

1.14.3.2 virtual Asn1PerBitField CurrBitField [get]

Gets a reference to the current bit field object (i.e. the one that was last created).

Value: Current bit field

1.15 Asn1PerBitFieldPrinter Class Reference

Public Member Functions

- [Asn1PerBitFieldPrinter](#) ([Asn1PerMessageBuffer](#) perMessageBuffer, System.IO.Stream encodedMessage)
- virtual void [Print](#) (System.IO.StreamWriter outs, System.String varName)

Protected Attributes

- internal int [mBitMask](#)
- internal int [mByteIndex](#)
- internal int [mCurrOctet](#)
- internal System.IO.Stream [mEncodedMessage](#)
- internal int [mFmtBitCharIdx](#)
- internal System.Text.StringBuilder [mFormatBuffer](#)
- internal [Asn1PerMessageBuffer](#) [mPerMessageBuffer](#)

1.15.1 Detailed Description

This class is used to obtain a formatted printout of the bit fields that make up a PER encoded message.

1.15.2 Constructor & Destructor Documentation

1.15.2.1 [Asn1PerBitFieldPrinter](#) ([Asn1PerMessageBuffer](#) *perMessageBuffer*, System.IO.Stream *encodedMessage*)

Constructor

Parameters

perMessageBuffer PER encode or decode message buffer
encodedMessage Input stream of encoded message

1.15.3 Member Function Documentation

1.15.3.1 virtual void [Print](#) (System.IO.StreamWriter *outs*, System.String *varName*) [**virtual**]

This method iterates through and prints all of the bit fields in a PER encoded message. Bit tracing needs to have been enabled in the buffer via the 'perTraceEnable' method prior to encoding or decoding the message.

Parameters

outs Print stream
varName Variable name. This will be printed before all fields (for example, <varName> .field1, etc.)

1.15.4 Member Data Documentation

1.15.4.1 internal int [mBitMask](#) [**protected**]

This variable holds the mask for current bit

1.15.4.2 internal int mByteIndex [protected]

This variable holds the byte index

1.15.4.3 internal int mCurrOctet [protected]

This variable holds the current byte

1.15.4.4 internal System.IO.Stream mEncodedMessage [protected]

This variable holds the input stream

1.15.4.5 internal int mFmtBitCharIdx [protected]

This variable holds the index for formatted information

1.15.4.6 internal System.Text.StringBuilder mFormatBuffer [protected]

Initial value:

```
new System.Text.StringBuilder()
```

This variable holds the formatted information of current byte

1.15.4.7 internal Asn1PerMessageBuffer mPerMessageBuffer [protected]

This variable holds the PER encode or decode message buffer

1.16 Asn1PerDecodeBuffer Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1PerMessageBuffer](#).

Inherited by [Asn1PerInputStream](#).

Public Member Functions

- [Asn1PerDecodeBuffer](#) (System.IO.Stream istream, bool aligned)
- [Asn1PerDecodeBuffer](#) (byte[] msgdata, bool aligned)
- virtual void [BinDump](#) (System.IO.StreamWriter outs, System.String varName)
- virtual void [BinDump](#) (System.String varName)
- virtual void [ByteAlign](#) ()
- virtual bool [DecodeBit](#) ()
- virtual bool [DecodeBit](#) (System.String ident)
- virtual int [DecodeBitsToInt](#) (int nbits)
- virtual int [DecodeBitsToInt](#) (int nbits, System.String ident)
- virtual long [DecodeBitsToLong](#) (int nbits)
- virtual long [DecodeBitsToLong](#) (int nbits, System.String ident)
- virtual void [DecodeBitsToOctetArray](#) (byte[] data, int offset, int nbits)
- virtual void [DecodeBitsToOctetArray](#) (byte[] data, int offset, int nbits, System.String ident)
- virtual void [DecodeCharString](#) (int nchars, int abpc, int ubpc, Asn1CharSet charSet, System.Text.StringBuilder sbuf)
- virtual long [DecodeConsWholeNumber](#) (long rangeValue)
- virtual long [DecodeConsWholeNumber](#) (long rangeValue, System.String ident)
- virtual long [DecodeExtLength](#) ()
- virtual long [DecodeInt](#) (int nocts, bool signExtend)
- virtual long [DecodeInt](#) (int nocts, bool signExtend, System.String ident)
- virtual long [DecodeLength](#) (long lower, long upper)
- virtual long [DecodeLength](#) ()
- virtual int [DecodeSmallNonNegWholeNumber](#) ()
- virtual bool [IsAligned](#) ()
- virtual void [MoveBitCursor](#) (long offset)
- override int [ReadByte](#) ()
- virtual void [SetAligned](#) (bool data)
- override void [SetInputStream](#) (byte[] msgdata, int offset, int length)

Static Public Member Functions

- static [Asn1PerDecodeBuffer SetBuffer](#) ([Asn1PerDecodeBuffer](#) buffer, byte[] msgdata, bool aligned)

Protected Attributes

- internal [Asn1PerTraceHandler mTraceHandler](#)

Properties

- virtual long [BitOffset](#) [get]
- virtual int [MsgBitCnt](#) [get]
- virtual [Asn1PerTraceHandler TraceHandler](#) [get]

1.16.1 Detailed Description

This class handles the decoding of ASN.1 messages as specified in the Packed Encoding Rules (PER) ITU-T X.691 standard.

1.16.2 Constructor & Destructor Documentation

1.16.2.1 `Asn1PerDecodeBuffer (byte[] msgdata, bool aligned)`

This constructor creates a PER Decode buffer object that references an encoded ASN.1 message.

Parameters

msgdata Byte array containing an encoded ASN.1 message.

aligned `true` for specifying PER aligned; otherwise `false` for unaligned encoding.

1.16.2.2 `Asn1PerDecodeBuffer (System.IO.Stream istream, bool aligned)`

This constructor creates a PER Decode buffer object that references an encoded ASN.1 message. In this case, the message is passed in using an `System.IO.Stream` object.

Parameters

istream Input stream containing an encoded ASN.1 message.

aligned Boolean specifying PER aligned or unaligned encoding.

1.16.3 Member Function Documentation

1.16.3.1 `virtual void BinDump (System.IO.StreamWriter outs, System.String varName) [virtual]`

This method dumps the encoded message in a human-readable format showing a bit trace of all fields to the given output stream.

Parameters

outs StreamWriter object to which output should be written

varName Name of top-level message object variable

1.16.3.2 `virtual void BinDump (System.String varName) [virtual]`

This method invokes an overloaded version of `BinDump` to dump the encoded message to standard output.

Parameters

varName Name of top-level message object variable

1.16.3.3 `virtual void ByteAlign () [virtual]`

This methods byte-aligns the buffer.

Implements [Asn1PerMessageBuffer](#).

1.16.3.4 virtual bool DecodeBit () [virtual]

This method decodes a single bit value. The `ident` argument which is used for tracing is defaulted to 'value'.

Returns

Boolean value of bit that was decoded.

1.16.3.5 virtual bool DecodeBit (System.String *ident*) [virtual]

This method decodes a single bit value.

Parameters

ident Bit field identifier name for tracing.

Returns

Boolean value of bit that was decoded.

1.16.3.6 virtual int DecodeBitsToInt (int *nbits*) [virtual]

This method decodes bits from the input stream into a standard integer value. Up to 32 bits can be decoded. The bits are placed in the least-significant bytes of the integer. The `ident` argument which is used for tracing is defaulted to 'value'.

Returns

Integer value containing decoded bits

Parameters

nbits Number of bits to Decode

1.16.3.7 virtual int DecodeBitsToInt (int *nbits*, System.String *ident*) [virtual]

This method decodes bits from the input stream into a standard integer value. Up to 32 bits can be decoded. The bits are placed in the least-significant bytes of the integer.

Parameters

nbits Number of bits to Decode

ident Bit field identifier name for tracing.

Returns

Integer value containing decoded bits

1.16.3.8 virtual long DecodeBitsToLong (int *nbits*) [virtual]

This method decodes bits from the input stream into a long integer value. Up to 64 bits can be decoded. The bits are placed in the least-significant bytes of the long integer. The `ident` argument which is used for tracing is defaulted to 'value'.

Parameters

nbits Number of bits to Decode

Returns

Long integer value containing decoded bits

1.16.3.9 virtual long DecodeBitsToLong (int *nbits*, System.String *ident*) [virtual]

This method decodes bits from the input stream into a long integer value. Up to 64 bits can be decoded. The bits are placed in the least-significant bytes of the long integer.

Returns

Long integer value containing decoded bits

Parameters

nbits Number of bits to Decode

ident Bit field identifier name for tracing.

1.16.3.10 virtual void DecodeBitsToOctetArray (byte[] *data*, int *offset*, int *nbits*) [virtual]

This method decodes bits from the input stream into an array of octets. The user is expected to have provided an array large enough to hold the number of bits requested to be decoded. The `ident` argument which is used for tracing is defaulted to 'value'.

Parameters

data Octet array for decoded data

offset Starting byte offset into array

nbits Number of bits to Decode

1.16.3.11 virtual void DecodeBitsToOctetArray (byte[] *data*, int *offset*, int *nbits*, System.String *ident*) [virtual]

This method decodes bits from the input stream into an array of octets. The user is expected to have provided an array large enough to hold the number of bits requested to be decoded.

Parameters

data Octet array for decoded data

offset Starting byte offset into array

nbits Number of bits to Decode

ident Bit field identifier name for tracing.

1.16.3.12 virtual void DecodeCharString (int *nchars*, int *abpc*, int *ubpc*, Asn1CharSet *charSet*, System.Text.StringBuilder *sbuf*) [virtual]

This method decodes the contents of a known-multiplier character string. This version of the method assumes a permitted alphabet constraint is in place.

Parameters

nchars Number of characters

abpc Number of bits per character (aligned)

ubpc Number of bits per character (unaligned)

charSet Object representing the permitted alphabet constraint character set (optional)

sbuf String buffer to receive decoded result

1.16.3.13 virtual long DecodeConsWholeNumber (long *rangeValue*) [virtual]

This method implements the rules to Decode a constrained whole number as specified in section 10.5 of the X.691 standard. The *ident* argument which is used for tracing is defaulted to 'value'.

Parameters

rangeValue lower - upper + 1

Returns

Decoded adjusted value = value - lower range endpoint value

1.16.3.14 virtual long DecodeConsWholeNumber (long *rangeValue*, System.String *ident*) [virtual]

This method implements the rules to Decode a constrained whole number as specified in section 10.5 of the X.691 standard.

Parameters

rangeValue upper - lower + 1. Treated as unsigned, with 0 representing 2^{64} .

ident Tracing identifier

Returns

Decoded adjusted value = value - lower range endpoint value

1.16.3.15 virtual long DecodeExtLength () [virtual]

This method decodes an extension length value. Note that the decoded length is not what is returned. The bit offset to the start of the next element within the Decode buffer is returned.

Returns

Bit offset to next element in buffer

1.16.3.16 virtual long DecodeInt (int *nocts*, bool *signExtend*) [virtual]

This method implements the rules to Decode an unconstrained integer value. The *ident* argument which is used for tracing is defaulted to 'value'.

Returns

Decoded long integer value

Parameters

nocts Number of octets to Decode

signExtend Sign extend resulting value

1.16.3.17 virtual long DecodeInt (int *nocts*, bool *signExtend*, System.String *ident*) [virtual]

This method implements the rules to Decode an unconstrained integer value.

Returns

Decoded long integer value

Parameters

nocts Number of octets to Decode

signExtend Sign extend resulting value

ident Tracing identifier

1.16.3.18 virtual long DecodeLength (long *lower*, long *upper*) [virtual]

This method decodes a constrained length determinant value.

Parameters

lower Lower bound (inclusive) of length value range

upper Upper bound (inclusive) of length value range

Returns

Decoded length value

1.16.3.19 virtual long DecodeLength () [virtual]

This method decodes a general (unconstrained) length determinant value as described in section 10.9 of the X.691 standard. The maximum value that will be returned is 64K which is the largest length fragment size defined for PER. If a value of 16K or larger is returned, the user must repeat this call to fully Decode the fragmented contents.

Returns

Decoded length value. If the returned value is $\geq 16k$, this indicates a fragmented length was decoded. The user must call this method again after the data fragment is decoded to get the next fragment length.

1.16.3.20 **virtual int DecodeSmallNonNegWholeNumber () [virtual]**

This method implements the rules to Decode a small non-negative whole number as specified in section 10.6 of the X.691 standard.

Returns

Decoded int value

1.16.3.21 **virtual bool IsAligned () [virtual]**

This method tests if PER alignment is turned on or off.

Returns

`true` for PER aligned encoding or `false` for unaligned encoding.

Implements [Asn1PerMessageBuffer](#).

1.16.3.22 **virtual void MoveBitCursor (long offset) [virtual]**

This method moves the bit cursor to the given offset.

Parameters

offset Absolute bit offset value

1.16.3.23 **override int ReadByte ()**

This method returns the next available 8-bit value from the input stream. It is implemented differently for BER/DER and PER to take into account odd alignments in PER.

Returns

Next 8-bit byte value from input stream

1.16.3.24 **virtual void SetAligned (bool data) [virtual]**

This method is used to turn PER aligned encoding on or off.

Parameters

data `true` for PER aligned encoding or `false` for unaligned encoding.

1.16.3.25 **static Asn1PerDecodeBuffer SetBuffer (Asn1PerDecodeBuffer buffer, byte[] msgdata, bool aligned) [static]**

This method will create or reinitialize a PER Decode message buffer object to read data from the given byte array. If the existing buffer reference is null, a new buffer will be created; otherwise, the existing buffer will be reused.

Parameters

- buffer* Existing message buffer object
- msgdata* Byte array containing message data
- aligned* `true` specifying PER aligned or `false` for unaligned encoding.

Returns

[Asn1PerDecodeBuffer](#) to read data from the given byte array

1.16.3.26 override void SetInputStream (byte[] msgdata, int offset, int length)

This method will set the input stream from which data is read. This version of the method allows a byte array containing encoded data to be specified.

Parameters

- msgdata* Byte array containing encoded message data
- offset* Starting offset of data in the byte array
- length* Length (in bytes) of the encoded data

1.16.4 Member Data Documentation

1.16.4.1 internal Asn1PerTraceHandler mTraceHandler [protected]

Variable holds the PER message trace handler

1.16.5 Property Documentation

1.16.5.1 virtual long BitOffset [get]

Gets the absolute offset to the current bit in the Decode buffer.

Value: offset to current bit in Decode buffer

1.16.5.2 virtual int MsgBitCnt [get]

Gets the number of bits in the encoded PER message.

Value: count of bits in encoded message

Implements [Asn1PerMessageBuffer](#).

1.16.5.3 virtual Asn1PerTraceHandler TraceHandler [get]

Gets a reference to the internal trace handler object used to trace the bit fields within a PER message.

Value: [Asn1PerTraceHandler](#) object

Implements [Asn1PerMessageBuffer](#).

1.17 Asn1PerDecodeTraceHandler Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1PerTraceHandler](#).

Public Member Functions

- [Asn1PerDecodeTraceHandler](#) ([Asn1PerDecodeBuffer](#) messageBuffer)
- override void [Enable](#) ()
- override void [Print](#) (System.IO.StreamWriter outs, System.String varName)
- override void [Reset](#) ()

1.17.1 Detailed Description

This is a utility class for handling the collection and printing of PER bit field trace information. An object of the class is present within both the [Asn1PerEncodeBuffer](#) and [Asn1PerDecodeBuffer](#) classes. It is accessed using the 'TraceHandler' property from within objects of these classes.

1.17.2 Constructor & Destructor Documentation

1.17.2.1 Asn1PerDecodeTraceHandler ([Asn1PerDecodeBuffer](#) *messageBuffer*)

This constructor initializes the internal trace handler member variables.

Parameters

messageBuffer PER decode message buffer object reference

1.17.3 Member Function Documentation

1.17.3.1 override void [Enable](#) () [virtual]

This method is used to turn PER bit tracing on

Implements [Asn1PerTraceHandler](#).

1.17.3.2 override void [Print](#) (System.IO.StreamWriter *outs*, System.String *varName*) [virtual]

This method prints the trace to the given output stream in a default format.

Parameters

outs Print stream to which output is to be written.

varName Name of the object variable being printed.

Implements [Asn1PerTraceHandler](#).

1.17.3.3 override void [Reset](#) () [virtual]

This method resets the trace bit field list.

Implements [Asn1PerTraceHandler](#).

1.18 Asn1PerEncodeBuffer Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1PerMessageBuffer](#).

Public Member Functions

- [Asn1PerEncodeBuffer](#) (bool aligned, int sizeIncrement)
- [Asn1PerEncodeBuffer](#) (bool aligned)
- override void [BinDump](#) (System.IO.StreamWriter outs, System.String varName)
- virtual void [ByteAlign](#) ()
- override void [Copy](#) (byte[] value)
- override void [Copy](#) (byte value)
- virtual void [EncodeBit](#) (bool value)
- virtual void [EncodeBit](#) (bool value, System.String ident)
- virtual void [EncodeBits](#) (byte[] value, int offset, int nbits)
- virtual void [EncodeBits](#) (byte[] value, int offset, int nbits, System.String ident)
- virtual void [EncodeBits](#) (byte value, int nbits)
- virtual void [EncodeCharString](#) (System.String value, int nchars, int offset, int abpc, int ubpc, Asn1CharSet charSet)
- virtual void [EncodeConsWholeNumber](#) (long adjustedValue, long rangeValue)
- virtual void [EncodeConsWholeNumber](#) (long adjustedValue, long rangeValue, System.String ident)
- virtual void [EncodeInt](#) (long value, bool encodeLen, bool signExtend)
- virtual void [EncodeInt](#) (long value, bool encodeLen, bool signExtend, System.String ident)
- virtual void [EncodeInt](#) (long value, int nbits)
- virtual void [EncodeInt](#) (long value, int nbits, System.String ident)
- virtual void [EncodeLength](#) (long value, long lower, long upper)
- virtual long [EncodeLength](#) (long value)
- virtual void [EncodeLengthEOM](#) (long value)
- virtual void [EncodeOctetString](#) (byte[] value, int offset, int nbytes)
- virtual void [EncodeOIDLengthAndValue](#) (int[] value)
- virtual void [EncodeOpenType](#) (Asn1PerEncodeBuffer buffer, System.String elemName)
- virtual void [EncodeOpenType](#) (byte[] value, int offset, int nbytes)
- virtual void [EncodeRelOIDLengthAndValue](#) (int[] value)
- virtual void [EncodeSmallNonNegWholeNumber](#) (int value)
- override System.IO.Stream [GetInputStream](#) ()
- override void [HexDump](#) ()
- virtual bool [IsAligned](#) ()
- override void [Reset](#) ()
- virtual void [ReverseBytes](#) (int offset, int nbytes)
- virtual void [SetAligned](#) (bool value)
- override System.String [ToString](#) ()
- override void [Write](#) (System.IO.Stream outs)

Protected Member Functions

- internal override void [CheckSize](#) (int bytesRequired)

Protected Attributes

- internal [Asn1PerTraceHandler](#) [mTraceHandler](#)

Properties

- virtual byte[] [Buffer](#) [get]
- virtual System.IO.MemoryStream [ByteArrayInputStream](#) [get]
- virtual int [ByteIndex](#) [get]
- virtual int [MsgBitCnt](#) [get]
- virtual int [MsgByteCnt](#) [get]
- override byte[] [MsgCopy](#) [get]
- override int [MsgLength](#) [get]
- virtual [Asn1PerTraceHandler TraceHandler](#) [get]

1.18.1 Detailed Description

This class handles the encoding of ASN.1 messages as specified in the Packed Encoding Rules (PER) ITU-T X.691 standard.

1.18.2 Constructor & Destructor Documentation

1.18.2.1 [Asn1PerEncodeBuffer](#) (bool *aligned*)

This constructor creates a PER encode buffer object with the default size increment. Whenever the buffer becomes full, the buffer will be expanded by the `sizeIncrement` size.

Parameters

aligned `true` for PER aligned or `false` for PER unaligned encoding.

1.18.2.2 [Asn1PerEncodeBuffer](#) (bool *aligned*, int *sizeIncrement*)

This constructor creates a PER encode buffer object with the given size increment. Whenever the buffer becomes full, the buffer will be expanded by the `sizeIncrement` size. This size should be large enough to prevent resizing in normal operation.

Parameters

aligned `true` for PER aligned or `false` for PER unaligned encoding.

sizeIncrement The initial size in bytes of an encode buffer. If the buffer becomes full, it will be expanded by the amount.

1.18.3 Member Function Documentation

1.18.3.1 `override void BinDump` (System.IO.StreamWriter *outs*, System.String *varName*)

This method dumps the encoded message in a human-readable format showing a bit trace of all fields to the given print output stream.

Parameters

outs StreamWriter object to which output should be written

varName Name of top-level message object variable

1.18.3.2 virtual void ByteAlign () [virtual]

This methods byte-aligns the buffer.

Implements [Asn1PerMessageBuffer](#).

1.18.3.3 internal override void CheckSize (int bytesRequired) [protected]

This method determines if the encode buffer can hold the requested number of bytes. If not, the buffer is expanded.

Parameters

bytesRequired Number of required bytes.

1.18.3.4 override void Copy (byte[] value)

This method copies multiple bytes to the encode buffer

Parameters

value Array of bytes to copy to the encode buffer

1.18.3.5 override void Copy (byte value)

This method is used to copy a single byte to the encode buffer.

Parameters

value The byte value to copy

1.18.3.6 virtual void EncodeBit (bool value) [virtual]

This method encodes a single bit value. The *ident* argument which is used for tracing is defaulted to 'value'.

Parameters

value Boolean value of bit to be encoded.

1.18.3.7 virtual void EncodeBit (bool value, System.String ident) [virtual]

This method encodes a single bit value.

Parameters

value Boolean value of bit to be encoded.

ident Bit field identifier name for tracing.

1.18.3.8 virtual void EncodeBits (byte[] value, int offset, int nbits) [virtual]

This method encodes bit values from an array of octets. The `ident` argument which is used for tracing is defaulted to 'value'.

Parameters

- value* Octet array containing bits to be encoded
- offset* Starting byte offset in value
- nbits* Number of bits to encode

1.18.3.9 virtual void EncodeBits (byte[] value, int offset, int nbits, System.String ident) [virtual]

This method encodes bit values from an array of octets.

Parameters

- value* Octet array containing bits to be encoded
- offset* Starting byte offset in value
- nbits* Number of bits to encode
- ident* Bit field identifier name for tracing.

1.18.3.10 virtual void EncodeBits (byte value, int nbits) [virtual]

This method encodes bit values from an octet. The most significant bits from the octet are encoded.

Parameters

- value* Octet containing bits to be encoded
- nbits* Number of bits to encode

1.18.3.11 virtual void EncodeCharString (System.String value, int nchars, int offset, int abpc, int ubpc, Asn1CharSet charSet) [virtual]

This method encodes the contents of a known-multiplier character string type. This version assumes a permitted alphabet constraint was specified.

Parameters

- value* String containing characters to encode
- nchars* Number of characters from string to encode
- offset* Offset to first char in string to encode
- abpc* Number of bits per character (aligned)
- ubpc* Number of bits per character (unaligned)
- charSet* Object representing permitted alphabet constraint character set (optional)

1.18.3.12 virtual void EncodeConsWholeNumber (long *adjustedValue*, long *rangeValue*) [virtual]

This method implements the rules to encode a constrained whole number as specified in section 10.5 of the X.691 standard. The *ident* argument which is used for tracing is defaulted to 'value'.

Parameters

adjustedValue Adjusted value to be encoded = value - lower range endpoint value

rangeValue lower - upper + 1

1.18.3.13 virtual void EncodeConsWholeNumber (long *adjustedValue*, long *rangeValue*, System.String *ident*) [virtual]

This method implements the rules to encode a constrained whole number as specified in section 10.5 of the X.691 standard.

Parameters

adjustedValue Adjusted value to be encoded = value - lower range endpoint value

rangeValue lower - upper + 1

ident Tracing identifier

1.18.3.14 virtual void EncodeInt (long *value*, bool *encodeLen*, bool *signExtend*) [virtual]

This method implements the rules to encode either a non-negative binary integer as specified in section 10.3 or a two's complement binary integer as specified in section 10.4 of the X.691 standard. The *ident* argument which is used for tracing is defaulted to 'value'.

Parameters

value Integer value to be encoded

encodeLen Flag indicating length determinant should be encoded before encoding integer value.

signExtend Flag indicating if sign extension should be performed.

1.18.3.15 virtual void EncodeInt (long *value*, bool *encodeLen*, bool *signExtend*, System.String *ident*) [virtual]

This method implements the rules to encode either a non-negative binary integer as specified in section 10.3 or a two's complement binary integer as specified in section 10.4 of the X.691 standard.

Parameters

value Integer value to be encoded

encodeLen Flag indicating length determinant should be encoded before encoding integer value.

signExtend Flag indicating if sign extension should be performed.

ident Tracing identifier

1.18.3.16 virtual void EncodeInt (long value, int nbits) [virtual]

This method encodes bit values from an integer value. The least significant bits from the integer are encoded. The `ident` argument which is used for tracing is defaulted to 'value'.

Parameters

value Integer containing bits to be encoded
nbits Number of bits to encode

1.18.3.17 virtual void EncodeInt (long value, int nbits, System.String ident) [virtual]

This method encodes bit values from an integer value. The least significant bits from the integer are encoded.

Parameters

value Integer containing bits to be encoded
nbits Number of bits to encode
ident Tracing identifier

1.18.3.18 virtual void EncodeLength (long value, long lower, long upper) [virtual]

This method encodes a constrained length determinant value.

Parameters

value Length value to be encoded
lower Lower bound (inclusive) of length value range
upper Upper bound (inclusive) of length value range

1.18.3.19 virtual long EncodeLength (long value) [virtual]

This method encodes a general (unconstrained) length determinant value as described in section 10.9 or the X.691 standard.

Parameters

value Length value to be encoded

Returns

Value that was actually encoded. This may be less than the value that was passed in if fragmentation was done (i.e the value was $\geq 16k$).

1.18.3.20 virtual void EncodeLengthEOM (long value) [virtual]

This method checks to see if a zero byte needs to be added after a fragmented length has been encoded. It will add it to the byte stream if necessary.

Parameters

value Original length value that was encoded.

1.18.3.21 virtual void EncodeOctetString (byte[] value, int offset, int nbytes) [virtual]

This method encodes the given array of bytes as an unconstrained octet string value.

Parameters

value Byte array containing data to encode. This is assumed to contain a previously encoded PER component.

offset Starting offset in byte array value

nbytes Number of bytes to encode

1.18.3.22 virtual void EncodeOIDLengthAndValue (int[] value) [virtual]

This method encodes the length and contents of an object identifier value.

Parameters

value Integer array containing arcs to encode

1.18.3.23 virtual void EncodeOpenType (Asn1PerEncodeBuffer buffer, System.String elemName) [virtual]

This overloaded version of encodeOpenType will encode the component in the given PER encode buffer into this PER encode buffer.

Parameters

buffer PER encode buffer containing encoded message component.

elemName Name of element being encoded.

1.18.3.24 virtual void EncodeOpenType (byte[] value, int offset, int nbytes) [virtual]

This method encodes the given array of bytes as an open type.

Parameters

value Byte array containing data to encode. This is assumed to contain a previously encoded PER component.

offset Starting offset in byte array value

nbytes Number of bytes to encode

1.18.3.25 virtual void EncodeRelOIDLengthAndValue (int[] value) [virtual]

This method encodes the length and contents of a relative object identifier value.

Parameters

value Integer array containing arcs to encode

1.18.3.26 virtual void EncodeSmallNonNegWholeNumber (int *value*) [virtual]

This method implements the rules to encode a small non-negative whole number as specified in section 10.6 of the X.691 standard.

Parameters

value Value to be encoded

1.18.3.27 override System.IO.Stream GetInputStream ()

This method returns an input stream representing the encoded message. This method is defined as abstract in the base class and must be implemented by all derived classes. In this case, a byte array input stream is returned.

Returns

Input stream containing encoded message

Implements [Asn1PerMessageBuffer](#).

1.18.3.28 override void HexDump ()

This method dumps the encoded message in hex/ascii format to the standard output stream.

1.18.3.29 virtual bool IsAligned () [virtual]

This method is used to test if PER aligned encoding has been specified.

Returns

`true` for PER aligned encoding or `false` for unaligned encoding.

Implements [Asn1PerMessageBuffer](#).

1.18.3.30 override void Reset ()

This method resets the buffer object so that it can be reused to encode another PER message. Any previously encoded data is lost.

1.18.3.31 virtual void ReverseBytes (int *offset*, int *nbytes*) [virtual]

This method reverses a series of bytes at a given offset within the encode buffer.

Parameters

offset Starting byte offset within the buffer

nbytes Number of bytes to reverse

1.18.3.32 virtual void SetAligned (bool *value*) [virtual]

This method is used to turn PER aligned encoding on or off

Parameters

value true for PER aligned encoding or false for unaligned encoding.

1.18.3.33 override System.String ToString ()

This method will return a string representation of the data in the encode buffer. The format is hex characters.

Returns

Stringified representation of the value

1.18.3.34 override void Write (System.IO.Stream *outs*)

This method writes the encoded record to the given output stream.

Parameters

outs Output stream to which record is to be written

1.18.4 Member Data Documentation

1.18.4.1 internal Asn1PerTraceHandler mTraceHandler [protected]

Variable holds the PER message trace handler

1.18.5 Property Documentation

1.18.5.1 virtual byte [] Buffer [get]

Gets a reference to the byte buffer used to hold the encoded message.

Value: Byte buffer reference

1.18.5.2 virtual System.IO.MemoryStream ByteArrayInputStream [get]

Gets a reference to a byte array input stream representing the encoded message. This is the preferred way to access the contents of the encoded message as it is the most efficient.

Value: byte array input stream containing encoded message

1.18.5.3 virtual int ByteIndex [get]

Gets the current byte index into the encode buffer.

Value: Byte index value

1.18.5.4 virtual int MsgBitCnt [get]

Gets the number of bits in the encoded PER message.

Value: Count of bits in encoded message

Implements [Asn1PerMessageBuffer](#).

1.18.5.5 virtual int MsgByteCnt [get]

Gets the number of bytes in the encoded PER message. The number is rounded up to include the last byte if one or more bits have been set in that byte.

Value: Count of bytes in encoded message

1.18.5.6 override byte [] MsgCopy [get]

Gets the encoded message in a byte array. This is less efficient than the `ByteArrayInputStream` property because the message contents must be copied to a newly created byte array.

Value: byte array containing encoded message

1.18.5.7 override int MsgLength [get]

Gets the length (in bytes) of the encoded message component.

Value: length of encoded message component

1.18.5.8 virtual Asn1PerTraceHandler TraceHandler [get]

Gets a reference to the internal trace handler object used to trace the bit fields within a PER message.

Value: [Asn1PerTraceHandler](#) object

Implements [Asn1PerMessageBuffer](#).

1.19 Asn1PerEncodeTraceHandler Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1PerTraceHandler](#).

Public Member Functions

- [Asn1PerEncodeTraceHandler](#) ([Asn1PerEncodeBuffer](#) messageBuffer)
- override void [Enable](#) ()
- override void [Print](#) (System.IO.StreamWriter outs, System.String varName)
- override void [Reset](#) ()

1.19.1 Detailed Description

This is a utility class for handling the collection and printing of PER bit field trace information. An object of the class is present within both the [Asn1PerEncodeBuffer](#) and [Asn1PerDecodeBuffer](#) classes. It is accessed using the 'TraceHandler' property from objects of these classes.

1.19.2 Constructor & Destructor Documentation

1.19.2.1 Asn1PerEncodeTraceHandler ([Asn1PerEncodeBuffer](#) *messageBuffer*)

This constructor initializes internal trace handler member variables.

Parameters

messageBuffer PER encode message buffer object reference

1.19.3 Member Function Documentation

1.19.3.1 override void [Enable](#) () [virtual]

This method is used to turn PER bit tracing on

Implements [Asn1PerTraceHandler](#).

1.19.3.2 override void [Print](#) (System.IO.StreamWriter *outs*, System.String *varName*) [virtual]

This method prints the trace to the given output stream in a default format.

Parameters

outs Print stream to which output is to be written.

varName Name of the object variable being printed.

Implements [Asn1PerTraceHandler](#).

1.19.3.3 override void [Reset](#) () [virtual]

This method resets the trace bit field list.

Implements [Asn1PerTraceHandler](#).

1.20 Asn1PerInputStream Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1PerDecodeBuffer](#).

Public Member Functions

- [Asn1PerInputStream](#) (System.IO.Stream istream, bool aligned)
- virtual int [Available](#) ()
- virtual void [Close](#) ()
- override void [Mark](#) ()
- virtual bool [MarkSupported](#) ()
- override void [Reset](#) ()
- override long [Skip](#) (long nbytes)

1.20.1 Detailed Description

This class handles the input stream for decoding of ASN.1 messages as specified in the Packed Encoding Rules (PER) ITU-T X.691 standard.

1.20.2 Constructor & Destructor Documentation

1.20.2.1 Asn1PerInputStream (System.IO.Stream *istream*, bool *aligned*)

This constructor creates a PER input stream object that references an encoded ASN.1 message. In this case, the message is passed in using an System.IO.Stream object.

Parameters

istream Input stream containing an encoded ASN.1 message.

aligned Boolean specifying PER aligned or unaligned encoding.

1.20.3 Member Function Documentation

1.20.3.1 virtual int Available () [virtual]

Returns the number of bytes that can be read (or skipped over) from this input stream without blocking by the next caller of a method for this input stream. The next caller might be the same thread or another thread.

Returns

the number of bytes that can be read from this input stream without blocking.

Exceptions

System.SystemException if an I/O error occurs.

1.20.3.2 virtual void Close () [virtual]

Closes this input stream and releases any system resources associated with the stream.

Exceptions

System.SystemException if an I/O error occurs.

1.20.3.3 override void Mark ()

This method is used to mark the current position in the input stream for retry processing or resetting the input stream position to current position.

1.20.3.4 virtual bool MarkSupported () [virtual]

Tests if this input stream supports the seeking. This method is equivalent to C# `CanSeek` method of `System.IO.Stream`.

Returns

`true` if input stream supports seeking; Otherwise `false`.

1.20.3.5 override void Reset ()

This method is used to reset the current position in the input stream back to the location of the last 'mark' call. It is equivalent to calling 'Stream.Position' to marked location.

1.20.3.6 override long Skip (long nbytes)

This method will skip over the requested number of bytes in the input stream.

Parameters

nbytes Number of bytes to skip

Exceptions

System.SystemException if an I/O error occurs.

Returns

Skipped number of bytes

1.21 Asn1PerMessageBuffer Interface Reference

Inherited by [Asn1PerDecodeBuffer](#), and [Asn1PerEncodeBuffer](#).

Public Member Functions

- void [ByteAlign](#) ()
- System.IO.Stream [GetInputStream](#) ()
- bool [IsAligned](#) ()

Properties

- int [MsgBitCnt](#) [get]
- [Asn1PerTraceHandler](#) [TraceHandler](#) [get]

1.21.1 Detailed Description

This interface defines constants and methods specific to encoding and decoding PER messages. All of the PER message buffer classes implement this interface.

1.21.2 Member Function Documentation

1.21.2.1 void [ByteAlign](#) ()

This method handles byte-alignment for aligned PER encoding or decoding.

Implemented in [Asn1PerDecodeBuffer](#), and [Asn1PerEncodeBuffer](#).

1.21.2.2 System.IO.Stream [GetInputStream](#) ()

This method returns an input stream object that represents the message being encoded or decoded.

Returns

Stream containing message

Implemented in [Asn1PerEncodeBuffer](#).

1.21.2.3 bool [IsAligned](#) ()

This method returns a flag indicating if PER aligned encoding is currently enabled (if false, unaligned is in effect).

Returns

true is aligned; otherwise false

Implemented in [Asn1PerDecodeBuffer](#), and [Asn1PerEncodeBuffer](#).

1.21.3 Property Documentation

1.21.3.1 `int MsgBitCnt` [get]

Gets the number of bits in the PER message.

Value: Count of bits in message

Implemented in [Asn1PerDecodeBuffer](#), and [Asn1PerEncodeBuffer](#).

1.21.3.2 `Asn1PerTraceHandler TraceHandler` [get]

Gets a reference to the internal trace handler object used to trace the bit fields within a PER message.

Value: [Asn1PerTraceHandler](#) object

Implemented in [Asn1PerDecodeBuffer](#), and [Asn1PerEncodeBuffer](#).

1.22 Asn1PerOutputStream Class Reference

Public Member Functions

- virtual void [AddCaptureBuffer](#) (System.IO.MemoryStream buffer)
- [Asn1PerOutputStream](#) (System.IO.Stream os, int bufSize, bool aligned)
- [Asn1PerOutputStream](#) (System.IO.Stream os, bool aligned)
- virtual void [BinDump](#) (System.IO.StreamWriter outs, System.String varName)
- virtual void [BinDump](#) (System.String varName)
- virtual void [ByteAlign](#) ()
- override void [Close](#) ()
- virtual void [EncodeBit](#) (bool value, System.String ident)
- virtual void [EncodeBit](#) (bool value)
- virtual void [EncodeBits](#) (byte[] value, int offset, int nbits, System.String ident)
- virtual void [EncodeBits](#) (byte[] value, int offset, int nbits)
- virtual void [EncodeBits](#) (byte value, int nbits)
- virtual void [EncodeCharString](#) (System.String value, int nchars, int offset, int abpc, int ubpc, Asn1CharSet charSet)
- virtual void [EncodeConsWholeNumber](#) (long adjustedValue, long rangeValue)
- virtual void [EncodeConsWholeNumber](#) (long adjustedValue, long rangeValue, System.String ident)
- virtual void [EncodeInt](#) (long value, bool encodeLen, bool signExtend)
- virtual void [EncodeInt](#) (long value, bool encodeLen, bool signExtend, System.String ident)
- virtual void [EncodeInt](#) (long value, int nbits)
- virtual void [EncodeInt](#) (long value, int nbits, System.String ident)
- virtual void [EncodeLength](#) (long value, long lower, long upper)
- virtual long [EncodeLength](#) (long value)
- virtual void [EncodeLengthEOM](#) (long value)
- virtual void [EncodeOctetString](#) (byte[] value, int offset, int nbytes)
- virtual void [EncodeOIDLengthAndValue](#) (int[] value)
- virtual void [EncodeOpenType](#) (byte[] value, int offset, int nbytes)
- virtual void [EncodeRelOIDLengthAndValue](#) (int[] value)
- virtual void [EncodeSmallNonNegWholeNumber](#) (int value)
- override void [Flush](#) ()
- virtual void [RemoveCaptureBuffer](#) (System.IO.MemoryStream buffer)
- override void [Write](#) (System.Byte[] b, int off, int len)
- override void [Write](#) (byte[] b)
- override void [WriteByte](#) (byte b)
- override void [WriteByte](#) (int b)

Protected Attributes

- internal [Asn1PerOutputStreamTraceHandler mTraceHandler](#)

Properties

- virtual bool [Aligned](#) [get]
- virtual [Asn1PerTraceHandler TraceHandler](#) [get]

1.22.1 Detailed Description

This class handles the output stream for encoding of ASN.1 messages as specified in the Packed Encoding Rules (PER) ITU-T X.691 standard.

1.22.2 Constructor & Destructor Documentation

1.22.2.1 `Asn1PerOutputStream` (`System.IO.Stream os`, `bool aligned`)

This constructor creates a buffered PER output stream object with the default size of buffer. Whenever the buffer becomes full, the buffer will be flushed to the stream.

Parameters

os The underlying `System.IO.Stream` object.

aligned Indicates whether PER aligned or unaligned encoding should be done.

1.22.2.2 `Asn1PerOutputStream` (`System.IO.Stream os`, `int bufSize`, `bool aligned`)

This constructor creates a buffered PER output stream object with the specified size of buffer. Whenever the buffer becomes full, the buffer will be flushed to the stream.

Parameters

os The underlying `System.IO.Stream` object.

bufSize The buffer size.

aligned `true` for PER aligned or `false` for PER unaligned encoding.

1.22.3 Member Function Documentation

1.22.3.1 `virtual void AddCaptureBuffer` (`System.IO.MemoryStream buffer`) [`virtual`]

This method is used to add a capture buffer to the internal capture buffer list. A capture buffer is used to capture all bytes read from this position forward from the input stream.

Parameters

buffer Buffer into which captured bytes are to be stored

1.22.3.2 `virtual void BinDump` (`System.IO.StreamWriter outs`, `System.String varName`) [`virtual`]

This method dumps the encoded message in a human-readable format showing a bit trace of all fields to the given print output stream.

Parameters

outs StreamWriter object to which output should be written

varName Name of top-level message object variable

1.22.3.3 virtual void BinDump (System.String varName) [virtual]

This method invokes an overloaded version of BinDump to dump the encoded message to standard output.

Parameters

varName Name of top-level message object variable

1.22.3.4 virtual void ByteAlign () [virtual]

This methods byte-aligns the buffer.

1.22.3.5 override void Close ()

Close the stream. Writes all bytes (even unfinished) before closing. Throws, exception thrown by the underlying System.IO.Stream object.

1.22.3.6 virtual void EncodeBit (bool value, System.String ident) [virtual]

This method encodes a single bit value.

Throws, exception thrown by the underlying System.IO.Stream object.

Parameters

value Boolean value of bit to be encoded.

ident Bit field identifier name for tracing.

Exceptions

Asn1Exception Any exception thrown by the underlying [Asn1PerEncodeBuffer](#).

1.22.3.7 virtual void EncodeBit (bool value) [virtual]

This method encodes a single bit value.

Throws, exception thrown by the underlying System.IO.Stream object.

Parameters

value Boolean value of bit to be encoded.

Exceptions

Asn1Exception Any exception thrown by the underlying [Asn1PerEncodeBuffer](#).

1.22.3.8 virtual void EncodeBits (byte[] value, int offset, int nbits, System.String ident) [virtual]

This method encodes bit values from an array of octets.

Throws, exception thrown by the underlying System.IO.Stream object.

Parameters

value Octet array containing bits to be encoded
offset Starting byte offset in value
nbits Number of bits to encode
ident Bit field identifier name for tracing.

Exceptions

Asn1InvalidArgException Any exception thrown by the underlying [Asn1PerEncodeBuffer](#).

1.22.3.9 virtual void EncodeBits (byte[] value, int offset, int nbits) [virtual]

This method encodes bit values from an array of octets.

Throws, exception thrown by the underlying System.IO.Stream object.

Parameters

value Octet array containing bits to be encoded
offset Starting byte offset in value
nbits Number of bits to encode

Exceptions

Asn1InvalidArgException Any exception thrown by the underlying [Asn1PerEncodeBuffer](#).

1.22.3.10 virtual void EncodeBits (byte value, int nbits) [virtual]

This method encodes bit values from an octet. The most significant bits from the octet are encoded.

Throws, exception thrown by the underlying System.IO.Stream object.

Parameters

value Octet containing bits to be encoded
nbits Number of bits to encode

Exceptions

Asn1InvalidArgException Any exception thrown by the underlying [Asn1PerEncodeBuffer](#).

1.22.3.11 virtual void EncodeCharString (System.String value, int nchars, int offset, int abpc, int ubpc, Asn1CharSet charSet) [virtual]

This method encodes the contents of a known-multiplier character string type. This version assumes a permitted alphabet constraint was specified.

Throws, exception thrown by the underlying System.IO.Stream object.

Parameters

value String containing characters to encode

nchars Number of characters from string to encode
offset Offset to first char in string to encode
abpc Number of bits per character (aligned)
ubpc Number of bits per character (unaligned)
charSet Object representing permitted alphabet constraint character set (optional)

Exceptions

Asn1Exception Any exception thrown by the underlying [Asn1PerEncodeBuffer](#).

1.22.3.12 virtual void EncodeConsWholeNumber (long *adjustedValue*, long *rangeValue*) [virtual]

This method implements the rules to encode a constrained whole number as specified in section 10.5 of the X.691 standard.

Throws, exception thrown by the underlying System.IO.Stream object.

Parameters

adjustedValue Adjusted value to be encoded = value - lower range endpoint value
rangeValue lower - upper + 1

Exceptions

Asn1InvalidArgException Any exception thrown by the underlying [Asn1PerEncodeBuffer](#).

1.22.3.13 virtual void EncodeConsWholeNumber (long *adjustedValue*, long *rangeValue*, System.String *ident*) [virtual]

This method implements the rules to encode a constrained whole number as specified in section 10.5 of the X.691 standard.

Throws, exception thrown by the underlying System.IO.Stream object.

Parameters

adjustedValue Adjusted value to be encoded = value - lower range endpoint value
rangeValue lower - upper + 1
ident Bit field identifier name for tracing.

Exceptions

Asn1InvalidArgException Any exception thrown by the underlying [Asn1PerEncodeBuffer](#).

1.22.3.14 virtual void EncodeInt (long *value*, bool *encodeLen*, bool *signExtend*) [virtual]

This method implements the rules to encode either a non-negative binary integer as specified in section 10.3 or a two's complement binary integer as specified in section 10.4 of the X.691 standard.

Throws, exception thrown by the underlying System.IO.Stream object.

Parameters

value Integer value to be encoded

encodeLen Flag indicating length determinant should be encoded before encoding integer value.

signExtend Flag indicating if sign extension should be performed.

Exceptions

Asn1InvalidArgException Any exception thrown by the underlying [Asn1PerEncodeBuffer](#).

1.22.3.15 virtual void EncodeInt (long value, bool encodeLen, bool signExtend, System.String ident) [virtual]

This method implements the rules to encode either a non-negative binary integer as specified in section 10.3 or a two's complement binary integer as specified in section 10.4 of the X.691 standard.

Throws, exception thrown by the underlying System.IO.Stream object.

Parameters

value Integer value to be encoded

encodeLen Flag indicating length determinant should be encoded before encoding integer value.

signExtend Flag indicating if sign extension should be performed.

ident Bit field identifier name for tracing.

Exceptions

Asn1InvalidArgException Any exception thrown by the underlying [Asn1PerEncodeBuffer](#).

1.22.3.16 virtual void EncodeInt (long value, int nbits) [virtual]

This method encodes bit values from an integer value. The least significant bits from the integer are encoded.

Throws, exception thrown by the underlying System.IO.Stream object.

Parameters

value Integer containing bits to be encoded

nbits Number of bits to encode

Exceptions

Asn1InvalidArgException Any exception thrown by the underlying [Asn1PerEncodeBuffer](#).

1.22.3.17 virtual void EncodeInt (long value, int nbits, System.String ident) [virtual]

This method encodes bit values from an integer value. The least significant bits from the integer are encoded.

Throws, exception thrown by the underlying System.IO.Stream object.

Parameters

value Integer containing bits to be encoded

nbits Number of bits to encode
ident Bit field identifier name for tracing.

Exceptions

Asn1InvalidArgException Any exception thrown by the underlying [Asn1PerEncodeBuffer](#).

1.22.3.18 virtual void EncodeLength (long value, long lower, long upper) [virtual]

This method encodes a constrained length determinant value.

Throws, exception thrown by the underlying System.IO.Stream object.

Parameters

value Length value to be encoded
lower Lower bound (inclusive) of length value range
upper Upper bound (inclusive) of length value range

Exceptions

Asn1Exception Any exception thrown by the underlying [Asn1PerEncodeBuffer](#).

1.22.3.19 virtual long EncodeLength (long value) [virtual]

This method encodes a general (unconstrained) length determinant value as described in section 10.9 or the X.691 standard.

Throws, exception thrown by the underlying System.IO.Stream object.

Parameters

value Length value to be encoded

Returns

Value that was actually encoded. This may be less than the value that was passed in if fragmentation was done (i.e the value was $\geq 16k$).

Exceptions

Asn1InvalidArgException Any exception thrown by the underlying [Asn1PerEncodeBuffer](#).

1.22.3.20 virtual void EncodeLengthEOM (long value) [virtual]

This method checks to see if a zero byte needs to be added after a fragmented length has been encoded. It will add it to the byte stream if necessary.

Throws, exception thrown by the underlying System.IO.Stream object.

Parameters

value Original length value that was encoded.

Exceptions

Asn1Exception Any exception thrown by the underlying [Asn1PerEncodeBuffer](#).

1.22.3.21 virtual void EncodeOctetString (byte[] value, int offset, int nbytes) [virtual]

This method encodes the given array of bytes as an unconstrained octet string value.

Throws, exception thrown by the underlying System.IO.Stream object.

Parameters

value Byte array containing data to encode. This is assumed to contain a previously encoded PER component.

offset Starting offset in byte array value

nbytes Number of bytes to encode

Exceptions

Asn1Exception Any exception thrown by the underlying [Asn1PerEncodeBuffer](#).

1.22.3.22 virtual void EncodeOIDLengthAndValue (int[] value) [virtual]

This method encodes the length and contents of an object identifier value.

Throws, exception thrown by the underlying System.IO.Stream object.

Parameters

value Integer array containing arcs to encode

Exceptions

Asn1Exception Any exception thrown by the underlying [Asn1PerEncodeBuffer](#).

1.22.3.23 virtual void EncodeOpenType (byte[] value, int offset, int nbytes) [virtual]

This method encodes the given array of bytes as an open type.

Throws, exception thrown by the underlying System.IO.Stream object.

Parameters

value Byte array containing data to encode. This is assumed to contain a previously encoded PER component.

offset Starting offset in byte array value

nbytes Number of bytes to encode

Exceptions

Asn1Exception Any exception thrown by the underlying [Asn1PerEncodeBuffer](#).

1.22.3.24 virtual void EncodeRelOIDLengthAndValue (int[] value) [virtual]

This method encodes the length and contents of a relative object identifier value.

Throws, exception thrown by the underlying System.IO.Stream object.

Parameters

value Integer array containing arcs to encode

Exceptions

Asn1Exception Any exception thrown by the underlying [Asn1PerEncodeBuffer](#).

1.22.3.25 virtual void EncodeSmallNonNegWholeNumber (int *value*) [virtual]

This method implements the rules to encode a small non-negative whole number as specified in section 10.6 of the X.691 standard.

Throws, exception thrown by the underlying System.IO.Stream object.

Parameters

value Value to be encoded

Exceptions

Asn1InvalidArgException Any exception thrown by the underlying [Asn1PerEncodeBuffer](#).

1.22.3.26 override void Flush ()

Flush the buffer to the stream. It writes whole bytes only. Throws, exception thrown by the underlying System.IO.Stream object.

1.22.3.27 virtual void RemoveCaptureBuffer (System.IO.MemoryStream *buffer*) [virtual]

This method is used to remove a capture buffer from the internal capture buffer list. The add and remove methods can be used to get a set of raw bytes from the input stream for further processing.

Parameters

buffer Buffer in which captured bytes stored

1.22.3.28 override void Write (System.Byte[] *b*, int *off*, int *len*)

Writes *len* bytes from the specified byte array to this output stream.

Parameters

b the data.

off The offset in array at which to begin write.

len The number of bytes to write.

Exceptions

System.SystemException if an I/O error occurs. In particular, write call after the the output stream is closed.

1.22.3.29 override void Write (byte[] b)

Writes `b.length` bytes from the specified byte array to this output stream. The general contract for `write(b)` is that it should have exactly the same effect as the call `Write(b, 0, b.length)`.

Parameters

b the binary data.

Exceptions

System.SystemException if an I/O error occurs.

1.22.3.30 override void WriteByte (byte b)

Writes the specified byte to this output stream.

Parameters

b the byte.

Exceptions

System.SystemException if an I/O error occurs. In particular, an write call after the output stream has been closed.

1.22.3.31 override void WriteByte (int b)

Writes the specified byte to this output stream.

Parameters

b the byte.

Exceptions

System.SystemException if an I/O error occurs. In particular, an write call after the output stream has been closed.

1.22.4 Member Data Documentation

1.22.4.1 internal Asn1PerOutputStreamTraceHandler mTraceHandler [protected]

Variable holds the PER message trace handler

1.22.5 Property Documentation

1.22.5.1 virtual bool Aligned [get]

Gets PER aligned encoding has been specified.

Value: `true` is aligned; otherwise `false`

1.22.5.2 virtual Asn1PerTraceHandler TraceHandler [get]

Gets a reference to the internal trace handler object used to trace the bit fields within a PER message.

Value: [Asn1PerTraceHandler](#) object

1.23 Asn1PerOutputStreamTraceHandler Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1PerTraceHandler](#).

Public Member Functions

- [Asn1PerOutputStreamTraceHandler](#) ([Asn1PerOutputStream](#) outs)
- override void [Enable](#) ()
- override void [Print](#) (System.IO.StreamWriter outs, System.String varName)
- override void [Reset](#) ()
- virtual void [ResetTrace](#) ()

1.23.1 Detailed Description

This is a utility class for handling the collection and printing of PER bit field trace information for PER output stream. An object of the class is present in the [Asn1PerOutputStream](#) classes. It is accessed using the 'TraceHandler' property from objects of these classes.

1.23.2 Constructor & Destructor Documentation

1.23.2.1 Asn1PerOutputStreamTraceHandler (Asn1PerOutputStream outs)

This constructor initializes the internal trace handler member variables.

Parameters

outs PER message stream object reference

1.23.3 Member Function Documentation

1.23.3.1 override void Enable () [virtual]

This method is used to turn PER bit tracing on

Implements [Asn1PerTraceHandler](#).

1.23.3.2 override void Print (System.IO.StreamWriter outs, System.String varName) [virtual]

This method prints the trace to the given output stream in a default format.

Parameters

outs Print stream to which output is to be written.

varName Name of the object variable being printed.

Implements [Asn1PerTraceHandler](#).

1.23.3.3 override void Reset () [virtual]

This method does nothing here.

Implements [Asn1PerTraceHandler](#).

1.23.3.4 virtual void ResetTrace () [virtual]

This method resets the trace bit field list.

1.24 Asn1PerTraceHandler Class Reference

Inherited by [Asn1PerDecodeTraceHandler](#), [Asn1PerEncodeTraceHandler](#), and [Asn1PerOutputStreamTraceHandler](#).

Public Member Functions

- virtual void [AddElemName](#) (System.String name, int arrayx)
- abstract void [Enable](#) ()
- virtual void [NewBitField](#) (System.String name, int bitCount)
- abstract void [Print](#) (System.IO.StreamWriter outs, System.String varName)
- virtual void [RemoveLastElemName](#) ()
- abstract void [Reset](#) ()
- virtual void [SetBitCount](#) ()
- virtual void [SetBitOffset](#) ()

Protected Member Functions

- internal [Asn1PerTraceHandler](#) ([Asn1PerMessageBuffer](#) messageBuffer)

Protected Attributes

- internal [Asn1PerBitFieldList](#) mBitFieldList

Properties

- virtual [Asn1PerBitFieldList](#) BitFieldList [get]

1.24.1 Detailed Description

This is the abstract base class for the PER encode and decode trace handler derived classes.

1.24.2 Constructor & Destructor Documentation

1.24.2.1 internal Asn1PerTraceHandler (Asn1PerMessageBuffer *messageBuffer*) [protected]

This constructor initializes internal trace handler member variables.

Parameters

messageBuffer PER message buffer object reference

1.24.3 Member Function Documentation

1.24.3.1 virtual void AddElemName (System.String *name*, int *arrayx*) [virtual]

This method adds an element name to the current fully qualified name. The fully qualified name is a string of name components separated by dots (ex. a.b.c).

Parameters

name Name component to append to string

arrayx Array index if named item is an element in an array (set to -1 otherwise)

1.24.3.2 abstract void Enable () [pure virtual]

This method is used to turn PER bit tracing on or off

Implemented in [Asn1PerEncodeTraceHandler](#), [Asn1PerDecodeTraceHandler](#), and [Asn1PerOutputStreamTraceHandler](#).

1.24.3.3 virtual void NewBitField (System.String name, int bitCount) [virtual]

This method creates a new bit field and appends it to the bit field list.

Parameters

name Name suffix to append to the current fully qualified name.

bitCount Number of bits in the bit field.

1.24.3.4 abstract void Print (System.IO.StreamWriter outs, System.String varName) [pure virtual]

This method prints the trace to the given output stream in a default format.

Parameters

outs Print stream to which output is to be written.

varName Name of the object variable being printed.

Implemented in [Asn1PerEncodeTraceHandler](#), [Asn1PerDecodeTraceHandler](#), and [Asn1PerOutputStreamTraceHandler](#).

1.24.3.5 virtual void RemoveLastElemName () [virtual]

This method removes the last element name in the current fully qualified name string. For example, if the current string is 'a.b.c', it will be 'a.b' after calling this method.

1.24.3.6 abstract void Reset () [pure virtual]

This method resets the trace bit field list.

Implemented in [Asn1PerEncodeTraceHandler](#), [Asn1PerDecodeTraceHandler](#), and [Asn1PerOutputStreamTraceHandler](#).

1.24.3.7 virtual void SetBitCount () [virtual]

This method sets the bit count within the current bit field to the difference between the current bit offset and the starting bit offset currently stored in the field object.

1.24.3.8 virtual void SetBitOffset () [virtual]

This method sets the bit offset within the current bit field to the current offset within the PER message buffer.

1.24.4 Member Data Documentation

1.24.4.1 internal Asn1PerBitFieldList mBitFieldsList [protected]

Variable holds the bit field list

1.24.5 Property Documentation

1.24.5.1 virtual Asn1PerBitFieldList BitFieldsList [get]

Gets a reference to the bit field list

Value: bit field list

1.25 Asn1PerUtil Class Reference

Static Public Member Functions

- static int [GetMsgBitCnt](#) (int byteCount, int bitOffset)

1.25.1 Detailed Description

This class contains general purpose static utility functions related to PER encoding/decoding

1.25.2 Member Function Documentation

1.25.2.1 static int GetMsgBitCnt (int *byteCount*, int *bitOffset*) [static]

This method returns the number of bits in an encoded PER message buffer.

Parameters

byteCount Number of full bytes in message

bitOffset Offset to current bit in last byte ((7 - 0) or -1 if no bits used).

Returns

Count of bits in encoded message

1.26 Asn1SetDuplicateException Class Reference

Public Member Functions

- [Asn1SetDuplicateException](#) ([Asn1BerDecodeBuffer](#) buffer, Asn1Tag tag)

1.26.1 Detailed Description

This class defines the 'ASN.1 set duplicate element' exception that is thrown from BER/DER methods when a SET construct is detected to more than one instance of a given tagged element..

1.26.2 Constructor & Destructor Documentation

1.26.2.1 Asn1SetDuplicateException (Asn1BerDecodeBuffer *buffer*, Asn1Tag *tag*)

This constructor creates an exception object with a textual message describing the tag of the duplicate element..

Parameters

buffer BER decode buffer object reference

tag Tag value of duplicate element

1.27 Asn1TaggedEventHandler Interface Reference

Inherited by [Asn1BerMessageDumpHandler](#).

Public Member Functions

- void [Contents](#) (byte[] data)
- void [EndElement](#) (Asn1Tag tag)
- void [StartElement](#) (Asn1Tag tag, int len, byte[] tagLenBytes)

1.27.1 Detailed Description

This interface defines the methods that must be implemented to define

a SAX-like event handler. These methods are invoked from within the generated C# decode logic when significant events occur during the parsing of an ASN.1 message.

A tagged event handler differs from a named event handler in

that it returns the tags from within a BER or DER message instead of the symbolic names. This type of handler can be used to generically parse a message without knowledge of the associated ASN.1 schema definition. It is used in conjunction with the [Asn1BerDecodeBuffer Parse](#) method.

1.27.2 Member Function Documentation

1.27.2.1 void Contents (byte[] data)

The contents callback method is invoked when the contents of a primitive data element are parsed.

Parameters

data Array containing encoded contents bytes.

Implemented in [Asn1BerMessageDumpHandler](#).

1.27.2.2 void EndElement (Asn1Tag tag)

The endElement callback method is invoked when the end of a tagged element is parsed.

Parameters

tag Parsed tag value.

Implemented in [Asn1BerMessageDumpHandler](#).

1.27.2.3 void StartElement (Asn1Tag tag, int len, byte[] tagLenBytes)

The StartElement callback method is invoked when the start of any tagged element is parsed.

Parameters

tag Parsed tag value.

len Parsed length value

tagLenBytes Array containing the encoded bytes that make up the tag/length sequence.

Implemented in [Asn1BerMessageDumpHandler](#).

1.28 Asn1TagMatchFailedException Class Reference

Public Member Functions

- [Asn1TagMatchFailedException](#) ([Asn1BerDecodeBuffer](#) buffer, Asn1Tag expectedTag)
- [Asn1TagMatchFailedException](#) ([Asn1BerDecodeBuffer](#) buffer, Asn1Tag expectedTag, Asn1Tag parsedTag)

1.28.1 Detailed Description

This class defines the 'ASN.1 tag match failed' exception that is thrown from BER/DER methods when an expected tag is not matched..

1.28.2 Constructor & Destructor Documentation

1.28.2.1 [Asn1TagMatchFailedException](#) ([Asn1BerDecodeBuffer](#) *buffer*, [Asn1Tag](#) *expectedTag*, [Asn1Tag](#) *parsedTag*)

This constructor creates an exception object with a textual message describing the expected and parsed tag values..

Parameters

buffer BER decode buffer object reference

expectedTag Expected tag value

parsedTag Parsed tag value

1.28.2.2 [Asn1TagMatchFailedException](#) ([Asn1BerDecodeBuffer](#) *buffer*, [Asn1Tag](#) *expectedTag*)

This constructor creates an exception object with a textual message describing only the expected tag value. It is used in cases where the parsed tag value cannot be determined.

Parameters

buffer BER decode buffer object reference

expectedTag Expected tag value

1.29 Asn1XerBase64OctetString Class Reference

Public Member Functions

- [Asn1XerBase64OctetString](#) (System.String value)
- [Asn1XerBase64OctetString](#) (byte[] data, int offset, int nbytes)
- [Asn1XerBase64OctetString](#) (byte[] data)
- [Asn1XerBase64OctetString](#) ()
- override void [DecodeXML](#) (System.String buffer, System.String attrs)
- override void [Encode](#) (Asn1XmlEncoder buffer, System.String elemName, System.String nsPrefix)
- override void [Encode](#) ([Asn1XerEncoder](#) buffer, System.String elemName)

1.29.1 Detailed Description

This is a container class for holding the components of an ASN.1 octet string value. This is a special version of the class that is only generated for the XER encoding rules, if Base64 encoding is used.

1.29.2 Constructor & Destructor Documentation

1.29.2.1 Asn1XerBase64OctetString ()

This constructor creates an empty octet string that can be used in a decode method call to receive an octet string value.

1.29.2.2 Asn1XerBase64OctetString (byte[] data)

This constructor initializes an octet string from the given byte array.

Parameters

data Byte array containing an octet string in binary form.

1.29.2.3 Asn1XerBase64OctetString (byte[] data, int offset, int nbytes)

This constructor initializes an octet string from a portion of the given byte array. A new byte array is created starting at the given offset and consisting of the given number of bytes.

Parameters

data Byte array containing an octet string in binary form.

offset Starting offset in data from which to copy bytes

nbytes Number of bytes to copy from target array

1.29.2.4 Asn1XerBase64OctetString (System.String value)

This constructor parses the given ASN.1 value text (either a binary or hex data string) and assigns the values to the internal bit string.

Examples of valid value formats are as follows:

Binary string: '11010010111001'B

Hex string: '0fa56920014abc'H

Char string: 'abcdefg'

Parameters

value The ASN.1 value specification text

1.29.3 Member Function Documentation

1.29.3.1 override void DecodeXML (System.String buffer, System.String attrs)

This method decodes an ASN.1 octet string type using the XML schema encoding rules(asn2xsd).

Parameters

buffer String containing data to be decoded

attrs Attributes string from element tag

1.29.3.2 override void Encode (Asn1XmlEncoder buffer, System.String elemName, System.String nsPrefix)

This method encodes ASN.1 octet string type with element and namespace prefix name tag according to the XML Encoding as specified in the XML schema standard(asn2xsd).

Parameters

buffer Encode message buffer object

elemName XML element name used to wrap string

nsPrefix Element namespace value

1.29.3.3 override void Encode (Asn1XerEncoder buffer, System.String elemName)

This method encodes ASN.1 octet string type using the XML encoding rules (XER).

Parameters

buffer Encode message buffer object

elemName XML element name used to wrap string

1.30 Asn1XerDecodeBuffer Class Reference

Public Member Functions

- [Asn1XerDecodeBuffer](#) (System.String source)

Protected Attributes

- internal [XmlSource mInputSource](#)

Properties

- virtual [XmlSource InputSource](#) [get]

1.30.1 Detailed Description

This class handles the decoding of ASN.1 messages as specified in the XML Encoding Rules (XER) as documented in the ITU-T X.693 standard. Note that this class is not derived from the `Asn1DecodeBuffer` class as are other decode buffer classes. Its purpose is to act as an input source for XML data to be read by a SAX parser.

1.30.2 Constructor & Destructor Documentation

1.30.2.1 `Asn1XerDecodeBuffer` (System.String source)

This constructor creates an XER decode buffer.

Parameters

source The source containing the XML document.

1.30.3 Member Data Documentation

1.30.3.1 internal `XmlSource mInputSource` [protected]

Variable holds the SAX input source object.

1.30.4 Property Documentation

1.30.4.1 virtual `XmlSource InputSource` [get]

Gets the SAX input source object.

Value: SAX input source object

1.31 Asn1XerElemInfo Class Reference

Public Member Functions

- [Asn1XerElemInfo](#) (System.String name, bool optional, int id)
- bool [Equals](#) (System.String name)
- override int [GetHashCode](#) ()

Properties

- virtual int [ID](#) [get]
- virtual bool [Optional](#) [get]

1.31.1 Detailed Description

This class holds XER element information needed to assign an identifier to an element after it is parsed from an XML message.

1.31.2 Constructor & Destructor Documentation

1.31.2.1 Asn1XerElemInfo (System.String name, bool optional, int id)

This constructor creates the element object.

Parameters

- name* element name
- optional* true if element is optional
- id* identifier

1.31.3 Member Function Documentation

1.31.3.1 bool Equals (System.String name)

Determines whether the specified Object is equal to the given String.

Parameters

- name* The String to compare with the current Object.

Returns

true if the specified String is equal to the current Object; otherwise, false.

1.31.3.2 override int GetHashCode ()

Serves as a hash function for a particular type, suitable for use in hashing algorithms and data structures like a hash table.

Returns

A hash code for the current Object.

1.31.4 Property Documentation

1.31.4.1 virtual int ID [get]

Returns the ID value for the element.

Value: Identifier value

1.31.4.2 virtual bool Optional [get]

Determines whether the this element is optional

Value: `true` is optional; otherwise `false`

1.32 Asn1XerEncodeBuffer Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1XerEncoder](#).

Public Member Functions

- [Asn1XerEncodeBuffer](#) (bool canonical, int sizeIncrement)
- [Asn1XerEncodeBuffer](#) (bool canonical)
- [Asn1XerEncodeBuffer](#) ()
- override void [BinDump](#) (System.IO.StreamWriter outs, System.String varName)
- virtual void [Copy](#) (System.String data)
- virtual void [Copy](#) (byte[] data, int off, int len)
- override void [Copy](#) (byte[] data)
- override void [Copy](#) (byte data)
- virtual void [DecrLevel](#) ()
- virtual void [EncodeBinStrValue](#) (byte[] bits, int nbits)
- virtual void [EncodeByte](#) (byte data)
- virtual void [EncodeData](#) (System.String data)
- virtual void [EncodeEmptyElement](#) (System.String elemName)
- virtual void [EncodeEndDocument](#) ()
- virtual void [EncodeEndElement](#) (System.String elemName)
- virtual void [EncodeHexStrValue](#) (byte[] data)
- virtual void [EncodeNamedValue](#) (System.String valueName, System.String elemName)
- virtual void [EncodeNamedValueElement](#) (System.String elemName)
- virtual void [EncodeObjectId](#) (int[] data)
- virtual void [EncodeRealValue](#) (double data, System.String elemName)
- virtual void [EncodeStartDocument](#) ()
- virtual void [EncodeStartElement](#) (System.String elemName)
- override System.IO.Stream [GetInputStream](#) ()
- virtual void [IncrLevel](#) ()
- virtual void [Indent](#) ()
- override void [Reset](#) ()
- override void [Write](#) (System.IO.Stream outs)

Protected Member Functions

- internal override void [CheckSize](#) (int bytesRequired)

Properties

- virtual byte[] [Buffer](#) [get]
- virtual bool [Canonical](#) [set]
- override byte[] [MsgCopy](#) [get]
- override int [MsgLength](#) [get]
- virtual int [State](#) [get, set]

1.32.1 Detailed Description

This class handles the encoding of ASN.1 messages as specified in the XML Encoding Rules (XER) as specified in the ITU-T X.693 standard.

1.32.2 Constructor & Destructor Documentation

1.32.2.1 `Asn1XerEncodeBuffer ()`

The default constructor creates an XER encode buffer object with the default size increment and canonical set to false.

1.32.2.2 `Asn1XerEncodeBuffer (bool canonical)`

The parameterized constructor creates an XER encode buffer object with default size increment and canonical set to the given values.

Parameters

canonical Boolean indicating a canonical or non-canonical encoding should be produced as defined in the X.693 standard.

1.32.2.3 `Asn1XerEncodeBuffer (bool canonical, int sizeIncrement)`

The parameterized constructor creates an XER encode buffer object with size increment and canonical set to the given values.

Parameters

canonical Boolean indicating a canonical or non-canonical encoding should be produced as defined in the X.693 standard.

sizeIncrement The initial size in bytes of an encode buffer. If the buffer becomes full, it will be expanded by the amount. If this parameter is set to zero, the default increment will be used.

1.32.3 Member Function Documentation

1.32.3.1 `override void BinDump (System.IO.StreamWriter outs, System.String varName)`

This method dumps the encoded message in a human-readable format showing a bit trace of all fields to the given print output stream.

Parameters

outs Output will be written to this stream

varName Name of the Decoded ASN1 Type

1.32.3.2 `internal override void CheckSize (int bytesRequired) [protected]`

This method determines if the encode buffer can hold the requested number of bytes. If not, the buffer is expanded.

Parameters

bytesRequired Number of required bytes.

1.32.3.3 virtual void Copy (System.String *data*) [virtual]

This method copies a character string to the encode buffer.

Parameters

data The string value to copy

1.32.3.4 virtual void Copy (byte[] *data*, int *off*, int *len*) [virtual]

This method copies multiple bytes to the encode buffer. It is assumed the byte are already formatted into a valid XML encoding type (for example, UTF-8).

Parameters

data Array of bytes to copy to the encode buffer

off The offset in array at which to begin copy.

len The number of bytes to copy

1.32.3.5 override void Copy (byte[] *data*)

This method copies multiple bytes to the encode buffer. It is assumed the byte are already formatted into a valid XML encoding type (for example, UTF-8).

Parameters

data Array of bytes to copy to the encode buffer

1.32.3.6 override void Copy (byte *data*)

This method is used to copy a single byte to the encode buffer. It first converts the byte to a hex character representation and then copies it to the output buffer.

Parameters

data The byte value to copy

1.32.3.7 virtual void DecrLevel () [virtual]

This method decrements the element nesting level counter.

1.32.3.8 virtual void EncodeBinStrValue (byte[] *bits*, int *nbits*) [virtual]

This method encodes XML binary string data

Parameters

bits Bit String to encode

nbits Number of bits to encode

1.32.3.9 virtual void EncodeByte (byte *data*) [virtual]

This method is used to encode a single byte to the encode buffer. It first converts the byte to a hex character representation and then copies it to the output buffer.

Parameters

data The byte value to copy

1.32.3.10 virtual void EncodeData (System.String *data*) [virtual]

This method encodes XML string data

Parameters

data String value to encode

1.32.3.11 virtual void EncodeEmptyElement (System.String *elemName*) [virtual]

This method encodes an XML empty element tag

Parameters

elemName The name of element.

Implements [Asn1XerEncoder](#).

1.32.3.12 virtual void EncodeEndDocument () [virtual]

This method encodes standard trailer information at the end of the XML document.

1.32.3.13 virtual void EncodeEndElement (System.String *elemName*) [virtual]

This method encodes an XML end element tag

Parameters

elemName The name of element.

Implements [Asn1XerEncoder](#).

1.32.3.14 virtual void EncodeHexStrValue (byte[] *data*) [virtual]

This method encodes XML hexadecimal string data

Parameters

data Data to encode

1.32.3.15 virtual void EncodeNamedValue (System.String *valueName*, System.String *elemName*) [virtual]

This method encodes an XML named value (with start and end tags)

Parameters

elemName The name of element.

valueName named value.

Implements [Asn1XerEncoder](#).

1.32.3.16 virtual void EncodeNamedValueElement (System.String *elemName*) [virtual]

This method encodes an XML named value element tag

Parameters

elemName The name of element.

Exceptions

Asn1Exception Thrown, if operation is failed.

1.32.3.17 virtual void EncodeObjectId (int[] *data*) [virtual]

This method encodes XML Object Identifiers and Relative OIDs data

Parameters

data Object's identifiers to encode

1.32.3.18 virtual void EncodeRealValue (double *data*, System.String *elemName*) [virtual]

This method encodes an XML REAL (double) value (with start and end tags).

Parameters

data The value to be encoded.

elemName The name of element. If null, then start and end tags won't be encoded.

Exceptions

Asn1Exception Thrown, if operation is failed.

Implements [Asn1XerEncoder](#).

1.32.3.19 virtual void EncodeStartDocument () [virtual]

This method encodes standard header information at the beginning of the XML document.

1.32.3.20 **virtual void EncodeStartElement (System.String *elemName*) [virtual]**

This method encodes an XML start element tag

Parameters

elemName The name of element.

Implements [Asn1XerEncoder](#).

1.32.3.21 **override System.IO.Stream GetInputStream ()**

This method returns an input stream object reference to the message buffer contents (i.e. the encoded data). If an output stream was selected as the output method, this method returns null.

Returns

Input stream object reference

1.32.3.22 **virtual void IncrLevel () [virtual]**

This method increments the element nesting level counter.

1.32.3.23 **virtual void Indent () [virtual]**

This methods indents by adding a new-line followed by whitespace corresponding to the current nesting level to the encode buffer.

1.32.3.24 **override void Reset ()**

This method resets the buffer to allow a new record to be encoded into it. Any previously encoded data is lost.

1.32.3.25 **override void Write (System.IO.Stream *outs*)**

This method writes the encoded record to the given output stream.

Parameters

outs Output stream to which record is to be written

1.32.4 **Property Documentation**

1.32.4.1 **virtual byte [] Buffer [get]**

Gets a reference of the byte buffer used to hold the encoded message.

Value: byte array containing encoded message

1.32.4.2 virtual bool Canonical [set]

Sets the canonical encoding rule.

Value: `true` if canonical encoding; otherwise `false`.

1.32.4.3 override byte [] MsgCopy [get]

Gets the copy of the byte buffer used to hold the encoded message.

Value: byte array containing encoded message

1.32.4.4 override int MsgLength [get]

Gets the length (in bytes) of the encoded message component.

Value: length of encoded message component

1.32.4.5 virtual int State [get, set]

Sets the state of the buffer.

Value: buffer stat

Implements [Asn1XerEncoder](#).

1.33 Asn1XerEncoder Interface Reference

Inherited by [Asn1XerEncodeBuffer](#), and [Asn1XerOutputStream](#).

Public Member Functions

- void [EncodeEmptyElement](#) (System.String elemName)
- void [EncodeEndElement](#) (System.String elemName)
- void [EncodeNamedValue](#) (System.String valueName, System.String elemName)
- void [EncodeRealValue](#) (double valueName, System.String elemName)
- void [EncodeStartElement](#) (System.String elemName)

Properties

- int [State](#) [get, set]

1.33.1 Detailed Description

This is a base interface for encoding of ASN.1 messages as specified in the XML Encoding Rules (XER) as specified in the ITU-T X.693 standard. It is implemented by both the [Asn1XerEncodeBuffer](#) and [Asn1XerOutputStream](#).

1.33.2 Member Function Documentation

1.33.2.1 void EncodeEmptyElement (System.String *elemName*)

This method encodes an XML empty element tag.

Throws C# Exception, If I/O error occurs.

Parameters

elemName The name of element.

Exceptions

Asn1Exception Thrown, if operation is failed.

Implemented in [Asn1XerEncodeBuffer](#), and [Asn1XerOutputStream](#).

1.33.2.2 void EncodeEndElement (System.String *elemName*)

This method encodes an XML start element and attribute tag. start tag will contain the attribute name and value

Throws C# Exception, If I/O error occurs.

Parameters

elemName The name of element.

Exceptions

Asn1Exception Thrown, if operation is failed.

Implemented in [Asn1XerEncodeBuffer](#), and [Asn1XerOutputStream](#).

1.33.2.3 void EncodeNamedValue (System.String valueName, System.String elemName)

This method encodes an XML named value (with start and end tags).

Throws C# Exception, If I/O error occurs.

Parameters

valueName The name of value.

elemName The name of element.

Exceptions

Asn1Exception Thrown, if operation is failed.

Implemented in [Asn1XerEncodeBuffer](#), and [Asn1XerOutputStream](#).

1.33.2.4 void EncodeRealValue (double valueName, System.String elemName)

This method encodes an XML REAL (double) value (with start and end tags).

Throws C# Exception, If I/O error occurs.

Parameters

valueName The name of value.

elemName The name of element. If null, then start and end tags won't be encoded.

Exceptions

Asn1Exception Thrown, if operation is failed.

Implemented in [Asn1XerEncodeBuffer](#), and [Asn1XerOutputStream](#).

1.33.2.5 void EncodeStartElement (System.String elemName)

This method encodes an XML start element tag.

Throws C# Exception, If I/O error occurs.

Parameters

elemName The name of element.

Exceptions

Asn1Exception Thrown, if operation is failed.

Implemented in [Asn1XerEncodeBuffer](#), and [Asn1XerOutputStream](#).

1.33.3 Property Documentation

1.33.3.1 int State [get, set]

This method gets and sets the state of the buffer.

Value: Buffer Stat

Implemented in [Asn1XerEncodeBuffer](#), and [Asn1XerOutputStream](#).

1.34 Asn1XerEncoder_Fields Struct Reference

Static Public Attributes

- static readonly int [XERDATA](#) = 2
- static readonly int [XEREND](#) = 3
- static readonly int [XERINDENT](#) = 3
- static readonly int [XERINIT](#) = 0
- static readonly int [XERSTART](#) = 1

1.34.1 Detailed Description

This class defines the constant variables for [Asn1XerEncoder](#).

1.34.2 Member Data Documentation

1.34.2.1 readonly int XERDATA = 2 [static]

XER characters (data) state

1.34.2.2 readonly int XEREND = 3 [static]

XER end element state

1.34.2.3 readonly int XERINDENT = 3 [static]

Number of indent spaces required to print XER element

1.34.2.4 readonly int XERINIT = 0 [static]

XER initialization state

1.34.2.5 readonly int XERSTART = 1 [static]

XER start element state

1.35 Asn1XerOpenType Class Reference

Classes

- class [SaxHandler](#)

Public Member Functions

- [Asn1XerOpenType](#) ([Asn1EncodeBuffer](#) buffer)
- [Asn1XerOpenType](#) (byte[] data, int offset, int nbytes)
- [Asn1XerOpenType](#) (byte[] data)
- [Asn1XerOpenType](#) ()
- override void [Decode](#) ([Asn1PerDecodeBuffer](#) buffer)
- override void [Decode](#) ([Asn1BerDecodeBuffer](#) buffer, bool explicitTagging, int implicitLength)
- override void [Encode](#) ([Asn1XerEncoder](#) buffer)
- override void [Encode](#) ([Asn1XerEncoder](#) buffer, System.String elemName)
- virtual void [Encode](#) ([Asn1XmlEncoder](#) buffer)
- override void [Encode](#) ([Asn1XmlEncoder](#) buffer, System.String elemName, System.String nsPrefix)
- override int [Encode](#) ([Asn1BerEncodeBuffer](#) buffer, bool explicitTagging)
- virtual [Asn1XerSaxHandler](#) [GetSaxHandler](#) (bool captureOuterElem)
- virtual [Asn1XerSaxHandler](#) [GetSaxHandler](#) ()
- override System.String [ToString](#) ()

Protected Attributes

- bool [named](#)

1.35.1 Detailed Description

This is a container class for holding the an ASN.1 open type value. This is a special version of the class that is only generated for the XER encoding rules. The data held in objects of this type should be UTF-8 encoded XML

1.35.2 Constructor & Destructor Documentation

1.35.2.1 [Asn1XerOpenType](#) ()

This constructor creates an empty type that can be used in a [Decode](#) method call to receive an encoded value.

1.35.2.2 [Asn1XerOpenType](#) (byte[] *data*)

This constructor initializes an open type from the given byte array. The array is assumed to contain a previously encoded message component.

Parameters

- data* Byte array containing a previously encoded message component.

1.35.2.3 **Asn1XerOpenType** (*byte[] data*, *int offset*, *int nbytes*)

This constructor initializes the open type from a portion of the given byte array. A new byte array is created starting at the given offset and consisting of the given number of bytes.

Parameters

data Byte array containing an octet string in binary form.

offset The byte offset in array at which to begin.

nbytes Number of bytes to copy from offset

1.35.2.4 **Asn1XerOpenType** (*Asn1EncodeBuffer buffer*)

This constructor initializes an open type using an encoded component. This can be used if a header (for example, a ROSE header) is being prepended to a pre-encoded component. The content of the given buffer should be XML encoded data.

Parameters

buffer Reference to encode buffer into which component type was encoded.

1.35.3 **Member Function Documentation**

1.35.3.1 **override void Decode** (*Asn1PerDecodeBuffer buffer*)

This operation is not allowed on this subclass.

1.35.3.2 **override void Decode** (*Asn1BerDecodeBuffer buffer*, *bool explicitTagging*, *int implicitLength*)

This operation converts BER-encoded data into a hexadecimal string and stores it in a <isBinary> element.

1.35.3.3 **override void Encode** (*Asn1XerEncoder buffer*)

This method encodes an ASN.1 open type value using the XML Encoding Rules (XER).

Parameters

buffer Encode message buffer object

1.35.3.4 **override void Encode** (*Asn1XerEncoder buffer*, *System.String elemName*)

This method encodes an ASN.1 open type value using the XML Encoding Rules (XER).

Parameters

buffer Encode message buffer object

elemName Element name

1.35.3.5 virtual void Encode (Asn1XmlEncoder *buffer*) [virtual]

This method encodes an ASN.1 open type value using the XML Encoding as specified in the XML schema standard(asn2xsd).

Parameters

buffer Encode message buffer object

1.35.3.6 override void Encode (Asn1XmlEncoder *buffer*, System.String *elemName*, System.String *nsPrefix*)

This operation is not allowed on this subclass.

This method encodes an ASN.1 open type value using the XML Encoding as specified in the XML schema standard(asn2xsd).

Parameters

buffer Encode message buffer object

elemName Element name

nsPrefix Element namespace value

1.35.3.7 override int Encode (Asn1BerEncodeBuffer *buffer*, bool *explicitTagging*)

Encoding [Asn1XerOpenType](#) data (which represents XML encoded data) into BER is not supported. If the content is binary (internally set during decode or encode), the data will be encoded as a regular Asn1OpenType.

Parameters

buffer Encode message buffer object

explicit Flag indicating element is explicitly tagged

Returns

Length of encoded component

1.35.3.8 virtual Asn1XerSaxHandler GetSaxHandler (bool *captureOuterElem*) [virtual]

This method returns the [Asn1XerOpenType.SaxHandler](#) class instance used for ASN.1 XER encoding.

Parameters

captureOuterElem Pass true if the outer element start and end tags (if present) should be captured. The outer element is the element for which startElement is called when the level is the start level. Note that this parameter is ignored if you have previously invoked one of the getSaxHandler methods on this object.

Returns

[Asn1XerOpenType.SaxHandler](#) object

1.35.3.9 virtual Asn1XerSaxHandler GetSaxHandler () [virtual]

This method returns the [Asn1XerOpenType.SaxHandler](#) class instance used for ASN.1 XER encoding. If this is the first invocation of any of the GetSaxHandler methods on this object, the returned handler will capture the outer element start/end tags. Otherwise, this will simply return the same SAX handler as previously returned.

Returns

[Asn1XerOpenType.SaxHandler](#) object

1.35.3.10 override System.String ToString ()

This method will return a string representation of the open type value. The format is the ASN.1 value format for this type..

Returns

Stringified representation of the value

1.35.4 Member Data Documentation

1.35.4.1 bool named [protected]

A flag that tells whether the element name has been printed or not.

This is used only when encoding a binary extension element, which may or may not have a name. If it does not, then we add the <isBinary> element name.

1.36 Asn1XerOutputStream Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1XerEncoder](#).

Public Member Functions

- [Asn1XerOutputStream](#) (System.IO.Stream os, bool canonical, int bufSize)
- [Asn1XerOutputStream](#) (System.IO.Stream os)
- virtual void [Copy](#) (System.String data)
- virtual void [Copy](#) (byte[] data, int off, int len)
- virtual void [Copy](#) (byte[] data)
- virtual void [Copy](#) (byte data)
- virtual void [DecrLevel](#) ()
- virtual void [EncodeBinStrValue](#) (byte[] bits, int nbits)
- virtual void [EncodeByte](#) (byte data)
- virtual void [EncodeData](#) (System.String data)
- virtual void [EncodeEmptyElement](#) (System.String elemName)
- virtual void [EncodeEndDocument](#) ()
- virtual void [EncodeEndElement](#) (System.String elemName)
- virtual void [EncodeHexStrValue](#) (byte[] data)
- virtual void [EncodeNamedValue](#) (System.String valueName, System.String elemName)
- virtual void [EncodeNamedValueElement](#) (System.String elemName)
- virtual void [EncodeObjectId](#) (int[] data)
- virtual void [EncodeRealValue](#) (double data, System.String elemName)
- virtual void [EncodeStartDocument](#) ()
- virtual void [EncodeStartElement](#) (System.String elemName)
- virtual void [IncrLevel](#) ()
- virtual void [Indent](#) ()
- virtual void [Write](#) (System.String data)

Properties

- virtual bool [Canonical](#) [set]
- virtual int [State](#) [get, set]

1.36.1 Detailed Description

This class implements the output stream to encode ASN.1 messages as specified in the XML Encoding Rules (XER) as specified in the ITU-T X.693 standard. A reference to an object of this type is passed to each of the ASN.1 type encode methods involved in encoding a particular message type.

1.36.2 Constructor & Destructor Documentation

1.36.2.1 Asn1XerOutputStream (System.IO.Stream os)

This constructor creates a buffered XER output stream object with default size of buffer. Whenever the buffer becomes full, the buffer will be flushed to the stream.

Parameters

- os* The underlying System.IO.Stream object.

1.36.2.2 Asn1XerOutputStream (System.IO.Stream *os*, bool *canonical*, int *bufSize*)

This constructor creates a buffered XER output stream object. Whenever the buffer becomes full, the buffer will be flushed to the stream.

Parameters

os The underlying System.IO.Stream object.

canonical Boolean indicating a canonical or non-canonical encoding should be produced as defined in the X.693 standard.

bufSize The buffer size. If it is 0 then the output stream is used as unbuffered.

1.36.3 Member Function Documentation

1.36.3.1 virtual void Copy (System.String *data*) [virtual]

This method copies a character string to the output stream.

Throws, exception thrown by the underlying System.IO.Stream.

Parameters

data The string value to copy

Exceptions

Asn1Exception Thrown, if operation is failed.

1.36.3.2 virtual void Copy (byte[] *data*, int *off*, int *len*) [virtual]

This method copies multiple bytes to the output stream. It is assumed the byte are already formatted into a valid XML encoding type (for example, UTF-8).

Throws, exception thrown by the underlying System.IO.Stream.

Parameters

data Array of bytes to copy to the output stream

off The offset in array at which to begin copy.

len The Number of bytes to copy

Exceptions

Asn1Exception Thrown, if operation is failed.

1.36.3.3 virtual void Copy (byte[] *data*) [virtual]

This method copies multiple bytes to the output stream. It is assumed the byte are already formatted into a valid XML encoding type (for example, UTF-8).

Throws, exception thrown by the underlying System.IO.Stream.

Parameters

data Array of bytes to copy to the output stream

Exceptions

Asn1Exception Thrown, if operation is failed.

1.36.3.4 virtual void Copy (byte *data*) [virtual]

This method is used to copy a single byte to the output stream. It first converts the byte to a hex character representation and then copies it to the output buffer.

Throws, exception thrown by the underlying System.IO.Stream.

Parameters

data The byte value to copy

1.36.3.5 virtual void DecrLevel () [virtual]

This method decrements the element nesting level counter.

1.36.3.6 virtual void EncodeBinStrValue (byte[] *bits*, int *nbits*) [virtual]

This method encodes XML binary string data

Throws, exception thrown by the underlying System.IO.Stream.

Parameters

bits Bit String to encode

nbits Number of bits to encode

Exceptions

Asn1Exception Thrown, if operation is failed.

1.36.3.7 virtual void EncodeByte (byte *data*) [virtual]

This method is used to encode a single byte to the output stream. It first converts the byte to a hex character representation and then copies it to the output buffer.

Throws, exception thrown by the underlying System.IO.Stream.

Parameters

data The byte value to copy

1.36.3.8 virtual void EncodeData (System.String data) [virtual]

This method encodes XML string data

Throws, exception thrown by the underlying System.IO.Stream.

Parameters

data String value to encode

Exceptions

Asn1Exception Thrown, if operation is failed.

1.36.3.9 virtual void EncodeEmptyElement (System.String elemName) [virtual]

This method encodes an XML empty element tag.

Throws, exception thrown by the underlying System.IO.Stream.

Parameters

elemName The name of element.

Exceptions

Asn1Exception Thrown, if operation is failed.

Implements [Asn1XerEncoder](#).

1.36.3.10 virtual void EncodeEndDocument () [virtual]

This method encodes standard trailer information at the end of the XML document.

Throws, exception thrown by the underlying System.IO.Stream.

Exceptions

Asn1Exception Thrown, if operation is failed.

1.36.3.11 virtual void EncodeEndElement (System.String elemName) [virtual]

This method encodes an XML end element tag.

Throws, exception thrown by the underlying System.IO.Stream.

Parameters

elemName The name of element.

Exceptions

Asn1Exception Thrown, if operation is failed.

Implements [Asn1XerEncoder](#).

1.36.3.12 virtual void EncodeHexStrValue (byte[] data) [virtual]

This method encodes XML hexadecimal string data

Throws, exception thrown by the underlying System.IO.Stream.

Parameters

data Data to encode

Exceptions

Asn1Exception Thrown, if operation is failed.

1.36.3.13 virtual void EncodeNamedValue (System.String valueName, System.String elemName) [virtual]

This method encodes an XML named value (with start and end tags).

Throws, exception thrown by the underlying System.IO.Stream.

Parameters

valueName The named value.

elemName The name of element.

Exceptions

Asn1Exception Thrown, if operation is failed.

Implements [Asn1XerEncoder](#).

1.36.3.14 virtual void EncodeNamedValueElement (System.String elemName) [virtual]

This method encodes an XML named value element tag.

Throws, exception thrown by the underlying System.IO.Stream.

Parameters

elemName The name of element.

Exceptions

Asn1Exception Thrown, if operation is failed.

1.36.3.15 virtual void EncodeObjectId (int[] data) [virtual]

This method encodes XML Object Identifiers and Relative OIDs data

Throws, exception thrown by the underlying System.IO.Stream.

Parameters

data Object's identifiers to encode

Exceptions

Asn1Exception Thrown, if operation is failed.

1.36.3.16 virtual void EncodeRealValue (double *data*, System.String *elemName*) [virtual]

This method encodes an XML REAL (double) value (with start and end tags).

Throws, exception thrown by the underlying System.IO.Stream.

Parameters

data The value to be encoded.

elemName The name of element. If null, then start and end tags won't be encoded.

Exceptions

Asn1Exception Thrown, if operation is failed.

Implements [Asn1XerEncoder](#).

1.36.3.17 virtual void EncodeStartDocument () [virtual]

This method encodes standard header information at the beginning of the XML document.

Throws, exception thrown by the underlying System.IO.Stream.

Exceptions

Asn1Exception Thrown, if operation is failed.

1.36.3.18 virtual void EncodeStartElement (System.String *elemName*) [virtual]

This method encodes an XML start element tag.

Throws, exception thrown by the underlying System.IO.Stream.

Parameters

elemName The name of element.

Exceptions

Asn1Exception Thrown, if operation is failed.

Implements [Asn1XerEncoder](#).

1.36.3.19 virtual void IncrLevel () [virtual]

This method increments the element nesting level counter.

1.36.3.20 virtual void Indent () [virtual]

This methods indents by adding a new-line followed by whitespace corresponding to the current nesting level to the output stream.

Throws, exception thrown by the underlying System.IO.Stream.

Exceptions

Asn1Exception Thrown, if operation is failed.

1.36.3.21 virtual void Write (System.String *data*) [virtual]

This method copies a character string to the output stream.

Throws, exception thrown by the underlying System.IO.Stream.

Parameters

data The string value to copy

Exceptions

Asn1Exception Thrown, if operation is failed.

1.36.4 Property Documentation

1.36.4.1 virtual bool Canonical [set]

Sets the canonical encoding rule.

Value: `true` if canonical encoding; otherwise `false`.

1.36.4.2 virtual int State [get, set]

Sets the state of the buffer.

Value: buffer stat

Implements [Asn1XerEncoder](#).

1.37 Asn1XerSaxHandler Class Reference

Inherits [Com::Objsys::Asn1::Runtime::XmlSaxDefaultHandler](#).

Inherited by [SaxHandler](#).

Public Member Functions

- override void [Error](#) (System.Xml.XmlException exception)
- override void [FatalError](#) (System.Xml.XmlException exception)
- virtual void [Init](#) (int startLevel)
- override void [Warning](#) (System.Xml.XmlException exception)

Protected Member Functions

- internal [Asn1XerSaxHandler](#) ()

Protected Attributes

- internal int [mCurrElemID](#)
- internal int [mCurrState](#)
- internal int [mLevel](#)
- internal readonly int [XERDATA](#) = 2
- internal readonly int [XEREND](#) = 3
- internal readonly int [XERINIT](#) = 0
- internal readonly int [XERSTART](#) = 1
- internal readonly int [XERUNKNOWN](#) = - 1

Properties

- virtual bool [Complete](#) [get]
- virtual int [State](#) [get]

1.37.1 Detailed Description

This class extends the DefaultHandler SAX handler class to add items specific to ASN.1 XER encoding.

1.37.2 Constructor & Destructor Documentation

1.37.2.1 internal Asn1XerSaxHandler () [protected]

The default constructor creates an XER SAX parser instance.

1.37.3 Member Function Documentation

1.37.3.1 override void Error (System.Xml.XmlException *exception*) [virtual]

This method manage when an error exception occurs in the parsing process

Parameters

exception The exception throws by the parser

Exceptions

System.Xml.XmlException The error exception

Reimplemented from [XmlSaxDefaultHandler](#).

1.37.3.2 override void FatalError (System.Xml.XmlException *exception*) [virtual]

This method throws a fatal error exception.

Parameters

exception The exception thrown by the parser

Exceptions

System.Xml.XmlException The error exception

Reimplemented from [XmlSaxDefaultHandler](#).

1.37.3.3 virtual void Init (int *startLevel*) [virtual]

This method initializes the class member variables.

Parameters

startLevel The XER level to begin

1.37.3.4 override void Warning (System.Xml.XmlException *exception*) [virtual]

This method manage when a warning exception occurs in the parsing process

Parameters

exception The exception Throws by the parser

Exceptions

System.Xml.XmlException The warning exception

Reimplemented from [XmlSaxDefaultHandler](#).

1.37.4 Member Data Documentation

1.37.4.1 internal int mCurrElemID [protected]

Variable holds the current element ID

1.37.4.2 internal int mCurrState [protected]

Variable holds the current XER processing state

1.37.4.3 internal int mLevel [protected]

Variable holds the start and current level

1.37.4.4 internal readonly int XERDATA = 2 [protected]

XER characters (data) state

1.37.4.5 internal readonly int XEREND = 3 [protected]

XER end element state

1.37.4.6 internal readonly int XERINIT = 0 [protected]

XER initialization state

1.37.4.7 internal readonly int XERSTART = 1 [protected]

XER start element state

1.37.4.8 internal readonly int XERUNKNOWN = - 1 [protected]

XER unknown state

1.37.5 Property Documentation

1.37.5.1 virtual bool Complete [get]

Gets the status of the current element parsing process is complete.

Value: true if found; otherwise false

1.37.5.2 virtual int State [get]

Gets the current state of the event handler.

Value: current state

1.38 Asn1XerUtil Class Reference

Static Public Member Functions

- static void [EncodeReal](#) ([Asn1XerEncoder](#) buffer, double value, System.String elemName)
- static System.String [NormalizedRealValueToString](#) (double value, bool isXer)

1.38.1 Detailed Description

This class contains some general purpose static utility functions for XER encoding or decoding.

1.38.2 Member Function Documentation

1.38.2.1 static void EncodeReal (Asn1XerEncoder *buffer*, double *value*, System.String *elemName*) [static]

This method encodes an ASN.1 real value using the XML encoding rules (XER).

Parameters

- buffer* Encode message buffer object
value Value to be encoded.
elemName Element name

1.38.2.2 static System.String NormalizedRealValueToString (double *value*, bool *isXer*) [static]

This method will return a string representation of the normalized REAL value. The output format is value format [+|-]X.XXXXXE[-]XXX as defined in X.693.

Parameters

- value* value to be normalized and stringified.
isXer true, if this value is being encoded for XER.

Returns

Stringified representation of the value

1.39 Asn1XmlEncodeBuffer Class Reference

Public Member Functions

- [Asn1XmlEncodeBuffer](#) (int sizeIncrement)
- [Asn1XmlEncodeBuffer](#) ()
- override void [BinDump](#) (System.IO.StreamWriter outs, System.String varName)
- virtual void [Copy](#) (System.String data)
- virtual void [Copy](#) (byte[] data, int off, int len)
- override void [Copy](#) (byte[] data)
- override void [Copy](#) (byte data)
- virtual void [DecrLevel](#) ()
- virtual void [EncodeAttr](#) (System.String qname, System.String data)
- virtual void [EncodeBinStrValue](#) (byte[] bits, int nbits)
- virtual void [EncodeByte](#) (byte data)
- virtual void [EncodeData](#) (System.String data)
- virtual void [EncodeDoubleValue](#) (double data, System.String elemName, System.String nsPrefix)
- virtual void [EncodeEmptyElement](#) (System.String elemName, System.String nsPrefix, bool terminate)
- virtual void [EncodeEndDocument](#) ()
- virtual void [EncodeEndElement](#) (System.String elemName, System.String nsPrefix, bool indent)
- virtual void [EncodeEndElement](#) (System.String elemName, System.String nsPrefix)
- virtual void [EncodeHexStrValue](#) (byte[] data)
- virtual void [EncodeNamedValue](#) (System.String valueName, System.String elemName, System.String nsPrefix)
- virtual void [EncodeNamedValueElement](#) (System.String valueName)
- virtual void [EncodeObjectId](#) (int[] data)
- virtual void [EncodeStartDocument](#) ()
- virtual void [EncodeStartElement](#) (System.String elemName, System.String nsPrefix, bool terminate)
- virtual void [EncodeXSIAttrs](#) ()
- override System.IO.Stream [GetInputStream](#) ()
- virtual void [IncrLevel](#) ()
- virtual void [Indent](#) ()
- override void [Reset](#) ()
- virtual void [SetXSIAttrs](#) (Asn1XmlXSIAttrs data)
- override void [Write](#) (System.IO.Stream outs)

Protected Member Functions

- internal override void [CheckSize](#) (int bytesRequired)

Properties

- virtual byte[] [Buffer](#) [get]
- Asn1XmlEncodeHelper [Helper](#) [get]
- override byte[] [MsgCopy](#) [get]
- override int [MsgLength](#) [get]
- virtual int [State](#) [get, set]

1.39.1 Detailed Description

This class handles the encoding of ASN.1 messages as specified in the XML Encoding (non-XER) by the XML schema standard (generated by asn2xsd).

1.39.2 Constructor & Destructor Documentation

1.39.2.1 Asn1XmlEncodeBuffer ()

The default constructor creates an XML encode buffer object with the default size increment and canonical set to false.

1.39.2.2 Asn1XmlEncodeBuffer (int *sizeIncrement*)

The parameterized constructor creates an XML encode buffer object with size increment and canonical set to the given values.

Parameters

canonical Boolean indicating a canonical or non-canonical encoding should be produced as defined in the X.693 standard.

sizeIncrement The initial size in bytes of an encode buffer. If the buffer becomes full, it will be expanded by this amount. If this parameter is set to zero, the default increment will be used.

1.39.3 Member Function Documentation

1.39.3.1 override void BinDump (System.IO.StreamWriter *outs*, System.String *varName*)

This method dumps the encoded message in a human-readable format showing a bit trace of all fields to the given print output stream.

Parameters

outs Output will be written to this stream

varName Name of the Decoded ASN1 Type

1.39.3.2 internal override void CheckSize (int *bytesRequired*) [protected]

This method determines if the encode buffer can hold the requested number of bytes. If not, the buffer is expanded.

Parameters

bytesRequired Number of required bytes.

1.39.3.3 virtual void Copy (System.String *data*) [virtual]

This method copies a character string to the encode buffer.

Parameters

data The string value to copy

1.39.3.4 virtual void Copy (byte[] data, int off, int len) [virtual]

This method copies multiple bytes to the encode buffer. It is assumed the byte are already formatted into a valid XML encoding type (for example, UTF-8).

Parameters

data Array of bytes to copy to the encode buffer

off The offset in array at which to begin copy.

len The number of bytes to copy

1.39.3.5 override void Copy (byte[] data)

This method copies multiple bytes to the encode buffer. It is assumed the byte are already formatted into a valid XML encoding type (for example, UTF-8).

Parameters

data Array of bytes to copy to the encode buffer

1.39.3.6 override void Copy (byte data)

This method is used to copy a single byte to the encode buffer. It first converts the byte to a hex character representation and then copies it to the output buffer.

Parameters

data The byte value to copy

1.39.3.7 virtual void DecrLevel () [virtual]

This method decrements the element nesting level counter.

1.39.3.8 virtual void EncodeAttr (System.String qname, System.String data) [virtual]

This method encodes an XML attribute value.

Parameters

qname Attribute qualified name.

value Attribute value in string form.

1.39.3.9 virtual void EncodeBinStrValue (byte[] bits, int nbits) [virtual]

This method encodes XML binary string data

Parameters

bits Bit string to encode

<throws> IOException Any exception thrown by the underlying OutputStream. </throws> <throws> Asn1Exception Thrown, if operation is failed. </throws>

1.39.3.10 virtual void EncodeByte (byte *data*) [virtual]

This method is used to encode a single byte to the encode buffer. It first converts the byte to a hex character representation and then copies it to the output buffer.

Parameters

data The byte value to copy

1.39.3.11 virtual void EncodeData (System.String *data*) [virtual]

This method encodes XML string data

Parameters

value String value to encode

<throws> IOException Any exception thrown by the underlying OutputStream. </throws> <throws> Asn1Exception Thrown, if operation is failed. </throws>

1.39.3.12 virtual void EncodeDoubleValue (double *data*, System.String *elemName*, System.String *nsPrefix*) [virtual]

This method encodes an XML REAL (double) value (with start and end tags).

Parameters

data The value to be encoded.

elemName The name of element. If null, then start and end tags won't be encoded.

Exceptions

Asn1Exception Thrown, if operation is failed.

1.39.3.13 virtual void EncodeEmptyElement (System.String *elemName*, System.String *nsPrefix*, bool *terminate*) [virtual]

This method encodes an XML empty element tag

Parameters

elemName The name of element.

nsPrefix The namespace prefix of element.

<throws> Asn1Exception Thrown, if operation is failed. </throws>

1.39.3.14 virtual void EncodeEndDocument () [virtual]

This method encodes standard trailer information at the end of the XML document.

1.39.3.15 virtual void EncodeEndElement (System.String *elemName*, System.String *nsPrefix*, bool *indent*) [virtual]

This method encodes an XML end element tag without indenting

Parameters

elemName The name of element.

<throws> Asn1Exception Thrown, if operation is failed. </throws>

1.39.3.16 virtual void EncodeEndElement (System.String *elemName*, System.String *nsPrefix*) [virtual]

This method encodes an XML end element tag

Parameters

elemName The name of element, as String.

1.39.3.17 virtual void EncodeHexStrValue (byte[] *data*) [virtual]

This method encodes XML hexadecimal string data

Parameters

data Data to encode

<throws> IOException Any exception thrown by the underlying OutputStream. </throws> <throws> Asn1Exception Thrown, if operation is failed. </throws>

1.39.3.18 virtual void EncodeNamedValue (System.String *valueName*, System.String *elemName*, System.String *nsPrefix*) [virtual]

This method encodes an XML named value (with start and end tags)

1.39.3.19 virtual void EncodeNamedValueElement (System.String *valueName*) [virtual]

This method encodes an XML named value element tag

Parameters

valueName The named value, as String.

Exceptions

Asn1Exception Thrown, if operation is failed.

1.39.3.20 **virtual void EncodeObjectId (int[] *data*) [virtual]**

This method encodes XML Object Identifiers and Relative OIDs data

Parameters

data Object's identifiers to encode

<throws> IOException Any exception thrown by the underlying OutputStream. </throws> <throws> Asn1Exception Thrown, if operation is failed. </throws>

1.39.3.21 **virtual void EncodeStartDocument () [virtual]**

This method encodes standard header information at the beginning of the XML document.

1.39.3.22 **virtual void EncodeStartElement (System.String *elemName*, System.String *nsPrefix*, bool *terminate*) [virtual]**

This method encodes an XML start element tag.

Parameters

elemName The name of element.

nsPrefix The namespace prefix of element.

<throws> Asn1Exception Thrown, if operation is failed. </throws>

1.39.3.23 **virtual void EncodeXSAttrs () [virtual]**

This method encodes XSI attributes.

1.39.3.24 **override System.IO.Stream GetInputStream ()**

This method returns an input stream object reference to the message buffer contents (i.e. the encoded data). If an output stream was selected as the output method, this method returns null.

Returns

Input stream object reference

1.39.3.25 **virtual void IncrLevel () [virtual]**

This method increments the element nesting level counter.

1.39.3.26 **virtual void Indent () [virtual]**

This methods indents by adding a new-line followed by whitespace corresponding to the current nesting level to the encode buffer.

1.39.3.27 **override void Reset ()**

This method resets the buffer to allow a new record to be encoded into it. Any previously encoded data is lost.

1.39.3.28 **virtual void SetXSIAttrs (Asn1XmlXSIAttrs data) [virtual]**

This method sets the XSI attributes object to the given value.

Parameters

value XSI attributes object

1.39.3.29 **override void Write (System.IO.Stream outs)**

This method writes the encoded record to the given output stream.

Parameters

outs Output stream to which record is to be written

1.39.4 **Property Documentation**

1.39.4.1 **virtual byte [] Buffer [get]**

Gets a reference of the byte buffer used to hold the encoded message.

Value: byte array containing encoded message

1.39.4.2 **Asn1XmlEncodeHelper Helper [get]**

Gets the encoding helper object.

1.39.4.3 **override byte [] MsgCopy [get]**

Gets the copy of the byte buffer used to hold the encoded message.

Value: byte array containing encoded message

1.39.4.4 **override int MsgLength [get]**

Gets the length (in bytes) of the encoded message component.

Value: length of encoded message component

1.39.4.5 **virtual int State [get, set]**

Sets the state of the buffer.

Value: buffer stat

1.40 Asn1XmlOutputStream Class Reference

Public Member Functions

- [Asn1XmlOutputStream](#) (System.IO.Stream os, bool canonical, int bufSize)
- [Asn1XmlOutputStream](#) (System.IO.Stream os, int bufSize)
- [Asn1XmlOutputStream](#) (System.IO.Stream os)
- virtual void [Copy](#) (System.String data)
- virtual void [Copy](#) (byte[] data, int off, int len)
- virtual void [Copy](#) (byte[] data)
- virtual void [Copy](#) (byte data)
- virtual void [DecrLevel](#) ()
- virtual void [EncodeAttr](#) (System.String qname, System.String data)
- virtual void [EncodeBinStrValue](#) (byte[] bits, int nbits)
- virtual void [EncodeByte](#) (byte data)
- virtual void [EncodeData](#) (System.String data)
- virtual void [EncodeDoubleValue](#) (double data, System.String elemName, System.String nsPrefix)
- virtual void [EncodeEmptyElement](#) (System.String elemName, System.String nsPrefix, bool terminate)
- virtual void [EncodeEndDocument](#) ()
- virtual void [EncodeEndElement](#) (System.String elemName, System.String nsPrefix, bool indent)
- virtual void [EncodeEndElement](#) (System.String elemName, System.String nsPrefix)
- virtual void [EncodeHexStrValue](#) (byte[] data)
- virtual void [EncodeNamedValue](#) (System.String valueName, System.String elemName, System.String nsPrefix)
- virtual void [EncodeNamedValueElement](#) (System.String valueName)
- virtual void [EncodeObjectId](#) (int[] data)
- virtual void [EncodeStartDocument](#) ()
- virtual void [EncodeStartElement](#) (System.String elemName, System.String nsPrefix, bool terminate)
- virtual void [EncodeXSIAttrs](#) ()
- virtual void [IncrLevel](#) ()
- virtual void [Indent](#) ()
- virtual void [SetXSIAttrs](#) (Asn1XmlXSIAttrs data)
- virtual void [Write](#) (System.String data)

Properties

- virtual Asn1XmlEncodeHelper [Helper](#) [get]
- virtual int [State](#) [get, set]

1.40.1 Detailed Description

This class implements the output stream to encode ASN.1 messages as specified in the XML Encoding by the XML schema standard (generated by asn2xsd). A reference to an object of this type is passed to each of the ASN.1 type encode methods involved in encoding a particular message type.

1.40.2 Constructor & Destructor Documentation

1.40.2.1 Asn1XmlOutputStream (System.IO.Stream *os*)

This constructor creates a buffered XML output stream object with default size of buffer. Whenever the buffer becomes full, the buffer will be flushed to the stream.

Parameters

os The underlying System.IO.Stream object.

1.40.2.2 Asn1XmlOutputStream (System.IO.Stream *os*, int *bufSize*)

This constructor creates a buffered XML output stream object. Whenever the buffer becomes full, the buffer will be flushed to the stream.

Parameters

os The underlying System.IO.Stream object.

bufSize The buffer size. If it is 0 then the output stream is used as unbuffered.

1.40.2.3 Asn1XmlOutputStream (System.IO.Stream *os*, bool *canonical*, int *bufSize*)

This constructor creates a buffered XML output stream object. Whenever the buffer becomes full, the buffer will be flushed to the stream.

Parameters

os The underlying System.IO.Stream object.

canonical Boolean indicating a canonical or non-canonical encoding should be produced as defined in the X.693 standard.

bufSize The buffer size. If it is 0 then the output stream is used as unbuffered.

1.40.3 Member Function Documentation

1.40.3.1 virtual void Copy (System.String *data*) [virtual]

This method copies a character string to the output stream.

Parameters

value The string value to copy

<throws> IOException Any exception thrown by the underlying OutputStream. </throws> <throws> Asn1Exception Thrown, if operation is failed. </throws>

1.40.3.2 virtual void Copy (byte[] *data*, int *off*, int *len*) [virtual]

This method copies multiple bytes to the output stream. It is assumed the byte are already formatted into a valid XML encoding type (for example, UTF-8).

Parameters

value Array of bytes to copy to the output stream

off Starting offset in array

len The length to be encoded

<throws> IOException Any exception thrown by the underlying OutputStream. </throws> <throws> Asn1Exception Thrown, if operation is failed. </throws>

1.40.3.3 virtual void Copy (byte[] data) [virtual]

This method copies multiple bytes to the output stream. It is assumed the byte are already formatted into a valid XML encoding type (for example, UTF-8).

Parameters

value Array of bytes to copy to the output stream

<throws> IOException Any exception thrown by the underlying OutputStream. </throws> <throws> Asn1Exception Thrown, if operation is failed. </throws>

1.40.3.4 virtual void Copy (byte data) [virtual]

This method is used to copy a single byte to the output stream. It first converts the byte to a hex character representation and then copies it to the output buffer.

Parameters

value The byte value to copy

<throws> IOException Any exception thrown by the underlying OutputStream. </throws>

1.40.3.5 virtual void DecrLevel () [virtual]

This method decrements the element nesting level counter.

1.40.3.6 virtual void EncodeAttr (System.String qname, System.String data) [virtual]

This method encodes an XML attribute value.

Parameters

qname Attribute qualified name.

value Attribute value in string form.

1.40.3.7 virtual void EncodeBinStrValue (byte[] bits, int nbits) [virtual]

This method encodes XML binary string data

Parameters

bits Bit string to encode

<throws> IOException Any exception thrown by the underlying OutputStream. </throws> <throws> Asn1Exception Thrown, if operation is failed. </throws>

1.40.3.8 virtual void EncodeByte (byte *data*) [virtual]

This method is used to encode a single byte to the output stream. It first converts the byte to a hex character representation and then copies it to the output buffer.

Parameters

value The byte value to copy

<throws> IOException Any exception thrown by the underlying OutputStream. </throws>

1.40.3.9 virtual void EncodeData (System.String *data*) [virtual]

This method encodes XML string data

Parameters

value String value to encode

<throws> IOException Any exception thrown by the underlying OutputStream. </throws> <throws> Asn1Exception Thrown, if operation is failed. </throws>

1.40.3.10 virtual void EncodeDoubleValue (double *data*, System.String *elemName*, System.String *nsPrefix*) [virtual]

This method encodes an XML REAL (double) value (with start and end tags).

Parameters

data The value to be encoded.

elemName The name of element. If null, then start and end tags won't be encoded.

Exceptions

Asn1Exception Thrown, if operation is failed.

1.40.3.11 virtual void EncodeEmptyElement (System.String *elemName*, System.String *nsPrefix*, bool *terminate*) [virtual]

This method encodes an XML empty element tag

Parameters

elemName The name of element.

nsPrefix The namespace prefix of element.

<throws> Asn1Exception Thrown, if operation is failed. </throws>

1.40.3.12 virtual void EncodeEndDocument () [virtual]

This method encodes standard trailer information at the end of the XML document.

1.40.3.13 virtual void EncodeEndElement (System.String *elemName*, System.String *nsPrefix*, bool *indent*) [virtual]

This method encodes an XML end element tag without indenting

Parameters

elemName The name of element.

<throws> Asn1Exception Thrown, if operation is failed. </throws>

1.40.3.14 virtual void EncodeEndElement (System.String *elemName*, System.String *nsPrefix*) [virtual]

This method encodes an XML end element tag

Parameters

elemName The name of element, as String.

1.40.3.15 virtual void EncodeHexStrValue (byte[] *data*) [virtual]

This method encodes XML hexadecimal string data

Parameters

data Data to encode

<throws> IOException Any exception thrown by the underlying OutputStream. </throws> <throws> Asn1Exception Thrown, if operation is failed. </throws>

1.40.3.16 virtual void EncodeNamedValue (System.String *valueName*, System.String *elemName*, System.String *nsPrefix*) [virtual]

This method encodes an XML named value (with start and end tags)

Parameters

valueName The name of value.

elemName The name of element.

<throws> IOException If I/O error occurs. </throws> <throws> Asn1Exception Thrown, if operation is failed. </throws>

1.40.3.17 virtual void EncodeNamedValueElement (System.String *valueName*) [virtual]

This method encodes an XML named value element tag

Parameters

valueName The named value, as String.

Exceptions

Asn1Exception Thrown, if operation is failed.

1.40.3.18 virtual void EncodeObjectId (int[] *data*) [virtual]

This method encodes XML Object Identifiers and Relative OIDs data

Parameters

data Object's identifiers to encode

<throws> IOException Any exception thrown by the underlying OutputStream. </throws> <throws> Asn1Exception Thrown, if operation is failed. </throws>

1.40.3.19 virtual void EncodeStartDocument () [virtual]

This method encodes standard header information at the beginning of the XML document.

1.40.3.20 virtual void EncodeStartElement (System.String *elemName*, System.String *nsPrefix*, bool *terminate*) [virtual]

This method encodes an XML start element tag.

Parameters

elemName The name of element.

nsPrefix The namespace prefix of element.

<throws> Asn1Exception Thrown, if operation is failed. </throws>

1.40.3.21 virtual void EncodeXSIAttrs () [virtual]

This method encodes XSI attributes.

1.40.3.22 virtual void IncrLevel () [virtual]

This method increments the element nesting level counter.

1.40.3.23 virtual void Indent () [virtual]

This methods indents by adding a new-line followed by whitespace corresponding to the current nesting level to the output stream.

<throws> IOException Any exception thrown by the underlying OutputStream. </throws> <throws> Asn1Exception Thrown, if operation is failed. </throws>

1.40.3.24 virtual void SetXSIAttrs (Asn1XmlXSIAttrs data) [virtual]

This method sets the XSI attributes object to the given value.

Parameters

value XSI attributes object

1.40.3.25 virtual void Write (System.String data) [virtual]

This method copies a character string to the output stream.

Parameters

value The string value to copy

<throws> IOException Any exception thrown by the underlying OutputStream. </throws> <throws> Asn1Exception Thrown, if operation is failed. </throws>

1.40.4 Property Documentation

1.40.4.1 virtual Asn1XmlEncodeHelper Helper [get]

Gets the encoding helper object.

Value: The helper object.

1.40.4.2 virtual int State [get, set]

Sets the state of the buffer.

Value: buffer stat

1.41 Asn1XmlUtil Class Reference

Static Public Member Functions

- static void [EncodeDouble](#) (Asn1XmlEncoder buffer, double data)
- static void [EncodeDouble](#) (Asn1XmlEncoder buffer, double data, System.String elemName, System.String nsPrefix)
- static void [EncodeNSAttrs](#) (Asn1XmlEncoder buffer, Asn1XmlNamespace[] nsArray)
- static double [GetMinusZero](#) ()
- static System.String [GetXMLString](#) (System.String data)
- static bool [IsMinusZero](#) (double value)
- static void [KeepNullsInString](#) (bool keep)
- static String[] [TokenizeXsdList](#) (String listValue)

1.41.1 Detailed Description

This class contains some general purpose static utility functions for XML encoding or decoding.

1.41.2 Member Function Documentation

1.41.2.1 static void EncodeDouble (Asn1XmlEncoder *buffer*, double *data*) [static]

This method encodes an ASN.1 real value using the XML encoding (non-XER).

Parameters

- buffer* Encode message buffer object
- value* Value to be encoded.

1.41.2.2 static void EncodeDouble (Asn1XmlEncoder *buffer*, double *data*, System.String *elemName*, System.String *nsPrefix*) [static]

This method encodes an ASN.1 real value using the XML encoding (non-XER).

Parameters

- buffer* Encode message buffer object
- value* Value to be encoded.
- elemName* Element name
- nsPrefix* Element namespace prefix value

1.41.2.3 static void EncodeNSAttrs (Asn1XmlEncoder *buffer*, Asn1XmlNamespace[] *nsArray*) [static]

This method encodes XML namespace attributes in the form 'xmlns[:prefix]="uri"'.

Parameters

- nsArray* Array of XML namespace prefix/URI mappings.

1.41.2.4 static double GetMinusZero () [static]

This method returns double value for "minus zero" (-0) special XML value.

Returns

double value for "-0".

1.41.2.5 static System.String GetXMLString (System.String data) [static]

This method will convert the given string value into XML character content by escaping special characters in the sting such as ampersand (&), left angle bracket (>), etc.

Parameters

data String to convert

Returns

Converted string value

1.41.2.6 static bool IsMinusZero (double value) [static]

This method will return true, if value is "minus zero" (-0) special XML value.

Parameters

value value to test

Returns

true, if this value is "-0".

1.41.2.7 static void KeepNullsInString (bool keep) [static]

This method allows users to toggle the output of a null entity code in XML strings. Null bytes are not permitted in any XML document, but are permissible in ASN.1 strings. When converting, users may elect to retain null bytes as entities (&x0;) by passing

true

to this function. By default, null bytes are dropped.

Parameters

keep Boolean switch to keep or ignore null bytes.

1.41.2.8 `static String [] TokenizeXsdList (String listValue) [static]`

Return an array of strings representing the (lexical) values of an `xsd:list`

Parameters

listValue the lexical value of the `xsd:list`. It need not have whitespace collapse applied yet.

Returns

array of lexical values, one per value in the `listValue`. No empty strings will appear in the array.

1.42 SaxHandler Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1XerSaxHandler](#).

Public Member Functions

- override void [Characters](#) (System.Char[] *ch*, int *start*, int *length*)
- override void [EndElement](#) (System.String *namespaceURI*, System.String *localName*, System.String *qName*)
- override void [StartElement](#) (System.String *namespaceURI*, System.String *localName*, System.String *qName*, [XmlAttributes](#) *atts*)

1.42.1 Detailed Description

This class extends the [Asn1XerSaxHandler](#) class to add items specific to ASN.1 XER encoding.

1.42.2 Member Function Documentation

1.42.2.1 override void Characters (System.Char[] *ch*, int *start*, int *length*)

This method manage the notification when Characters element were found.

Parameters

- ch* The array with the characters founds
- start* The index of the first position of the characters found
- length* Specify how many characters must be read from the array

1.42.2.2 override void EndElement (System.String *namespaceURI*, System.String *localName*, System.String *qName*) [virtual]

This method manage the notification when the end element node were found

Parameters

- namespaceURI* The namespace URI of the element
- localName* The local name of the element
- qName* The long name (qualify name) of the element

Reimplemented from [XmlSaxDefaultHandler](#).

1.42.2.3 override void StartElement (System.String *namespaceURI*, System.String *localName*, System.String *qName*, [XmlAttributes](#) *atts*) [virtual]

This method manage the event when a start element node were found

Parameters

- namespaceURI* The namespace uri of the element tag
- localName* The local name of the element

qName The Qualify (long) name of the element

atts The list of attributes of the element

Reimplemented from [XmlSaxDefaultHandler](#).

1.43 XmlAttribute Class Reference

Public Member Functions

- [XmlAttribute](#) (System.String Uri, System.String Lname, System.String Qname, System.String Type, System.String Value)

Public Attributes

- System.String [att_fullName](#)
- System.String [att_localName](#)
- System.String [att_type](#)
- System.String [att_URI](#)
- System.String [att_value](#)

1.43.1 Detailed Description

This class is created to save the information of each attributes in the [XmlAttributes](#).

1.43.2 Constructor & Destructor Documentation

1.43.2.1 XmlAttribute (System.String Uri, System.String Lname, System.String Qname, System.String Type, System.String Value)

This is the constructor of the [XmlAttribute](#)

Parameters

Uri The namespace URI of the attribute

Lname The local name of the attribute

Qname The long(Qualify) name of attribute

Type The type of the attribute

Value The value of the attribute

1.43.3 Member Data Documentation

1.43.3.1 System.String att_fullName

Variable holds attribte full name (namespace + local name)

1.43.3.2 System.String att_localName

Variable holds attribte local name

1.43.3.3 System.String att_type

Variable holds attribte type

1.43.3.4 System.String att_URI

Variable holds attribute namespace

1.43.3.5 System.String att_value

Variable holds attribute value

1.44 XmlAttributes Class Reference

Classes

- class [XmlAttribute](#)

Public Member Functions

- virtual void [Add](#) (System.String Uri, System.String Lname, System.String Qname, System.String Type, System.String Value)
- virtual void [Clear](#) ()
- virtual System.String [GetFullName](#) (int index)
- virtual int [GetIndex](#) (System.String Uri, System.String Lname)
- virtual int [GetIndex](#) (System.String Qname)
- virtual int [GetLength](#) ()
- virtual System.String [GetLocalName](#) (int index)
- virtual System.String [GetQName](#) (int index)
- virtual System.String [GetType](#) (System.String Uri, System.String Lname)
- virtual System.String [GetType](#) (System.String Qname)
- virtual System.String [GetType](#) (int index)
- virtual System.String [GetURI](#) (int index)
- virtual System.String [GetValue](#) (System.String Uri, System.String Lname)
- virtual System.String [GetValue](#) (System.String Qname)
- virtual System.String [GetValue](#) (int index)
- virtual void [RemoveAttribute](#) (System.String indexName)
- virtual void [RemoveAttribute](#) (int index)
- virtual void [SetAttribute](#) (int index, System.String Uri, System.String Lname, System.String Qname, System.String Type, System.String Value)
- virtual void [SetAttributes](#) ([XmlAttribute](#) Source)
- virtual void [SetFullName](#) (int index, System.String FullName)
- virtual void [SetLocalName](#) (int index, System.String LocalName)
- virtual void [SetType](#) (int index, System.String Type)
- virtual void [SetURI](#) (int index, System.String URI)
- virtual void [SetValue](#) (int index, System.String Value)
- [XmlAttribute](#)s ([XmlAttribute](#)s arrayList)
- [XmlAttribute](#)s ()

1.44.1 Detailed Description

This class will manage all the parsing operations emulating the SAX parser behavior

1.44.2 Constructor & Destructor Documentation

1.44.2.1 [XmlAttribute](#)s ()

Builds a new instance of [XmlAttribute](#)s.

1.44.2.2 XmlAttributes (XmlAttributes *arrayList*)

Creates a new instance of [XmlAttributes](#) from an ArrayList of [XmlAttribute](#) class.

Parameters

arrayList An ArraList of [XmlAttribute](#) class instances.

Returns

A new instance of [XmlAttributes](#)

1.44.3 Member Function Documentation

1.44.3.1 virtual void Add (System.String *Uri*, System.String *Lname*, System.String *Qname*, System.String *Type*, System.String *Value*) [**virtual**]

Adds a new attribute element to the given [XmlAttributes](#) instance.

Parameters

Uri The Uri of the attribute to be added.

Lname The Local name of the attribute to be added.

Qname The Long(qualify) name of the attribute to be added.

Type The type of the attribute to be added.

Value The value of the attribute to be added.

1.44.3.2 virtual void Clear () [**virtual**]

Clears the list of attributes in the given AttributesSupport instance.

1.44.3.3 virtual System.String GetFullName (int *index*) [**virtual**]

Returns the qualified name of the attribute indicated by the given index.

Parameters

index The attribute index.

Returns

The qualified name or empty string if the index is out of bounds.

1.44.3.4 virtual int GetIndex (System.String *Uri*, System.String *Lname*) [**virtual**]

Obtains the index of an attribute of the AttributeSupport from its namespace URI and its localname.

Parameters

Uri The namespace URI of the attribute to search.

Lname The local name of the attribute to search.

Returns

An zero-based index of the attribute if it is found, otherwise it returns -1.

1.44.3.5 virtual int GetIndex (System.String *Qname*) [virtual]

Obtains the index of an attribute of the AttributeSupport from its qualified (long) name.

Parameters

Qname The qualified name of the attribute to search.

Returns

An zero-based index of the attribute if it is found, otherwise it returns -1.

1.44.3.6 virtual int GetLength () [virtual]

Returns the number of attributes saved in the [XmlAttributes](#) instance.

Returns

The number of elements in the given [XmlAttributes](#) instance.

1.44.3.7 virtual System.String GetLocalName (int *index*) [virtual]

Returns the local name of the attribute in the given [XmlAttributes](#) instance that indicates the given index.

Parameters

index The attribute index.

Returns

The local name of the attribute indicated by the index or null if the index is out of bounds.

1.44.3.8 virtual System.String GetQName (int *index*) [virtual]

Returns the qualified name of the attribute indicated by the given index. This is an alias for GetFullName.

Parameters

index

Returns

The qualified name or empty string if the index is out of bounds.

1.44.3.9 virtual System.String GetType (System.String *Uri*, System.String *Lname*) [virtual]

Returns the type of the Attribute that match with the given namespace URI and local name.

Parameters

Uri The namespace URI of the attribute to search.

Lname The local name of the attribute to search.

Returns

The type of the attribute if it exist otherwise returns null.

1.44.3.10 virtual System.String GetType (System.String *Qname*) [virtual]

Returns the type of the Attribute that match with the given qualified name.

Parameters

Qname The qualified name of the attribute to search.

Returns

The type of the attribute if it exist otherwise returns null.

1.44.3.11 virtual System.String GetType (int *index*) [virtual]

Returns the type of the attribute in the given [XmlAttributes](#) instance that indicates the given index.

Parameters

index The attribute index.

Returns

The type of the attribute indicated by the index or null if the index is out of bounds.

1.44.3.12 virtual System.String GetURI (int *index*) [virtual]

Returns the namespace URI of the attribute in the given [XmlAttributes](#) instance that indicates the given index.

Parameters

index The attribute index.

Returns

The namespace URI of the attribute indicated by the index or null if the index is out of bounds.

1.44.3.13 virtual System.String GetValue (System.String *Uri*, System.String *Lname*) [virtual]

Returns the value of the Attribute that match with the given namespace URI and local name.

Parameters

Uri The namespace URI of the attribute to search.

Lname The local name of the attribute to search.

Returns

The value of the attribute if it exist otherwise returns null.

1.44.3.14 virtual System.String GetValue (System.String *Qname*) [virtual]

Returns the value of the Attribute that match with the given qualified name.

Parameters

Qname The qualified name of the attribute to search.

Returns

The value of the attribute if it exist otherwise returns null.

1.44.3.15 virtual System.String GetValue (int *index*) [virtual]

Returns the value of the attribute in the given [XmlAttributes](#) instance that indicates the given index.

Parameters

index The attribute index.

Returns

The value of the attribute indicated by the index or null if the index is out of bounds.

1.44.3.16 virtual void RemoveAttribute (System.String *indexName*) [virtual]

This method eliminates the [XmlAttribute](#) instance in the specified index.

Parameters

indexName The index name of the attribute.

1.44.3.17 virtual void RemoveAttribute (int *index*) [virtual]

This method eliminates the [XmlAttribute](#) instance at the specified index.

Parameters

index The index of the attribute.

1.44.3.18 virtual void SetAttribute (int *index*, System.String *Uri*, System.String *Lname*, System.String *Qname*, System.String *Type*, System.String *Value*) [virtual]

Replaces an [XmlAttribute](#) in the given [XmlAttributes](#) instance.

Parameters

index The index of the attribute.

Uri The namespace URI of the new [XmlAttribute](#).

Lname The local name of the new [XmlAttribute](#).

Qname The namespace URI of the new [XmlAttribute](#).

Type The type of the new [XmlAttribute](#).

Value The value of the new [XmlAttribute](#).

1.44.3.19 virtual void SetAttributes (XmlAttribute Source) [virtual]

Replaces all the list of [XmlAttribute](#) of the given [XmlAttributes](#) instance.

Parameters

Source The source [XmlAttributes](#) instance.

1.44.3.20 virtual void SetFullName (int index, System.String FullName) [virtual]

Modifies the qualified name of the attribute in the given [XmlAttributes](#) instance.

Parameters

index The attribute index.

FullName The new qualified name for the attribute.

1.44.3.21 virtual void SetLocalName (int index, System.String LocalName) [virtual]

Modifies the local name of the attribute in the given [XmlAttributes](#) instance.

Parameters

index The attribute index.

LocalName The new Local name for the attribute.

1.44.3.22 virtual void SetType (int index, System.String Type) [virtual]

Modifies the type of the attribute in the given [XmlAttributes](#) instance.

Parameters

index The attribute index.

Type The new type for the attribute.

1.44.3.23 virtual void SetURI (int index, System.String URI) [virtual]

Modifies the namespace URI of the attribute in the given [XmlAttributes](#) instance.

Parameters

index The attribute index.

URI The new namespace URI for the attribute.

1.44.3.24 virtual void SetValue (int index, System.String Value) [virtual]

Modifies the value of the attribute in the given [XmlAttributes](#) instance.

Parameters

index The attribute index.

Value The new value for the attribute.

1.45 XmlSaxContentHandler Interface Reference

Inherited by [XmlSaxDefaultHandler](#), and [XmlSaxParserAdapter](#).

Public Member Functions

- void [Characters](#) (char[] ch, int start, int length)
- void [EndDocument](#) ()
- void [EndElement](#) (System.String namespaceURI, System.String localName, System.String qName)
- void [EndPrefixMapping](#) (System.String prefix)
- void [IgnorableWhitespace](#) (char[] Ch, int Start, int Length)
- void [ProcessingInstruction](#) (System.String target, System.String data)
- void [SetDocumentLocator](#) ([XmlSaxLocator](#) locator)
- void [SkippedEntity](#) (System.String name)
- void [StartDocument](#) ()
- void [StartElement](#) (System.String namespaceURI, System.String localName, System.String qName, [XmlAttribute](#) atts)
- void [StartPrefixMapping](#) (System.String prefix, System.String uri)

1.45.1 Detailed Description

This interface will manage the Content events of a XML document.

1.45.2 Member Function Documentation

1.45.2.1 void Characters (char[] *ch*, int *start*, int *length*)

This method manage the notification when Characters elements were found.

Parameters

ch The array with the characters found.

start The index of the first position of the characters found.

length Specify how many characters must be read from the array.

Implemented in [XmlSaxDefaultHandler](#), and [XmlSaxParserAdapter](#).

1.45.2.2 void EndDocument ()

This method manage the notification when the end document node were found.

Implemented in [XmlSaxDefaultHandler](#), and [XmlSaxParserAdapter](#).

1.45.2.3 void EndElement (System.String *namespaceURI*, System.String *localName*, System.String *qName*)

This method manage the notification when the end element node was found.

Parameters

namespaceURI The namespace URI of the element.

localName The local name of the element.

qName The long (qualified) name of the element.

Implemented in [SaxHandler](#), [XmlSaxDefaultHandler](#), and [XmlSaxParserAdapter](#).

1.45.2.4 void EndPrefixMapping (System.String *prefix*)

This method manage the event when an area of expecific URI prefix was ended.

Parameters

prefix The prefix that ends.

Implemented in [XmlSaxDefaultHandler](#), and [XmlSaxParserAdapter](#).

1.45.2.5 void IgnorableWhitespace (char[] *Ch*, int *Start*, int *Length*)

This method manage the event when a ignorable whitespace node was found.

Parameters

Ch The array with the ignorable whitespaces.

Start The index in the array with the ignorable whitespace.

Length The length of the whitespaces.

Implemented in [XmlSaxDefaultHandler](#), and [XmlSaxParserAdapter](#).

1.45.2.6 void ProcessingInstruction (System.String *target*, System.String *data*)

This method manage the event when a processing instruction was found.

Parameters

target The processing instruction target.

data The processing instruction data.

Implemented in [XmlSaxDefaultHandler](#), and [XmlSaxParserAdapter](#).

1.45.2.7 void SetDocumentLocator (XmlSaxLocator *locator*)

This method is not supported, it is included for compatibility.

Parameters

locator A [XmlSaxLocator](#) object that can return the location of any events into the XML document

Implemented in [XmlSaxDefaultHandler](#), and [XmlSaxParserAdapter](#).

1.45.2.8 void SkippedEntity (System.String name)

This method manage the event when a skipped entity was found.

Parameters

name The name of the skipped entity.

Implemented in [XmlSaxDefaultHandler](#), and [XmlSaxParserAdapter](#).

1.45.2.9 void StartDocument ()

This method manage the event when a start document node was found.

Implemented in [XmlSaxDefaultHandler](#), and [XmlSaxParserAdapter](#).

1.45.2.10 void StartElement (System.String namespaceURI, System.String localName, System.String qName, XmlAttributes atts)

This method manage the event when a start element node was found.

Parameters

namespaceURI The namespace uri of the element tag.

localName The local name of the element.

qName The long (qualified) name of the element.

atts The list of attributes of the element.

Implemented in [SaxHandler](#), [XmlSaxDefaultHandler](#), and [XmlSaxParserAdapter](#).

1.45.2.11 void StartPrefixMapping (System.String prefix, System.String uri)

This methods indicates the start of a prefix area in the XML document.

Parameters

prefix The prefix of the area.

uri The namespace URI of the prefix area.

Implemented in [XmlSaxDefaultHandler](#), and [XmlSaxParserAdapter](#).

1.46 XmlSaxDefaultHandler Class Reference

Inherits [Com::Objsys::Asn1::Runtime::XmlSaxContentHandler](#), [Com::Objsys::Asn1::Runtime::XmlSaxErrorHandler](#), and [Com::Objsys::Asn1::Runtime::XmlSaxEntityResolver](#).

Inherited by [Asn1XerSaxHandler](#).

Public Member Functions

- virtual void [Characters](#) (char[] ch, int start, int length)
- virtual void [EndDocument](#) ()
- virtual void [EndElement](#) (System.String ns, System.String localName, System.String qName)
- virtual void [EndPrefixMapping](#) (System.String prefix)
- virtual void [Error](#) (System.Xml.XmlException exception)
- virtual void [FatalError](#) (System.Xml.XmlException exception)
- virtual void [IgnorableWhitespace](#) (char[] chars, int start, int length)
- virtual void [ProcessingInstruction](#) (System.String target, System.String data)
- virtual [XmlSource ResolveEntity](#) (System.String publicId, System.String systemId)
- virtual void [SetDocumentLocator](#) ([XmlSaxLocator](#) locator)
- virtual void [SkippedEntity](#) (System.String name)
- virtual void [StartDocument](#) ()
- virtual void [StartElement](#) (System.String ns, System.String localName, System.String qName, [XmlAttributes](#) attributes)
- virtual void [StartPrefixMapping](#) (System.String prefix, System.String uri)
- virtual void [Warning](#) (System.Xml.XmlException exception)

1.46.1 Detailed Description

This class provides the base implementation for the management of XML documents parsing.

1.46.2 Member Function Documentation

1.46.2.1 virtual void Characters (char[] *ch*, int *start*, int *length*) [virtual]

This method manage the notification when Characters element were found.

Parameters

ch The array with the characters founds

start The index of the first position of the characters found

length Specify how many characters must be read from the array

Implements [XmlSaxContentHandler](#).

1.46.2.2 virtual void EndDocument () [virtual]

This method manage the notification when the end document node were found

Implements [XmlSaxContentHandler](#).

1.46.2.3 virtual void EndElement (System.String ns, System.String localName, System.String qName) [virtual]

This method manage the notification when the end element node were found

Parameters

ns The namespace of the element

localName The local name of the element

qName The long name (qualify name) of the element

Implements [XmlSaxContentHandler](#).

Reimplemented in [SaxHandler](#).

1.46.2.4 virtual void EndPrefixMapping (System.String prefix) [virtual]

This method manage the event when an area of expecific URI prefix was ended.

Parameters

prefix The prefix that ends

Implements [XmlSaxContentHandler](#).

1.46.2.5 virtual void Error (System.Xml.XmlException exception) [virtual]

This method manage when an error exception occurs in the parsing process

Parameters

exception The exception thrown by the parser

Implements [XmlSaxErrorHandler](#).

Reimplemented in [Asn1XerSaxHandler](#).

1.46.2.6 virtual void FatalError (System.Xml.XmlException exception) [virtual]

This method manage when a fatal error exception occurs in the parsing process

Parameters

exception The exception Thrown by the parser

Implements [XmlSaxErrorHandler](#).

Reimplemented in [Asn1XerSaxHandler](#).

1.46.2.7 virtual void IgnorableWhitespace (char[] chars, int start, int length) [virtual]

This method manage the event when a ignorable whitespace node were found

Parameters

chars The array with the ignorable whitespaces

start The array offset at the ignorable whitespace

length The length of the whitespaces

Implements [XmlSaxContentHandler](#).

1.46.2.8 virtual void ProcessingInstruction (System.String *target*, System.String *data*) [virtual]

This method manage the event when a processing instruction were found

Parameters

target The processing instruction target

data The processing instruction data

Implements [XmlSaxContentHandler](#).

1.46.2.9 virtual XmlSource ResolveEntity (System.String *publicId*, System.String *systemId*) [virtual]

Allow the application to resolve external entities.

Parameters

publicId The public identifier of the external entity being referenced, or null if none was supplied.

systemId The system identifier of the external entity being referenced.

Returns

A XmlSourceSupport object describing the new input source, or null to request that the parser open a regular URI connection to the system identifier.

Implements [XmlSaxEntityResolver](#).

1.46.2.10 virtual void SetDocumentLocator (XmlSaxLocator *locator*) [virtual]

This method is not supported, is include for compatibility

Parameters

locator A [XmlSaxLocator](#) object that can return the location of any events into the XML document

Implements [XmlSaxContentHandler](#).

1.46.2.11 virtual void SkippedEntity (System.String *name*) [virtual]

This method manage the event when a skipped entity were found

Parameters

name The name of the skipped entity

Implements [XmlSaxContentHandler](#).

1.46.2.12 virtual void StartDocument () [virtual]

This method manage the event when a start document node were found

Implements [XmlSaxContentHandler](#).

1.46.2.13 virtual void StartElement (System.String *ns*, System.String *localName*, System.String *qName*, XmlAttributes *attributes*) [virtual]

This method manage the event when a start element node were found

Parameters

- ns* The namespace uri of the element tag
- localName* The local name of the element
- qName* The Qualify (long) name of the element
- attributes* The list of attributes of the element

Implements [XmlSaxContentHandler](#).

Reimplemented in [SaxHandler](#).

1.46.2.14 virtual void StartPrefixMapping (System.String *prefix*, System.String *uri*) [virtual]

This methods indicates the start of a prefix area in the XML document.

Parameters

- prefix* The prefix of the area
- uri* The namespace uri of the prefix area

Implements [XmlSaxContentHandler](#).

1.46.2.15 virtual void Warning (System.Xml.XmlException *exception*) [virtual]

This method manage when a warning exception occurs in the parsing process

Parameters

- exception* The exception Thrown by the parser

Implements [XmlSaxErrorHandler](#).

Reimplemented in [AsnIXerSaxHandler](#).

1.47 XmlSaxEntityResolver Interface Reference

Inherited by [XmlSaxDefaultHandler](#).

Public Member Functions

- [XmlSource ResolveEntity](#) (System.String publicId, System.String systemId)

1.47.1 Detailed Description

Basic interface for resolving entities.

1.47.2 Member Function Documentation

1.47.2.1 XmlSource ResolveEntity (System.String *publicId*, System.String *systemId*)

Allow the application to resolve external entities.

Parameters

publicId The public identifier of the external entity being referenced, or null if none was supplied.

systemId The system identifier of the external entity being referenced.

Returns

A XmlSourceSupport object describing the new input source, or null to request that the parser open a regular URI connection to the system identifier.

Implemented in [XmlSaxDefaultHandler](#).

1.48 XmlSaxErrorHandler Interface Reference

Inherited by [XmlSaxDefaultHandler](#).

Public Member Functions

- void [Error](#) (System.Xml.XmlException exception)
- void [FatalError](#) (System.Xml.XmlException exception)
- void [Warning](#) (System.Xml.XmlException exception)

1.48.1 Detailed Description

This interface will manage errors during the parsing of a XML document.

1.48.2 Member Function Documentation

1.48.2.1 void Error (System.Xml.XmlException *exception*)

This method manage an error exception occurred during the parsing process.

Parameters

exception The exception thrown by the parser.

Implemented in [Asn1XerSaxHandler](#), and [XmlSaxDefaultHandler](#).

1.48.2.2 void FatalError (System.Xml.XmlException *exception*)

This method manage a fatal error exception occurred during the parsing process.

Parameters

exception The exception thrown by the parser.

Implemented in [Asn1XerSaxHandler](#), and [XmlSaxDefaultHandler](#).

1.48.2.3 void Warning (System.Xml.XmlException *exception*)

This method manage a warning exception occurred during the parsing process.

Parameters

exception The exception thrown by the parser.

Implemented in [Asn1XerSaxHandler](#), and [XmlSaxDefaultHandler](#).

1.49 XmlSaxLexicalHandler Interface Reference

Public Member Functions

- void [Comment](#) (char[] *ch*, int *start*, int *length*)
- void [EndCDATA](#) ()
- void [EndDTD](#) ()
- void [EndEntity](#) (System.String *name*)
- void [StartCDATA](#) ()
- void [StartDTD](#) (System.String *name*, System.String *publicId*, System.String *systemId*)
- void [StartEntity](#) (System.String *name*)

1.49.1 Detailed Description

This interface will manage the Content events of a XML document.

1.49.2 Member Function Documentation

1.49.2.1 void [Comment](#) (char[] *ch*, int *start*, int *length*)

This method manage the notification when Characters elements were found.

Parameters

- ch* The array with the characters found.
- start* The index of the first position of the characters found.
- length* Specify how many characters must be read from the array.

1.49.2.2 void [EndCDATA](#) ()

This method manage the notification when the end of a CDATA section were found.

1.49.2.3 void [EndDTD](#) ()

This method manage the notification when the end of DTD declarations were found.

1.49.2.4 void [EndEntity](#) (System.String *name*)

This method report the end of an entity.

Parameters

- name* The name of the entity that is ending.

1.49.2.5 void [StartCDATA](#) ()

This method manage the notification when the start of a CDATA section were found.

1.49.2.6 void StartDTD (System.String *name*, System.String *publicId*, System.String *systemId*)

This method manage the notification when the start of DTD declarations were found.

Parameters

name The name of the DTD entity.

publicId The public identifier.

systemId The system identifier.

1.49.2.7 void StartEntity (System.String *name*)

This method report the start of an entity.

Parameters

name The name of the entity that is ending.

1.50 XmlSaxLocator Interface Reference

Inherited by [XmlSaxLocatorImpl](#).

Public Member Functions

- int [GetColumnNumber](#) ()
- int [GetLineNumber](#) ()
- System.String [GetPublicId](#) ()
- System.String [GetSystemId](#) ()

1.50.1 Detailed Description

This interface is created to emulate the SAX Locator interface behavior.

1.50.2 Member Function Documentation

1.50.2.1 int GetColumnNumber ()

This method return the column number where the current document event ends.

Returns

The column number where the current document event ends.

Implemented in [XmlSaxLocatorImpl](#).

1.50.2.2 int GetLineNumber ()

This method return the line number where the current document event ends.

Returns

The line number where the current document event ends.

Implemented in [XmlSaxLocatorImpl](#).

1.50.2.3 System.String GetPublicId ()

This method is not supported, it is included for compatibility.

Returns

The saved public identifier.

Implemented in [XmlSaxLocatorImpl](#).

1.50.2.4 System.String GetSystemId ()

This method is not supported, it is included for compatibility.

Returns

The saved system identifier.

Implemented in [XmlSaxLocatorImpl](#).

1.51 XmlSaxLocatorImpl Class Reference

Inherits [Com::Objsys::Asn1::Runtime::XmlSaxLocator](#).

Public Member Functions

- virtual int [GetColumnNumber](#) ()
- virtual int [GetLineNumber](#) ()
- virtual System.String [GetPublicId](#) ()
- virtual System.String [GetSystemId](#) ()
- virtual void [SetColumnNumber](#) (int columnNumber)
- virtual void [SetLineNumber](#) (int lineNumber)
- virtual void [SetPublicId](#) (System.String publicId)
- virtual void [SetSystemId](#) (System.String systemId)
- [XmlSaxLocatorImpl](#) ([XmlSaxLocator](#) locator)
- [XmlSaxLocatorImpl](#) ()

1.51.1 Detailed Description

This class is created for emulates the SAX LocatorImpl behaviors.

1.51.2 Constructor & Destructor Documentation

1.51.2.1 [XmlSaxLocatorImpl](#) ()

This method returns a new instance of 'XmlSaxLocatorImpl'.

Returns

A new 'XmlSaxLocatorImpl' instance.

1.51.2.2 [XmlSaxLocatorImpl](#) ([XmlSaxLocator](#) *locator*)

This method returns a new instance of 'XmlSaxLocatorImpl'. Create a persistent copy of the current state of a locator.

Parameters

locator The current state of a locator.

Returns

A new 'XmlSaxLocatorImpl' instance.

1.51.3 Member Function Documentation

1.51.3.1 virtual int [GetColumnNumber](#) () [virtual]

Return the saved column number.

Returns

The saved column number.

Implements [XmlSaxLocator](#).

1.51.3.2 virtual int GetLineNumber () [virtual]

Return the saved line number.

Returns

The saved line number.

Implements [XmlSaxLocator](#).

1.51.3.3 virtual System.String GetPublicId () [virtual]

This method is not supported, it is included for compatibility. Return the saved public identifier.

Returns

The saved public identifier.

Implements [XmlSaxLocator](#).

1.51.3.4 virtual System.String GetSystemId () [virtual]

This method is not supported, it is included for compatibility. Return the saved system identifier.

Returns

The saved system identifier.

Implements [XmlSaxLocator](#).

1.51.3.5 virtual void SetColumnNumber (int *columnNumber*) [virtual]

Set the column number for this locator.

Parameters

columnNumber The column number.

1.51.3.6 virtual void SetLineNumber (int *lineNumber*) [virtual]

Set the line number for this locator.

Parameters

lineNumber The line number.

1.51.3.7 virtual void SetPublicId (System.String *publicId*) [virtual]

This method is not supported, it is included for compatibility. Set the public identifier for this locator.

Parameters

publicId The new public identifier.

1.51.3.8 virtual void SetSystemId (System.String *systemId*) [virtual]

This method is not supported, it is included for compatibility. Set the system identifier for this locator.

Parameters

systemId The new system identifier.

1.52 XmlSaxParser Class Reference

Inherited by [XmlSaxParserAdapter](#).

Public Member Functions

- virtual [XmlSaxContentHandler](#) [GetContentHandler](#) ()
- virtual [XmlSaxEntityResolver](#) [GetEntityResolver](#) ()
- virtual [XmlSaxErrorHandler](#) [GetErrorHandler](#) ()
- virtual void [Parse](#) ([XmlSource](#) source)
- virtual void [Parse](#) ([System.IO.Stream](#) stream, [System.String](#) URI)
- virtual void [Parse](#) ([System.IO.Stream](#) stream)
- virtual void [Parse](#) ([System.String](#) filepath)
- virtual void [Parse](#) ([System.IO.FileInfo](#) filepath)
- virtual void [Parse](#) ([XmlSource](#) source, [XmlSaxContentHandler](#) handler)
- virtual void [Parse](#) ([System.IO.Stream](#) stream, [XmlSaxContentHandler](#) handler, [System.String](#) URI)
- virtual void [Parse](#) ([System.IO.Stream](#) stream, [XmlSaxContentHandler](#) handler)
- virtual void [Parse](#) ([System.String](#) filepath, [XmlSaxContentHandler](#) handler)
- virtual void [Parse](#) ([System.IO.FileInfo](#) filepath, [XmlSaxContentHandler](#) handler)
- virtual void [SetContentHandler](#) ([XmlSaxContentHandler](#) handler)
- virtual void [SetDocumentHandler](#) ([XmlSaxContentHandler](#) handler)
- virtual void [SetEntityResolver](#) ([XmlSaxEntityResolver](#) resolver)
- virtual void [SetErrorHandler](#) ([XmlSaxErrorHandler](#) handler)
- [XmlSaxParser](#) ()

Static Public Member Functions

- static [XmlSaxParser](#) [CloneInstance](#) ([XmlSaxParser](#) instance)
- static [XmlSaxParser](#) [NewInstance](#) ()

Protected Attributes

- [XmlSaxContentHandler](#) [callBackHandler](#)
- [XmlSaxEntityResolver](#) [entityResolver](#)
- [XmlSaxErrorHandler](#) [errorHandler](#)
- [XmlSaxLexicalHandler](#) [lexical](#)
- [XmlSaxLocatorImpl](#) [locator](#)
- bool [namespaceAllowed](#)
- [System.String](#) [parserFileName](#)
- [System.Xml.XmlTextReader](#) [reader](#)

Properties

- bool [NamespaceAllowed](#) [get, set]

1.52.1 Detailed Description

Emulates the SAX parsers behaviours.

1.52.2 Constructor & Destructor Documentation

1.52.2.1 XmlSaxParser ()

Public constructor for the class.

1.52.3 Member Function Documentation

1.52.3.1 static XmlSaxParser CloneInstance (XmlSaxParser *instance*) [static]

Create a clone instance of 'XmlSaxParser'.

Parameters

instance The [XmlSaxParser](#) instance to be cloned.

Returns

A clone 'XmlSaxParser' instance.

1.52.3.2 virtual XmlSaxContentHandler GetContentHandler () [virtual]

Obtains the object that will handle all the content events.

Returns

The object that handles the content events.

1.52.3.3 virtual XmlSaxEntityResolver GetEntityResolver () [virtual]

Returns the current entity resolver.

Returns

The current entity resolver, or null if none has been registered.

1.52.3.4 virtual XmlSaxErrorHandler GetErrorHandler () [virtual]

Assigns the object that will handle all the error events.

Returns

The object that handles the error events.

1.52.3.5 static XmlSaxParser NewInstance () [static]

Returns a new instance of 'XmlSaxParser'.

Returns

A new 'XmlSaxParser' instance.

1.52.3.6 virtual void Parse (XmlSource *source*) [virtual]

Parses the specified 'XmlSource' and processes the events over the specified handler, and resolves the entities with the specified URI.

Parameters

source The 'XmlSource' instance with the XML.

1.52.3.7 virtual void Parse (System.IO.Stream *stream*, System.String *URI*) [virtual]

Parses the specified stream and processes the events over previously specified handler, and resolves the external entities with the specified URI.

Parameters

stream The stream with the XML.

URI The namespace URI for resolve external entities.

1.52.3.8 virtual void Parse (System.IO.Stream *stream*) [virtual]

Parses the specified stream and process the events over previously specified handler.

Parameters

stream The stream with the XML.

1.52.3.9 virtual void Parse (System.String *filepath*) [virtual]

Parses the specified file path and processes the events over previously specified handler.

Parameters

filepath The path of the file with the XML.

1.52.3.10 virtual void Parse (System.IO.FileInfo *filepath*) [virtual]

Parses the specified file and process the events over previously specified handler.

Parameters

filepath The file with the XML.

1.52.3.11 virtual void Parse (XmlSource *source*, XmlSaxContentHandler *handler*) [virtual]

Parses the specified 'XmlSource' instance and process the events over the specified handler, and resolves the entities with the specified URI.

Parameters

source The 'XmlSource' that contains the XML.

handler The handler that manages the parser events.

1.52.3.12 virtual void Parse (System.IO.Stream *stream*, XmlSaxContentHandler *handler*, System.String *URI*) [virtual]

Parses the specified stream and process the events over the specified handler, and resolves the entities with the specified URI.

Parameters

stream The stream with the XML.

handler The handler that manage the parser events.

URI The namespace URI for resolve external etities.

1.52.3.13 virtual void Parse (System.IO.Stream *stream*, XmlSaxContentHandler *handler*) [virtual]

Parses the specified stream and process the events over the specified handler.

Parameters

stream The stream with the XML.

handler The handler that manage the parser events.

1.52.3.14 virtual void Parse (System.String *filepath*, XmlSaxContentHandler *handler*) [virtual]

Parses the specified file path and process the events over the specified handler.

Parameters

filepath The path of the file to be used.

handler The handler that manage the parser events.

1.52.3.15 virtual void Parse (System.IO.FileInfo *filepath*, XmlSaxContentHandler *handler*) [virtual]

Parses the specified file and process the events over the specified handler.

Parameters

filepath The file to be used.

handler The handler that manages the parser events.

1.52.3.16 virtual void SetContentHandler (XmlSaxContentHandler *handler*) [virtual]

Assigns the object that will handle all the content events.

Parameters

handler The object that handles the content events.

1.52.3.17 virtual void SetDocumentHandler (XmlSaxContentHandler *handler*) [virtual]

Assigns the object that will handle all the document events.

Parameters

handler The object that handles the content events.

1.52.3.18 virtual void SetEntityResolver (XmlSaxEntityResolver *resolver*) [virtual]

Allows an application to register an entity resolver.

Parameters

resolver The entity resolver.

1.52.3.19 virtual void SetErrorHandler (XmlSaxErrorHandler *handler*) [virtual]

Assigns the object that will handle all the error events.

Parameters

handler The object that handles the errors events.

1.52.4 Member Data Documentation

1.52.4.1 XmlSaxContentHandler callBackHandler [protected]

[XmlSaxContentHandler](#) variable manages the Content events of a XML document.

1.52.4.2 XmlSaxEntityResolver entityResolver [protected]

[XmlSaxEntityResolver](#) variable for resolving entities

1.52.4.3 XmlSaxErrorHandler errorHandler [protected]

[XmlSaxErrorHandler](#) variable manages errors during the parsing of a XML document

1.52.4.4 XmlSaxLexicalHandler lexical [protected]

[XmlSaxLexicalHandler](#) variable manages the Content events of a XML document

1.52.4.5 XmlSaxLocatorImpl locator [protected]

[XmlSaxLocatorImpl](#) variable to emulates the SAX LocatorImpl behaviors.

1.52.4.6 bool namespaceAllowed [protected]

Bool variable manages XML document namespace processing.

1.52.4.7 System.String parserFileName [protected]

String variable holds the XER or XML message file name

1.52.4.8 System.Xml.XmlTextReader reader [protected]

XmlTextReader variable manages XML document parsing.

1.52.5 Property Documentation

1.52.5.1 bool NamespaceAllowed [get, set]

Indicates whether the 'XmlSaxParser' allows namespaces.

1.53 XmlSaxParserAdapter Class Reference

Inherits [Com::Objsys::Asn1::Runtime::XmlSaxParser](#), and [Com::Objsys::Asn1::Runtime::XmlSaxContentHandler](#).

Public Member Functions

- virtual void [Characters](#) (char[] ch, int start, int length)
- virtual void [EndDocument](#) ()
- virtual void [EndElement](#) (System.String namespaceURI, System.String localName, System.String qName)
- virtual void [EndPrefixMapping](#) (System.String prefix)
- virtual void [IgnorableWhitespace](#) (char[] ch, int start, int length)
- virtual void [ProcessingInstruction](#) (System.String target, System.String data)
- virtual void [SetDocumentLocator](#) ([XmlSaxLocator](#) locator)
- virtual void [SkippedEntity](#) (System.String name)
- virtual void [StartDocument](#) ()
- virtual void [StartElement](#) (System.String namespaceURI, System.String localName, System.String qName, [XmlAttributes](#) qAtts)
- virtual void [StartPrefixMapping](#) (System.String prefix, System.String uri)

1.53.1 Detailed Description

This class provides the base implementation for the management of XML documents parsing.

1.53.2 Member Function Documentation

1.53.2.1 virtual void Characters (char[] *ch*, int *start*, int *length*) [virtual]

This method manage the notification when Characters element were found.

Parameters

- ch* The array with the characters founds
- start* The index of the first position of the characters found
- length* Specify how many characters must be read from the array

Implements [XmlSaxContentHandler](#).

1.53.2.2 virtual void EndDocument () [virtual]

This method manage the notification when the end document node were found

Implements [XmlSaxContentHandler](#).

1.53.2.3 virtual void EndElement (System.String *namespaceURI*, System.String *localName*, System.String *qName*) [virtual]

This method manage the notification when the end element node were found

Parameters

- namespaceURI* The namespace URI of the element

localName The local name of the element

qName The long name (qualify name) of the element

Implements [XmlSaxContentHandler](#).

1.53.2.4 virtual void EndPrefixMapping (System.String *prefix*) [virtual]

This method manage the event when an area of expecific URI prefix was ended.

Parameters

prefix The prefix that ends.

Implements [XmlSaxContentHandler](#).

1.53.2.5 virtual void IgnorableWhitespace (char[] *ch*, int *start*, int *length*) [virtual]

This method manage the event when a ignorable whitespace node were found

Parameters

ch The array with the ignorable whitespaces

start The index in the array with the ignorable whitespace

length The length of the whitespaces

Implements [XmlSaxContentHandler](#).

1.53.2.6 virtual void ProcessingInstruction (System.String *target*, System.String *data*) [virtual]

This method manage the event when a processing instruction were found

Parameters

target The processing instruction target

data The processing instruction data

Implements [XmlSaxContentHandler](#).

1.53.2.7 virtual void SetDocumentLocator (XmlSaxLocator *locator*) [virtual]

Receive an object for locating the origin of events into the XML document

Parameters

locator A [XmlSaxLocator](#) object that can return the location of any events into the XML document

Implements [XmlSaxContentHandler](#).

1.53.2.8 virtual void SkippedEntity (System.String name) [virtual]

This method manage the event when a skipped entity was found.

Parameters

name The name of the skipped entity.

Implements [XmlSaxContentHandler](#).

1.53.2.9 virtual void StartDocument () [virtual]

This method manage the event when a start document node were found

Implements [XmlSaxContentHandler](#).

1.53.2.10 virtual void StartElement (System.String namespaceURI, System.String localName, System.String qName, XmlAttributes qAtts) [virtual]

This method manage the event when a start element node were found

Parameters

namespaceURI The namespace uri of the element tag

localName The local name of the element

qName The Qualify (long) name of the element

qAtts The list of attributes of the element

Implements [XmlSaxContentHandler](#).

1.53.2.11 virtual void StartPrefixMapping (System.String prefix, System.String uri) [virtual]

This methods indicates the start of a prefix area in the XML document.

Parameters

prefix The prefix of the area.

uri The namespace URI of the prefix area.

Implements [XmlSaxContentHandler](#).

1.54 XmlSource Class Reference

Public Member Functions

- [XmlSource](#) (System.String source)
- [XmlSource](#) (System.IO.StreamReader reader)
- [XmlSource](#) (System.IO.Stream stream)
- [XmlSource](#) ()

Properties

- System.IO.Stream [Bytes](#) [get, set]
- System.IO.StreamReader [Characters](#) [get, set]
- System.String [Uri](#) [get, set]

1.54.1 Detailed Description

This class is used to encapsulate a source of Xml code in an single class.

1.54.2 Constructor & Destructor Documentation

1.54.2.1 [XmlSource](#) ()

Constructs an empty [XmlSource](#) instance.

1.54.2.2 [XmlSource](#) (System.IO.Stream *stream*)

Constructs a [XmlSource](#) instance with the specified source System.IO.Stream.

Parameters

stream The stream containing the document.

1.54.2.3 [XmlSource](#) (System.IO.StreamReader *reader*)

Constructs a [XmlSource](#) instance with the specified source System.IO.StreamReader.

Parameters

reader The reader containing the document.

1.54.2.4 [XmlSource](#) (System.String *source*)

Construct a [XmlSource](#) instance with the specified source Uri string.

Parameters

source The source containing the document.

1.54.3 Property Documentation

1.54.3.1 System.IO.Stream Bytes [get, set]

Represents the source Stream of the [XmlSource](#).

1.54.3.2 System.IO.StreamReader Characters [get, set]

Represents the source StreamReader of the [XmlSource](#).

1.54.3.3 System.String Uri [get, set]

Represents the source URI of the [XmlSource](#).

Index

Add
Com::Objsys::Asn1::Runtime::XmlAttributes, 137

AddCaptureBuffer
Com::Objsys::Asn1::Runtime::Asn1PerOutputStream, 65

AddElemName
Com::Objsys::Asn1::Runtime::Asn1PerBitFieldList, 36
Com::Objsys::Asn1::Runtime::Asn1PerTraceHandler, 77

Aligned
Com::Objsys::Asn1::Runtime::Asn1PerOutputStream, 73

Asn1BerDecodeBuffer
Com::Objsys::Asn1::Runtime::Asn1BerDecodeBuffer, 2

Asn1BerDecodeContext
Com::Objsys::Asn1::Runtime::Asn1BerDecodeContext, 6

Asn1BerEncodeBuffer
Com::Objsys::Asn1::Runtime::Asn1BerEncodeBuffer, 8

Asn1BerInputStream
Com::Objsys::Asn1::Runtime::Asn1BerInputStream, 14

Asn1BerMessageDumpHandler
Com::Objsys::Asn1::Runtime::Asn1BerMessageDumpHandler, 16

Asn1BerOutputStream
Com::Objsys::Asn1::Runtime::Asn1BerOutputStream, 18

Asn1CerInputStream
Com::Objsys::Asn1::Runtime::Asn1CerInputStream, 24

Asn1CerOutputStream
Com::Objsys::Asn1::Runtime::Asn1CerOutputStream, 25

Asn1DerDecodeBuffer
Com::Objsys::Asn1::Runtime::Asn1DerDecodeBuffer, 29

Asn1DerEncodeBuffer
Com::Objsys::Asn1::Runtime::Asn1DerEncodeBuffer, 30

Asn1DerInputStream
Com::Objsys::Asn1::Runtime::Asn1DerInputStream, 31

Asn1NotInSetException
Com::Objsys::Asn1::Runtime::Asn1NotInSetException, 33

Asn1PerBitField
Com::Objsys::Asn1::Runtime::Asn1PerBitField, 34

Asn1PerBitFieldPrinter
Com::Objsys::Asn1::Runtime::Asn1PerBitFieldPrinter, 38

Asn1PerDecodeBuffer
Com::Objsys::Asn1::Runtime::Asn1PerDecodeBuffer, 41

Asn1PerDecodeTraceHandler
Com::Objsys::Asn1::Runtime::Asn1PerDecodeTraceHandler, 48

Asn1PerEncodeBuffer
Com::Objsys::Asn1::Runtime::Asn1PerEncodeBuffer, 50

Asn1PerEncodeTraceHandler
Com::Objsys::Asn1::Runtime::Asn1PerEncodeTraceHandler, 59

Asn1PerInputStream
Com::Objsys::Asn1::Runtime::Asn1PerInputStream, 60

Asn1PerOutputStream
Com::Objsys::Asn1::Runtime::Asn1PerOutputStream, 65

Asn1PerOutputStreamTraceHandler
Com::Objsys::Asn1::Runtime::Asn1PerOutputStreamTraceHandler, 75

Asn1PerTraceHandler
Com::Objsys::Asn1::Runtime::Asn1PerTraceHandler, 77

Asn1SetDuplicateException
Com::Objsys::Asn1::Runtime::Asn1SetDuplicateException, 81

Asn1TagMatchFailedException
Com::Objsys::Asn1::Runtime::Asn1TagMatchFailedException, 84

Asn1XerBase64OctetString
Com::Objsys::Asn1::Runtime::Asn1XerBase64OctetString, 85

Asn1XerDecodeBuffer
Com::Objsys::Asn1::Runtime::Asn1XerDecodeBuffer, 87

Asn1XerElemInfo	Com::Objsys::Asn1::Runtime::Asn1XerElemInfo,	Com::Objsys::Asn1::Runtime::Asn1XerEncodeBuffer,
	88	91
Asn1XerEncodeBuffer	Com::Objsys::Asn1::Runtime::Asn1XerEncodeBuffer, BitCount	Com::Objsys::Asn1::Runtime::Asn1XmlEncodeBuffer,
	91	116
Asn1XerOpenType	Com::Objsys::Asn1::Runtime::Asn1XerOpenType,	Com::Objsys::Asn1::Runtime::Asn1PerBitField, 34
	100, 101	BitFieldList
Asn1XerOutputStream	Com::Objsys::Asn1::Runtime::Asn1XerOutputStream,	Com::Objsys::Asn1::Runtime::Asn1PerTraceHandler,
	104	79
Asn1XerSaxHandler	Com::Objsys::Asn1::Runtime::Asn1XerSaxHandler,	Com::Objsys::Asn1::Runtime::Asn1PerDecodeBuffer,
	111	47
Asn1XmlEncodeBuffer	Com::Objsys::Asn1::Runtime::Asn1XmlEncodeBuffer,	Com::Objsys::Asn1::Runtime::Asn1PerEncodeBuffer,
	116	57
Asn1XmlOutputStream	Com::Objsys::Asn1::Runtime::Asn1XmlOutputStream,	Com::Objsys::Asn1::Runtime::Asn1XerEncodeBuffer,
	123	95
att_fullName	Com::Objsys::Asn1::Runtime::XmlAttributes::XmlAttribute,	Com::Objsys::Asn1::Runtime::Asn1XmlEncodeBuffer,
	134	121
att_localName	Com::Objsys::Asn1::Runtime::XmlAttributes::XmlAttribute,	Com::Objsys::Asn1::Runtime::Asn1PerDecodeBuffer,
	134	41
att_type	Com::Objsys::Asn1::Runtime::XmlAttributes::XmlAttribute,	Com::Objsys::Asn1::Runtime::Asn1PerEncodeBuffer,
	134	50
att_URI	Com::Objsys::Asn1::Runtime::XmlAttributes::XmlAttribute,	Com::Objsys::Asn1::Runtime::Asn1PerMessageBuffer,
	134	62
Available	Com::Objsys::Asn1::Runtime::Asn1BerInputStream,	Com::Objsys::Asn1::Runtime::Asn1PerOutputStream,
	14	66
	Com::Objsys::Asn1::Runtime::Asn1DerInputStream,	Com::Objsys::Asn1::Runtime::Asn1BerEncodeBuffer,
	31	12
	Com::Objsys::Asn1::Runtime::Asn1PerInputStream,	Com::Objsys::Asn1::Runtime::Asn1PerEncodeBuffer,
	60	57
BinDump	Com::Objsys::Asn1::Runtime::Asn1BerEncodeBuffer, callBackHandler	Com::Objsys::Asn1::Runtime::Asn1PerEncodeBuffer,
	9	57
	Com::Objsys::Asn1::Runtime::Asn1PerDecodeBuffer, Canonical	Com::Objsys::Asn1::Runtime::XmlSource, 168
	41	Bytes
	Com::Objsys::Asn1::Runtime::Asn1PerEncodeBuffer,	Com::Objsys::Asn1::Runtime::Asn1BerDecodeBuffer,
	50	2
	Com::Objsys::Asn1::Runtime::Asn1PerOutputStream,	Com::Objsys::Asn1::Runtime::XmlSaxParser, 162
	65	Com::Objsys::Asn1::Runtime::Asn1XerEncodeBuffer,
		95
		Com::Objsys::Asn1::Runtime::Asn1XerOutputStream,
		110
		Characters

Com::Objsys::Asn1::Runtime::Asn1XerOpenType::SaxHandler, 7
 132
 Com::Objsys::Asn1::Runtime::XmlSaxContentHandler, 142
 Com::Objsys::Asn1::Runtime::XmlSaxDefaultHandler, 145
 Com::Objsys::Asn1::Runtime::XmlSaxParserAdapter, 164
 Com::Objsys::Asn1::Runtime::XmlSource, 168
 CheckSize
 Com::Objsys::Asn1::Runtime::Asn1BerEncodeBuffer, 9
 Com::Objsys::Asn1::Runtime::Asn1PerEncodeBuffer, 51
 Com::Objsys::Asn1::Runtime::Asn1XerEncodeBuffer, 91
 Com::Objsys::Asn1::Runtime::Asn1XmlEncodeBuffer, 116
 Clear
 Com::Objsys::Asn1::Runtime::XmlAttributes, 137
 CloneInstance
 Com::Objsys::Asn1::Runtime::XmlSaxParser, 159
 Close
 Com::Objsys::Asn1::Runtime::Asn1BerInputStream, 14
 Com::Objsys::Asn1::Runtime::Asn1DerInputStream, 31
 Com::Objsys::Asn1::Runtime::Asn1PerInputStream, 60
 Com::Objsys::Asn1::Runtime::Asn1PerOutputStream, 66
 Com::Objsys::Asn1::Runtime::Asn1BerDecodeBuffer, 1
 Asn1BerDecodeBuffer, 2
 CalcIndefLen, 2
 DecodeEnumValue, 2
 DecodeLength, 3
 DecodeOpenType, 3
 DecodeTag, 3
 DecodeTagAndLength, 3
 LastTag, 5
 MatchTag, 4
 MovePastEOC, 4
 Parse, 5
 PeekTag, 5
 ReadByte, 5
 Com::Objsys::Asn1::Runtime::Asn1BerDecodeContext, 6
 Asn1BerDecodeContext, 6
 Expired, 6
 MatchElemTag, 6, 7
 mDecBufByteCount, 7
 mDecodeBuffer, 7
 mElemLength, 7
 mExplicitTagging, 7
 Com::Objsys::Asn1::Runtime::Asn1BerEncodeBuffer, 8
 Asn1BerEncodeBuffer, 8
 BinDump, 9
 ByteArrayInputStream, 12
 CheckSize, 9
 Copy, 9, 10
 EncodeIdentifier, 10
 EncodeIntValue, 10
 EncodeLength, 10
 EncodeTag, 10
 EncodeTagAndLength, 11
 EncodeUnsignedBinaryNumber, 11
 GetInputStream, 11
 MsgCopy, 12
 MsgLength, 13
 Reset, 12
 ToString, 12
 TrimBitString, 12
 Write, 12
 Com::Objsys::Asn1::Runtime::Asn1BerInputStream, 14
 Asn1BerInputStream, 14
 Available, 14
 Close, 14
 Mark, 15
 MarkSupported, 15
 Reset, 15
 Skip, 15
 Com::Objsys::Asn1::Runtime::Asn1BerMessageDumpHandler, 16
 Asn1BerMessageDumpHandler, 16
 Contents, 16
 EndElement, 16
 StartElement, 17
 Com::Objsys::Asn1::Runtime::Asn1BerOutputStream, 18
 Asn1BerOutputStream, 18
 Encode, 19
 EncodeBitString, 19
 EncodeBMPString, 19
 EncodeCharString, 19
 EncodeEOC, 20
 EncodeIdentifier, 20
 EncodeIntValue, 20
 EncodeLength, 20
 EncodeOctetString, 21
 EncodeTag, 21
 EncodeTagAndIndefLen, 21, 22
 EncodeTagAndLength, 22
 EncodeUnivString, 22
 EncodeUnsignedBinaryNumber, 22
 Com::Objsys::Asn1::Runtime::Asn1CerInputStream, 24
 Asn1CerInputStream, 24

Com::Objsys::Asn1::Runtime::Asn1CerOutputStream, 25

- Asn1CerOutputStream, 25
- Encode, 26
- EncodeBitString, 26
- EncodeBMPString, 26
- EncodeCharString, 26
- EncodeOctetString, 27
- EncodeStringTag, 27
- EncodeUnivString, 28

Com::Objsys::Asn1::Runtime::Asn1DerDecodeBuffer, 29

- Asn1DerDecodeBuffer, 29

Com::Objsys::Asn1::Runtime::Asn1DerEncodeBuffer, 30

- Asn1DerEncodeBuffer, 30
- TrimBitString, 30

Com::Objsys::Asn1::Runtime::Asn1DerInputStream, 31

- Asn1DerInputStream, 31
- Available, 31
- Close, 31
- Mark, 31
- MarkSupported, 32
- Reset, 32
- Skip, 32

Com::Objsys::Asn1::Runtime::Asn1NotInSetException, 33

- Asn1NotInSetException, 33

Com::Objsys::Asn1::Runtime::Asn1PerBitField, 34

- Asn1PerBitField, 34
- BitCount, 34
- BitOffset, 34
- Name, 35
- SetBitCountAndOffset, 34

Com::Objsys::Asn1::Runtime::Asn1PerBitFieldList, 36

- AddElemName, 36
- BitOffset, 37
- CurrBitField, 37
- Iterator, 36
- NewBitField, 36
- RemoveLastElemName, 37
- Reset, 37

Com::Objsys::Asn1::Runtime::Asn1PerBitFieldPrinter, 38

- Asn1PerBitFieldPrinter, 38
- mBitMask, 38
- mByteIndex, 38
- mCurrOctet, 39
- mEncodedMessage, 39
- mFmtBitCharIdx, 39
- mFormatBuffer, 39
- mPerMessageBuffer, 39
- Print, 38

Com::Objsys::Asn1::Runtime::Asn1PerDecodeBuffer, 40

- Asn1PerDecodeBuffer, 41
- BinDump, 41
- BitOffset, 47
- ByteAlign, 41
- DecodeBit, 41, 42
- DecodeBitsToInt, 42
- DecodeBitsToLong, 42, 43
- DecodeBitsToOctetArray, 43
- DecodeCharString, 43
- DecodeConsWholeNumber, 44
- DecodeExtLength, 44
- DecodeInt, 44, 45
- DecodeLength, 45
- DecodeSmallNonNegWholeNumber, 45
- IsAligned, 46
- MoveBitCursor, 46
- MsgBitCnt, 47
- mTraceHandler, 47
- ReadByte, 46
- SetAligned, 46
- SetBuffer, 46
- SetInputStream, 47
- TraceHandler, 47

Com::Objsys::Asn1::Runtime::Asn1PerDecodeTraceHandler, 48

- Asn1PerDecodeTraceHandler, 48
- Enable, 48
- Print, 48
- Reset, 48

Com::Objsys::Asn1::Runtime::Asn1PerEncodeBuffer, 49

- Asn1PerEncodeBuffer, 50
- BinDump, 50
- Buffer, 57
- ByteAlign, 50
- ByteArrayInputStream, 57
- ByteIndex, 57
- CheckSize, 51
- Copy, 51
- EncodeBit, 51
- EncodeBits, 51, 52
- EncodeCharString, 52
- EncodeConsWholeNumber, 52, 53
- EncodeInt, 53, 54
- EncodeLength, 54
- EncodeLengthEOM, 54
- EncodeOctetString, 54
- EncodeOIDLengthAndValue, 55
- EncodeOpenType, 55
- EncodeRelOIDLengthAndValue, 55
- EncodeSmallNonNegWholeNumber, 55
- GetInputStream, 56
- HexDump, 56

- IsAligned, [56](#)
- MsgBitCnt, [57](#)
- MsgByteCnt, [58](#)
- MsgCopy, [58](#)
- MsgLength, [58](#)
- mTraceHandler, [57](#)
- Reset, [56](#)
- ReverseBytes, [56](#)
- SetAligned, [56](#)
- ToString, [57](#)
- TraceHandler, [58](#)
- Write, [57](#)
- Com::Objsys::Asn1::Runtime::Asn1PerEncodeTraceHandler, [59](#)
 - Asn1PerEncodeTraceHandler, [59](#)
 - Enable, [59](#)
 - Print, [59](#)
 - Reset, [59](#)
- Com::Objsys::Asn1::Runtime::Asn1PerInputStream, [60](#)
 - Asn1PerInputStream, [60](#)
 - Available, [60](#)
 - Close, [60](#)
 - Mark, [61](#)
 - MarkSupported, [61](#)
 - Reset, [61](#)
 - Skip, [61](#)
- Com::Objsys::Asn1::Runtime::Asn1PerMessageBuffer, [62](#)
 - ByteAlign, [62](#)
 - GetInputStream, [62](#)
 - IsAligned, [62](#)
 - MsgBitCnt, [63](#)
 - TraceHandler, [63](#)
- Com::Objsys::Asn1::Runtime::Asn1PerOutputStream, [64](#)
 - AddCaptureBuffer, [65](#)
 - Aligned, [73](#)
 - Asn1PerOutputStream, [65](#)
 - BinDump, [65](#)
 - ByteAlign, [66](#)
 - Close, [66](#)
 - EncodeBit, [66](#)
 - EncodeBits, [66, 67](#)
 - EncodeCharString, [67](#)
 - EncodeConsWholeNumber, [68](#)
 - EncodeInt, [68, 69](#)
 - EncodeLength, [70](#)
 - EncodeLengthEOM, [70](#)
 - EncodeOctetString, [70](#)
 - EncodeOIDLengthAndValue, [71](#)
 - EncodeOpenType, [71](#)
 - EncodeRelOIDLengthAndValue, [71](#)
 - EncodeSmallNonNegWholeNumber, [72](#)
 - Flush, [72](#)
 - mTraceHandler, [73](#)
 - RemoveCaptureBuffer, [72](#)
 - TraceHandler, [73](#)
 - Write, [72](#)
 - WriteByte, [73](#)
- Com::Objsys::Asn1::Runtime::Asn1PerOutputStreamTraceHandler, [75](#)
 - Asn1PerOutputStreamTraceHandler, [75](#)
 - Enable, [75](#)
 - Print, [75](#)
 - Reset, [75](#)
 - ResetTrace, [75](#)
- Com::Objsys::Asn1::Runtime::Asn1PerTraceHandler, [77](#)
 - AddElemName, [77](#)
 - Asn1PerTraceHandler, [77](#)
 - BitFieldList, [79](#)
 - Enable, [78](#)
 - mBitFieldList, [79](#)
 - NewBitField, [78](#)
 - Print, [78](#)
 - RemoveLastElemName, [78](#)
 - Reset, [78](#)
 - SetBitCount, [78](#)
 - SetBitOffset, [78](#)
- Com::Objsys::Asn1::Runtime::Asn1PerUtil, [80](#)
 - GetMsgBitCnt, [80](#)
- Com::Objsys::Asn1::Runtime::Asn1SetDuplicateException, [81](#)
 - Asn1SetDuplicateException, [81](#)
- Com::Objsys::Asn1::Runtime::Asn1TaggedEventHandler, [82](#)
 - Contents, [82](#)
 - EndElement, [82](#)
 - StartElement, [82](#)
- Com::Objsys::Asn1::Runtime::Asn1TagMatchFailedException, [84](#)
 - Asn1TagMatchFailedException, [84](#)
- Com::Objsys::Asn1::Runtime::Asn1XerBase64OctetString, [85](#)
 - Asn1XerBase64OctetString, [85](#)
 - DecodeXML, [86](#)
 - Encode, [86](#)
- Com::Objsys::Asn1::Runtime::Asn1XerDecodeBuffer, [87](#)
 - Asn1XerDecodeBuffer, [87](#)
 - InputSource, [87](#)
 - mInputSource, [87](#)
- Com::Objsys::Asn1::Runtime::Asn1XerElemInfo, [88](#)
 - Asn1XerElemInfo, [88](#)
 - Equals, [88](#)
 - GetHashCode, [88](#)
 - ID, [89](#)
 - Optional, [89](#)

- Com::Objsys::Asn1::Runtime::Asn1XerEncodeBuffer, 90
 - Asn1XerEncodeBuffer, 91
 - BinDump, 91
 - Buffer, 95
 - Canonical, 95
 - CheckSize, 91
 - Copy, 91, 92
 - DecrLevel, 92
 - EncodeBinStrValue, 92
 - EncodeByte, 92
 - EncodeData, 93
 - EncodeEmptyElement, 93
 - EncodeEndDocument, 93
 - EncodeEndElement, 93
 - EncodeHexStrValue, 93
 - EncodeNamedValue, 93
 - EncodeNamedValueElement, 94
 - EncodeObjectId, 94
 - EncodeRealValue, 94
 - EncodeStartDocument, 94
 - EncodeStartElement, 94
 - GetInputStream, 95
 - IncrLevel, 95
 - Indent, 95
 - MsgCopy, 96
 - MsgLength, 96
 - Reset, 95
 - State, 96
 - Write, 95
- Com::Objsys::Asn1::Runtime::Asn1XerEncoder, 97
 - EncodeEmptyElement, 97
 - EncodeEndElement, 97
 - EncodeNamedValue, 97
 - EncodeRealValue, 98
 - EncodeStartElement, 98
 - State, 98
- Com::Objsys::Asn1::Runtime::Asn1XerEncoder_Fields, 99
 - XERDATA, 99
 - XEREND, 99
 - XERINDENT, 99
 - XERINIT, 99
 - XERSTART, 99
- Com::Objsys::Asn1::Runtime::Asn1XerOpenType, 100
 - Asn1XerOpenType, 100, 101
 - Decode, 101
 - Encode, 101, 102
 - GetSaxHandler, 102
 - named, 103
 - ToString, 103
- Com::Objsys::Asn1::Runtime::Asn1XerOpenType::SaxHandler, 132
 - Characters, 132
 - EndElement, 132
 - StartElement, 132
- Com::Objsys::Asn1::Runtime::Asn1XerOutputStream, 104
 - Asn1XerOutputStream, 104
 - Canonical, 110
 - Copy, 105, 106
 - DecrLevel, 106
 - EncodeBinStrValue, 106
 - EncodeByte, 106
 - EncodeData, 106
 - EncodeEmptyElement, 107
 - EncodeEndDocument, 107
 - EncodeEndElement, 107
 - EncodeHexStrValue, 107
 - EncodeNamedValue, 108
 - EncodeNamedValueElement, 108
 - EncodeObjectId, 108
 - EncodeRealValue, 108
 - EncodeStartDocument, 109
 - EncodeStartElement, 109
 - IncrLevel, 109
 - Indent, 109
 - State, 110
 - Write, 109
- Com::Objsys::Asn1::Runtime::Asn1XerSaxHandler, 111
 - Asn1XerSaxHandler, 111
 - Complete, 113
 - Error, 112
 - FatalError, 112
 - Init, 112
 - mCurrElemID, 113
 - mCurrState, 113
 - mLevel, 113
 - State, 113
 - Warning, 112
 - XERDATA, 113
 - XEREND, 113
 - XERINIT, 113
 - XERSTART, 113
 - XERUNKNOWN, 113
- Com::Objsys::Asn1::Runtime::Asn1XerUtil, 114
 - EncodeReal, 114
 - NormalizedRealValueToString, 114
- Com::Objsys::Asn1::Runtime::Asn1XmlEncodeBuffer, 115
 - Asn1XmlEncodeBuffer, 116
 - BinDump, 116
 - Buffer, 121
 - CheckSize, 116
 - Copy, 116, 117
 - DecrLevel, 117
 - EncodeAttr, 117
 - EncodeBinStrValue, 117

- EncodeByte, 117
- EncodeData, 118
- EncodeDoubleValue, 118
- EncodeEmptyElement, 118
- EncodeEndDocument, 118
- EncodeEndElement, 118, 119
- EncodeHexStrValue, 119
- EncodeNamedValue, 119
- EncodeNamedValueElement, 119
- EncodeObjectId, 119
- EncodeStartDocument, 120
- EncodeStartElement, 120
- EncodeXSIAttrs, 120
- GetInputStream, 120
- Helper, 121
- IncrLevel, 120
- Indent, 120
- MsgCopy, 121
- MsgLength, 121
- Reset, 120
- SetXSIAttrs, 121
- State, 121
- Write, 121
- Com::Objsys::Asn1::Runtime::Asn1XmlOutputStream, 122
 - Asn1XmlOutputStream, 123
 - Copy, 123, 124
 - DecrLevel, 124
 - EncodeAttr, 124
 - EncodeBinStrValue, 124
 - EncodeByte, 125
 - EncodeData, 125
 - EncodeDoubleValue, 125
 - EncodeEmptyElement, 125
 - EncodeEndDocument, 125
 - EncodeEndElement, 126
 - EncodeHexStrValue, 126
 - EncodeNamedValue, 126
 - EncodeNamedValueElement, 126
 - EncodeObjectId, 127
 - EncodeStartDocument, 127
 - EncodeStartElement, 127
 - EncodeXSIAttrs, 127
 - Helper, 128
 - IncrLevel, 127
 - Indent, 127
 - SetXSIAttrs, 128
 - State, 128
 - Write, 128
- Com::Objsys::Asn1::Runtime::Asn1XmlUtil, 129
 - EncodeDouble, 129
 - EncodeNSAttrs, 129
 - GetMinusZero, 129
 - GetXMLString, 130
 - IsMinusZero, 130
 - KeepNullsInString, 130
 - TokenizeXsdList, 130
- Com::Objsys::Asn1::Runtime::XmlAttributes, 136
 - Add, 137
 - Clear, 137
 - GetFullName, 137
 - GetIndex, 137
 - GetLength, 138
 - GetLocalName, 138
 - GetQName, 138
 - GetType, 138, 139
 - GetURI, 139
 - GetValue, 139, 140
 - RemoveAttribute, 140
 - SetAttribute, 140
 - SetAttributes, 140
 - SetFullName, 141
 - SetLocalName, 141
 - SetType, 141
 - SetURI, 141
 - SetValue, 141
 - XmlAttributes, 136
- Com::Objsys::Asn1::Runtime::XmlAttributes::XmlAttribute, 134
 - att_fullName, 134
 - att_localName, 134
 - att_type, 134
 - att_URI, 134
 - att_value, 135
 - XmlAttribute, 134
- Com::Objsys::Asn1::Runtime::XmlSaxContentHandler, 142
 - Characters, 142
 - EndDocument, 142
 - EndElement, 142
 - EndPrefixMapping, 143
 - IgnorableWhitespace, 143
 - ProcessingInstruction, 143
 - SetDocumentLocator, 143
 - SkippedEntity, 143
 - StartDocument, 144
 - StartElement, 144
 - StartPrefixMapping, 144
- Com::Objsys::Asn1::Runtime::XmlSaxDefaultHandler, 145
 - Characters, 145
 - EndDocument, 145
 - EndElement, 145
 - EndPrefixMapping, 146
 - Error, 146
 - FatalError, 146
 - IgnorableWhitespace, 146
 - ProcessingInstruction, 147

- ResolveEntity, 147
- SetDocumentLocator, 147
- SkippedEntity, 147
- StartDocument, 147
- StartElement, 148
- StartPrefixMapping, 148
- Warning, 148
- Com::Objsys::Asn1::Runtime::XmlSaxEntityResolver, 149
 - ResolveEntity, 149
- Com::Objsys::Asn1::Runtime::XmlSaxErrorHandler, 150
 - Error, 150
 - FatalError, 150
 - Warning, 150
- Com::Objsys::Asn1::Runtime::XmlSaxLexicalHandler, 151
 - Comment, 151
 - EndCDATA, 151
 - EndDTD, 151
 - EndEntity, 151
 - StartCDATA, 151
 - StartDTD, 151
 - StartEntity, 152
- Com::Objsys::Asn1::Runtime::XmlSaxLocator, 153
 - GetColumnNumber, 153
 - GetLineNumber, 153
 - GetPublicId, 153
 - GetSystemId, 153
- Com::Objsys::Asn1::Runtime::XmlSaxLocatorImpl, 155
 - GetColumnNumber, 155
 - GetLineNumber, 156
 - GetPublicId, 156
 - GetSystemId, 156
 - SetColumnNumber, 156
 - SetLineNumber, 156
 - SetPublicId, 156
 - SetSystemId, 157
 - XmlSaxLocatorImpl, 155
- Com::Objsys::Asn1::Runtime::XmlSaxParser, 158
 - callbackHandler, 162
 - CloneInstance, 159
 - entityResolver, 162
 - errorHandler, 162
 - GetContentHandler, 159
 - GetEntityResolver, 159
 - GetErrorHandler, 159
 - lexical, 162
 - locator, 162
 - NamespaceAllowed, 163
 - namespaceAllowed, 162
 - NewInstance, 159
 - Parse, 159–161
 - parserFileName, 162
 - reader, 163
 - setContentHandler, 161
 - setDocumentHandler, 161
 - setEntityResolver, 162
 - setErrorHandler, 162
 - XmlSaxParser, 159
- Com::Objsys::Asn1::Runtime::XmlSaxParserAdapter, 164
 - Characters, 164
 - EndDocument, 164
 - EndElement, 164
 - EndPrefixMapping, 165
 - IgnorableWhitespace, 165
 - ProcessingInstruction, 165
 - SetDocumentLocator, 165
 - SkippedEntity, 165
 - StartDocument, 166
 - StartElement, 166
 - StartPrefixMapping, 166
- Com::Objsys::Asn1::Runtime::XmlSource, 167
 - Bytes, 168
 - Characters, 168
 - Uri, 168
 - XmlSource, 167
- Comment
 - Com::Objsys::Asn1::Runtime::XmlSaxLexicalHandler, 151
- Complete
 - Com::Objsys::Asn1::Runtime::Asn1XerSaxHandler, 113
- Contents
 - Com::Objsys::Asn1::Runtime::Asn1BerMessageDumpHandler, 16
 - Com::Objsys::Asn1::Runtime::Asn1TaggedEventHandler, 82
- Copy
 - Com::Objsys::Asn1::Runtime::Asn1BerEncodeBuffer, 9, 10
 - Com::Objsys::Asn1::Runtime::Asn1PerEncodeBuffer, 51
 - Com::Objsys::Asn1::Runtime::Asn1XerEncodeBuffer, 91, 92
 - Com::Objsys::Asn1::Runtime::Asn1XerOutputStream, 105, 106
 - Com::Objsys::Asn1::Runtime::Asn1XmlEncodeBuffer, 116, 117
 - Com::Objsys::Asn1::Runtime::Asn1XmlOutputStream, 123, 124
- CurrBitField
 - Com::Objsys::Asn1::Runtime::Asn1PerBitFieldList, 37
- Decode

Com::Objsys::Asn1::Runtime::Asn1XerOpenType, 101	Com::Objsys::Asn1::Runtime::Asn1XmlEncodeBuffer, 117
DecodeBit Com::Objsys::Asn1::Runtime::Asn1PerDecodeBuffer, 41, 42	Com::Objsys::Asn1::Runtime::Asn1XmlOutputStream, 124
DecodeBitsToInt Com::Objsys::Asn1::Runtime::Asn1PerDecodeBuffer, 42	Enable Com::Objsys::Asn1::Runtime::Asn1PerDecodeTraceHandler, 48
DecodeBitsToLong Com::Objsys::Asn1::Runtime::Asn1PerDecodeBuffer, 42, 43	Com::Objsys::Asn1::Runtime::Asn1PerEncodeTraceHandler, 59
DecodeBitsToOctetArray Com::Objsys::Asn1::Runtime::Asn1PerDecodeBuffer, 43	Com::Objsys::Asn1::Runtime::Asn1PerOutputStreamTraceHandler, 75
DecodeCharString Com::Objsys::Asn1::Runtime::Asn1PerDecodeBuffer, 43	Com::Objsys::Asn1::Runtime::Asn1PerTraceHandler, 78
DecodeConsWholeNumber Com::Objsys::Asn1::Runtime::Asn1PerDecodeBuffer, 44	Encode Com::Objsys::Asn1::Runtime::Asn1BerOutputStream, 19
DecodeEnumValue Com::Objsys::Asn1::Runtime::Asn1BerDecodeBuffer, 2	Com::Objsys::Asn1::Runtime::Asn1CerOutputStream, 26
DecodeExtLength Com::Objsys::Asn1::Runtime::Asn1PerDecodeBuffer, 44	Com::Objsys::Asn1::Runtime::Asn1XerBase64OctetString, 86
DecodeInt Com::Objsys::Asn1::Runtime::Asn1PerDecodeBuffer, 44, 45	Com::Objsys::Asn1::Runtime::Asn1XerOpenType, 101, 102
DecodeLength Com::Objsys::Asn1::Runtime::Asn1BerDecodeBuffer, 3	EncodeAttr Com::Objsys::Asn1::Runtime::Asn1XmlEncodeBuffer, 117
Com::Objsys::Asn1::Runtime::Asn1PerDecodeBuffer, 45	Com::Objsys::Asn1::Runtime::Asn1XmlOutputStream, 124
DecodeOpenType Com::Objsys::Asn1::Runtime::Asn1BerDecodeBuffer, 3	EncodeBinStrValue Com::Objsys::Asn1::Runtime::Asn1XerEncodeBuffer, 92
DecodeSmallNonNegWholeNumber Com::Objsys::Asn1::Runtime::Asn1PerDecodeBuffer, 45	Com::Objsys::Asn1::Runtime::Asn1XerOutputStream, 106
DecodeTag Com::Objsys::Asn1::Runtime::Asn1BerDecodeBuffer, 3	Com::Objsys::Asn1::Runtime::Asn1XmlEncodeBuffer, 117
DecodeTagAndLength Com::Objsys::Asn1::Runtime::Asn1BerDecodeBuffer, 3	Com::Objsys::Asn1::Runtime::Asn1XmlOutputStream, 124
DecodeXML Com::Objsys::Asn1::Runtime::Asn1XerBase64OctetString, 86	EncodeBit Com::Objsys::Asn1::Runtime::Asn1PerEncodeBuffer, 51
DecrLevel Com::Objsys::Asn1::Runtime::Asn1XerEncodeBuffer, 92	Com::Objsys::Asn1::Runtime::Asn1PerOutputStream, 66
Com::Objsys::Asn1::Runtime::Asn1XerOutputStream, 106	EncodeBits Com::Objsys::Asn1::Runtime::Asn1PerEncodeBuffer, 51, 52
	Com::Objsys::Asn1::Runtime::Asn1PerOutputStream, 66, 67
	EncodeBitString Com::Objsys::Asn1::Runtime::Asn1BerOutputStream, 19
	Com::Objsys::Asn1::Runtime::Asn1CerOutputStream, 26
	EncodeBMPString

Com::Objsys::Asn1::Runtime::Asn1BerOutputStream, 19	Com::Objsys::Asn1::Runtime::Asn1XerEncodeBuffer, 93
Com::Objsys::Asn1::Runtime::Asn1CerOutputStream, 26	Com::Objsys::Asn1::Runtime::Asn1XerOutputStream, 107
EncodeByte	Com::Objsys::Asn1::Runtime::Asn1XmlEncodeBuffer, 118
Com::Objsys::Asn1::Runtime::Asn1XerEncodeBuffer, 92	Com::Objsys::Asn1::Runtime::Asn1XmlOutputStream, 125
Com::Objsys::Asn1::Runtime::Asn1XerOutputStream, 106	EncodeEndElement
Com::Objsys::Asn1::Runtime::Asn1XmlEncodeBuffer, 117	Com::Objsys::Asn1::Runtime::Asn1XerEncodeBuffer, 93
Com::Objsys::Asn1::Runtime::Asn1XmlOutputStream, 125	Com::Objsys::Asn1::Runtime::Asn1XerEncoder, 97
EncodeCharString	Com::Objsys::Asn1::Runtime::Asn1XerOutputStream, 107
Com::Objsys::Asn1::Runtime::Asn1BerOutputStream, 19	Com::Objsys::Asn1::Runtime::Asn1XmlEncodeBuffer, 118, 119
Com::Objsys::Asn1::Runtime::Asn1CerOutputStream, 26	Com::Objsys::Asn1::Runtime::Asn1XmlOutputStream, 126
Com::Objsys::Asn1::Runtime::Asn1PerEncodeBuffer, 52	EncodeEOC
Com::Objsys::Asn1::Runtime::Asn1PerOutputStream, 67	Com::Objsys::Asn1::Runtime::Asn1BerOutputStream, 20
EncodeConsWholeNumber	EncodeHexStrValue
Com::Objsys::Asn1::Runtime::Asn1PerEncodeBuffer, 52, 53	Com::Objsys::Asn1::Runtime::Asn1XerEncodeBuffer, 93
Com::Objsys::Asn1::Runtime::Asn1PerOutputStream, 68	Com::Objsys::Asn1::Runtime::Asn1XerOutputStream, 107
EncodeData	Com::Objsys::Asn1::Runtime::Asn1XmlEncodeBuffer, 119
Com::Objsys::Asn1::Runtime::Asn1XerEncodeBuffer, 93	Com::Objsys::Asn1::Runtime::Asn1XmlOutputStream, 126
Com::Objsys::Asn1::Runtime::Asn1XerOutputStream, 106	EncodeIdentifier
Com::Objsys::Asn1::Runtime::Asn1XmlEncodeBuffer, 118	Com::Objsys::Asn1::Runtime::Asn1BerEncodeBuffer, 10
Com::Objsys::Asn1::Runtime::Asn1XmlOutputStream, 125	Com::Objsys::Asn1::Runtime::Asn1BerOutputStream, 20
EncodeDouble	EncodeInt
Com::Objsys::Asn1::Runtime::Asn1XmlUtil, 129	Com::Objsys::Asn1::Runtime::Asn1PerEncodeBuffer, 53, 54
EncodeDoubleValue	Com::Objsys::Asn1::Runtime::Asn1PerOutputStream, 68, 69
Com::Objsys::Asn1::Runtime::Asn1XmlEncodeBuffer, 118	EncodeIntValue
Com::Objsys::Asn1::Runtime::Asn1XmlOutputStream, 125	Com::Objsys::Asn1::Runtime::Asn1BerEncodeBuffer, 10
EncodeEmptyElement	Com::Objsys::Asn1::Runtime::Asn1BerOutputStream, 20
Com::Objsys::Asn1::Runtime::Asn1XerEncodeBuffer, 93	EncodeLength
Com::Objsys::Asn1::Runtime::Asn1XerEncoder, 97	Com::Objsys::Asn1::Runtime::Asn1BerEncodeBuffer, 10
Com::Objsys::Asn1::Runtime::Asn1XerOutputStream, 107	Com::Objsys::Asn1::Runtime::Asn1BerOutputStream, 20
Com::Objsys::Asn1::Runtime::Asn1XmlEncodeBuffer, 118	Com::Objsys::Asn1::Runtime::Asn1PerEncodeBuffer, 54
Com::Objsys::Asn1::Runtime::Asn1XmlOutputStream, 125	Com::Objsys::Asn1::Runtime::Asn1PerOutputStream, 70
EncodeEndDocument	

EncodeLengthEOM	EncodeReal
Com::Objsys::Asn1::Runtime::Asn1PerEncodeBuffer, 54	Com::Objsys::Asn1::Runtime::Asn1XerUtil, 114
Com::Objsys::Asn1::Runtime::Asn1PerOutputStream, 70	EncodeRealValue
EncodeNamedValue	Com::Objsys::Asn1::Runtime::Asn1XerEncodeBuffer, 94
Com::Objsys::Asn1::Runtime::Asn1XerEncodeBuffer, 93	Com::Objsys::Asn1::Runtime::Asn1XerEncoder, 98
Com::Objsys::Asn1::Runtime::Asn1XerEncoder, 97	Com::Objsys::Asn1::Runtime::Asn1XerOutputStream, 108
Com::Objsys::Asn1::Runtime::Asn1XerOutputStream, 108	EncodeRelOIDLengthAndValue
Com::Objsys::Asn1::Runtime::Asn1XmlEncodeBuffer, 119	Com::Objsys::Asn1::Runtime::Asn1PerEncodeBuffer, 55
Com::Objsys::Asn1::Runtime::Asn1XmlOutputStreamEncodeSmallNonNegWholeNumber	Com::Objsys::Asn1::Runtime::Asn1PerOutputStream, 71
126	Com::Objsys::Asn1::Runtime::Asn1PerEncodeBuffer, 55
EncodeNamedValueElement	Com::Objsys::Asn1::Runtime::Asn1PerOutputStream, 72
Com::Objsys::Asn1::Runtime::Asn1XerEncodeBuffer, 94	EncodeStartElement
Com::Objsys::Asn1::Runtime::Asn1XerOutputStream, 108	Com::Objsys::Asn1::Runtime::Asn1XerEncodeBuffer, 94
Com::Objsys::Asn1::Runtime::Asn1XmlEncodeBuffer, 119	Com::Objsys::Asn1::Runtime::Asn1XerOutputStream, 109
Com::Objsys::Asn1::Runtime::Asn1XmlOutputStream, 126	Com::Objsys::Asn1::Runtime::Asn1XmlEncodeBuffer, 120
EncodeNSAttrs	Com::Objsys::Asn1::Runtime::Asn1XmlOutputStream, 127
Com::Objsys::Asn1::Runtime::Asn1XmlUtil, 129	EncodeStartElement
EncodeObjectId	Com::Objsys::Asn1::Runtime::Asn1XerEncodeBuffer, 94
Com::Objsys::Asn1::Runtime::Asn1XerEncodeBuffer, 94	Com::Objsys::Asn1::Runtime::Asn1XerEncoder, 98
Com::Objsys::Asn1::Runtime::Asn1XerOutputStream, 108	Com::Objsys::Asn1::Runtime::Asn1XerOutputStream, 109
Com::Objsys::Asn1::Runtime::Asn1XmlEncodeBuffer, 119	Com::Objsys::Asn1::Runtime::Asn1XmlEncodeBuffer, 120
Com::Objsys::Asn1::Runtime::Asn1XmlOutputStream, 127	Com::Objsys::Asn1::Runtime::Asn1XmlOutputStream, 127
EncodeOctetString	EncodeStringTag
Com::Objsys::Asn1::Runtime::Asn1BerOutputStream, 21	Com::Objsys::Asn1::Runtime::Asn1CerOutputStream, 27
Com::Objsys::Asn1::Runtime::Asn1CerOutputStream, 27	EncodeTag
Com::Objsys::Asn1::Runtime::Asn1PerEncodeBuffer, 54	Com::Objsys::Asn1::Runtime::Asn1BerEncodeBuffer, 10
Com::Objsys::Asn1::Runtime::Asn1PerOutputStream, 70	Com::Objsys::Asn1::Runtime::Asn1BerOutputStream, 21
EncodeOIDLengthAndValue	EncodeTagAndIndefLen
Com::Objsys::Asn1::Runtime::Asn1PerEncodeBuffer, 55	Com::Objsys::Asn1::Runtime::Asn1BerOutputStream, 21, 22
Com::Objsys::Asn1::Runtime::Asn1PerOutputStream, 71	EncodeTagAndLength
EncodeOpenType	Com::Objsys::Asn1::Runtime::Asn1BerEncodeBuffer, 11
Com::Objsys::Asn1::Runtime::Asn1PerEncodeBuffer, 55	Com::Objsys::Asn1::Runtime::Asn1BerOutputStream, 22
Com::Objsys::Asn1::Runtime::Asn1PerOutputStream, 71	EncodeUnivString

Com::Objsys::Asn1::Runtime::Asn1BerOutputStream, 22	88
	Error
Com::Objsys::Asn1::Runtime::Asn1CerOutputStream, 28	Com::Objsys::Asn1::Runtime::Asn1XerSaxHandler, 112
EncodeUnsignedBinaryNumber	Com::Objsys::Asn1::Runtime::XmlSaxDefaultHandler, 146
Com::Objsys::Asn1::Runtime::Asn1BerEncodeBuffer, 11	Com::Objsys::Asn1::Runtime::XmlSaxErrorHandler, 150
Com::Objsys::Asn1::Runtime::Asn1BerOutputStream, 22	errorHandler
EncodeXSIAttrs	Com::Objsys::Asn1::Runtime::XmlSaxParser, 162
Com::Objsys::Asn1::Runtime::Asn1XmlEncodeBufferExpired 120	Com::Objsys::Asn1::Runtime::Asn1BerDecodeContext, 6
Com::Objsys::Asn1::Runtime::Asn1XmlOutputStream, 127	
EndCDATA	FatalError
Com::Objsys::Asn1::Runtime::XmlSaxLexicalHandler, 151	Com::Objsys::Asn1::Runtime::Asn1XerSaxHandler, 112
EndDocument	Com::Objsys::Asn1::Runtime::XmlSaxDefaultHandler, 146
Com::Objsys::Asn1::Runtime::XmlSaxContentHandler, 142	Com::Objsys::Asn1::Runtime::XmlSaxErrorHandler, 150
Com::Objsys::Asn1::Runtime::XmlSaxDefaultHandler, 145	Flush
Com::Objsys::Asn1::Runtime::XmlSaxParserAdapter, 164	Com::Objsys::Asn1::Runtime::Asn1PerOutputStream, 72
EndDTD	
Com::Objsys::Asn1::Runtime::XmlSaxLexicalHandlerGetColumnNumber 151	Com::Objsys::Asn1::Runtime::XmlSaxLocator, 153
EndElement	Com::Objsys::Asn1::Runtime::XmlSaxLocatorImpl, 155
Com::Objsys::Asn1::Runtime::Asn1BerMessageDumpHandler, 16	GetContentHandler
Com::Objsys::Asn1::Runtime::Asn1TaggedEventHandler, 82	Com::Objsys::Asn1::Runtime::XmlSaxParser, 159
Com::Objsys::Asn1::Runtime::Asn1XerOpenType::SaxHandler, 132	GetEntityResolver
Com::Objsys::Asn1::Runtime::XmlSaxContentHandler, 142	Com::Objsys::Asn1::Runtime::XmlSaxParser, 159
Com::Objsys::Asn1::Runtime::XmlSaxDefaultHandler, 145	GetErrorHandler
Com::Objsys::Asn1::Runtime::XmlSaxParserAdapter, 164	Com::Objsys::Asn1::Runtime::XmlSaxParser, 159
	GetFullName
	Com::Objsys::Asn1::Runtime::XmlAttributes, 137
	GetHashCode
	Com::Objsys::Asn1::Runtime::Asn1XerElemInfo, 88
EndEntity	GetIndex
Com::Objsys::Asn1::Runtime::XmlSaxLexicalHandler, 151	Com::Objsys::Asn1::Runtime::XmlAttributes, 137
	GetInputStream
EndPrefixMapping	Com::Objsys::Asn1::Runtime::Asn1BerEncodeBuffer, 11
Com::Objsys::Asn1::Runtime::XmlSaxContentHandler, 143	Com::Objsys::Asn1::Runtime::Asn1PerEncodeBuffer, 56
Com::Objsys::Asn1::Runtime::XmlSaxDefaultHandler, 146	Com::Objsys::Asn1::Runtime::Asn1PerMessageBuffer, 62
Com::Objsys::Asn1::Runtime::XmlSaxParserAdapter, 165	Com::Objsys::Asn1::Runtime::Asn1XerEncodeBuffer, 95
entityResolver	Com::Objsys::Asn1::Runtime::Asn1XmlEncodeBuffer, 120
Com::Objsys::Asn1::Runtime::XmlSaxParser, 162	
Equals	120
Com::Objsys::Asn1::Runtime::Asn1XerElemInfo,	GetLength

Com::Objsys::Asn1::Runtime::XmlAttributes, 138
 GetLineNumber
 Com::Objsys::Asn1::Runtime::XmlSaxLocator, 153
 Com::Objsys::Asn1::Runtime::XmlSaxLocatorImpl, 156
 GetLocalName
 Com::Objsys::Asn1::Runtime::XmlAttributes, 138
 GetMinusZero
 Com::Objsys::Asn1::Runtime::Asn1XmlUtil, 129
 GetMsgBitCnt
 Com::Objsys::Asn1::Runtime::Asn1PerUtil, 80
 GetPublicId
 Com::Objsys::Asn1::Runtime::XmlSaxLocator, 153
 Com::Objsys::Asn1::Runtime::XmlSaxLocatorImpl, 156
 GetQName
 Com::Objsys::Asn1::Runtime::XmlAttributes, 138
 GetSaxHandler
 Com::Objsys::Asn1::Runtime::Asn1XerOpenType, 102
 GetSystemId
 Com::Objsys::Asn1::Runtime::XmlSaxLocator, 153
 Com::Objsys::Asn1::Runtime::XmlSaxLocatorImpl, 156
 GetType
 Com::Objsys::Asn1::Runtime::XmlAttributes, 138, 139
 GetURI
 Com::Objsys::Asn1::Runtime::XmlAttributes, 139
 GetValue
 Com::Objsys::Asn1::Runtime::XmlAttributes, 139, 140
 GetXMLString
 Com::Objsys::Asn1::Runtime::Asn1XmlUtil, 130
 Helper
 Com::Objsys::Asn1::Runtime::Asn1XmlEncodeBuffer, 121
 Com::Objsys::Asn1::Runtime::Asn1XmlOutputStream, 128
 HexDump
 Com::Objsys::Asn1::Runtime::Asn1PerEncodeBuffer, 56
 ID
 Com::Objsys::Asn1::Runtime::Asn1XerElemInfo, 89
 IgnorableWhitespace
 Com::Objsys::Asn1::Runtime::XmlSaxContentHandler, 143
 Com::Objsys::Asn1::Runtime::XmlSaxDefaultHandler, 146
 Com::Objsys::Asn1::Runtime::XmlSaxParserAdapter, 165
 IncrLevel
 Com::Objsys::Asn1::Runtime::Asn1XerEncodeBuffer, 95
 Com::Objsys::Asn1::Runtime::Asn1XerOutputStream, 109
 Com::Objsys::Asn1::Runtime::Asn1XmlEncodeBuffer, 120
 Com::Objsys::Asn1::Runtime::Asn1XmlOutputStream, 127
 Indent
 Com::Objsys::Asn1::Runtime::Asn1XerEncodeBuffer, 95
 Com::Objsys::Asn1::Runtime::Asn1XerOutputStream, 109
 Com::Objsys::Asn1::Runtime::Asn1XmlEncodeBuffer, 120
 Com::Objsys::Asn1::Runtime::Asn1XmlOutputStream, 127
 Init
 Com::Objsys::Asn1::Runtime::Asn1XerSaxHandler, 112
 InputSource
 Com::Objsys::Asn1::Runtime::Asn1XerDecodeBuffer, 87
 IsAligned
 Com::Objsys::Asn1::Runtime::Asn1PerDecodeBuffer, 46
 Com::Objsys::Asn1::Runtime::Asn1PerEncodeBuffer, 56
 Com::Objsys::Asn1::Runtime::Asn1PerMessageBuffer, 62
 IsMinusZero
 Com::Objsys::Asn1::Runtime::Asn1XmlUtil, 130
 Iterator
 Com::Objsys::Asn1::Runtime::Asn1PerBitFieldList, 36
 KeepNullsInString
 Com::Objsys::Asn1::Runtime::Asn1XmlUtil, 130
 LastTag
 Com::Objsys::Asn1::Runtime::Asn1BerDecodeBuffer, 5
 lexical
 Com::Objsys::Asn1::Runtime::XmlSaxParser, 162
 locator
 Com::Objsys::Asn1::Runtime::XmlSaxParser, 162
 Mark
 Com::Objsys::Asn1::Runtime::Asn1BerInputStream, 15
 Com::Objsys::Asn1::Runtime::Asn1DerInputStream, 31
 Com::Objsys::Asn1::Runtime::Asn1PerInputStream, 61

MarkSupported	87
Com::Objsys::Asn1::Runtime::Asn1BerInputStream, mLevel	
15	Com::Objsys::Asn1::Runtime::Asn1XerSaxHandler,
Com::Objsys::Asn1::Runtime::Asn1DerInputStream,	113
32	MoveBitCursor
Com::Objsys::Asn1::Runtime::Asn1PerInputStream,	Com::Objsys::Asn1::Runtime::Asn1PerDecodeBuffer,
61	46
MatchElemTag	MovePastEOC
Com::Objsys::Asn1::Runtime::Asn1BerDecodeContext,	Com::Objsys::Asn1::Runtime::Asn1BerDecodeBuffer,
6, 7	4
MatchTag	mPerMessageBuffer
Com::Objsys::Asn1::Runtime::Asn1BerDecodeBuffer,	Com::Objsys::Asn1::Runtime::Asn1PerBitFieldPrinter,
4	39
mBitFieldList	MsgBitCnt
Com::Objsys::Asn1::Runtime::Asn1PerTraceHandler,	Com::Objsys::Asn1::Runtime::Asn1PerDecodeBuffer,
79	47
mBitMask	Com::Objsys::Asn1::Runtime::Asn1PerEncodeBuffer,
Com::Objsys::Asn1::Runtime::Asn1PerBitFieldPrinter,	57
38	Com::Objsys::Asn1::Runtime::Asn1PerMessageBuffer,
mByteIndex	63
Com::Objsys::Asn1::Runtime::Asn1PerBitFieldPrinter,MsgByteCnt	
38	Com::Objsys::Asn1::Runtime::Asn1PerEncodeBuffer,
mCurrElemID	58
Com::Objsys::Asn1::Runtime::Asn1XerSaxHandler, MsgCopy	
113	Com::Objsys::Asn1::Runtime::Asn1BerEncodeBuffer,
mCurrOctet	12
Com::Objsys::Asn1::Runtime::Asn1PerBitFieldPrinter,	Com::Objsys::Asn1::Runtime::Asn1PerEncodeBuffer,
39	58
mCurrState	Com::Objsys::Asn1::Runtime::Asn1XerEncodeBuffer,
Com::Objsys::Asn1::Runtime::Asn1XerSaxHandler,	96
113	Com::Objsys::Asn1::Runtime::Asn1XmlEncodeBuffer,
mDecBufByteCount	121
Com::Objsys::Asn1::Runtime::Asn1BerDecodeContext,MsgLength	
7	Com::Objsys::Asn1::Runtime::Asn1BerEncodeBuffer,
mDecodeBuffer	13
Com::Objsys::Asn1::Runtime::Asn1BerDecodeContext,	Com::Objsys::Asn1::Runtime::Asn1PerEncodeBuffer,
7	58
mElemLength	Com::Objsys::Asn1::Runtime::Asn1XerEncodeBuffer,
Com::Objsys::Asn1::Runtime::Asn1BerDecodeContext,	96
7	Com::Objsys::Asn1::Runtime::Asn1XmlEncodeBuffer,
mEncodedMessage	121
Com::Objsys::Asn1::Runtime::Asn1PerBitFieldPrinter,mTagHolder	
39	Com::Objsys::Asn1::Runtime::Asn1BerDecodeContext,
mExplicitTagging	7
Com::Objsys::Asn1::Runtime::Asn1BerDecodeContext,mTraceHandler	
7	Com::Objsys::Asn1::Runtime::Asn1PerDecodeBuffer,
mFmtBitCharIdx	47
Com::Objsys::Asn1::Runtime::Asn1PerBitFieldPrinter,	Com::Objsys::Asn1::Runtime::Asn1PerEncodeBuffer,
39	57
mFormatBuffer	Com::Objsys::Asn1::Runtime::Asn1PerOutputStream,
Com::Objsys::Asn1::Runtime::Asn1PerBitFieldPrinter,	73
39	
mInputSource	Name
Com::Objsys::Asn1::Runtime::Asn1XerDecodeBuffer,	Com::Objsys::Asn1::Runtime::Asn1PerBitField, 35

named	Com::Objsys::Asn1::Runtime::Asn1XerOpenType, 103	reader	Com::Objsys::Asn1::Runtime::XmlSaxParser, 163
NamespaceAllowed	Com::Objsys::Asn1::Runtime::XmlSaxParser, 163	RemoveAttribute	Com::Objsys::Asn1::Runtime::XmlAttributes, 140
namespaceAllowed	Com::Objsys::Asn1::Runtime::XmlSaxParser, 162	RemoveCaptureBuffer	Com::Objsys::Asn1::Runtime::Asn1PerOutputStream, 72
NewBitField	Com::Objsys::Asn1::Runtime::Asn1PerBitFieldList, 36	RemoveLastElemName	Com::Objsys::Asn1::Runtime::Asn1PerBitFieldList, 37
	Com::Objsys::Asn1::Runtime::Asn1PerTraceHandler, 78		Com::Objsys::Asn1::Runtime::Asn1PerTraceHandler, 78
NewInstance	Com::Objsys::Asn1::Runtime::XmlSaxParser, 159	Reset	Com::Objsys::Asn1::Runtime::Asn1BerEncodeBuffer, 12
NormalizedRealValueToString	Com::Objsys::Asn1::Runtime::Asn1XerUtil, 114		Com::Objsys::Asn1::Runtime::Asn1BerInputStream, 15
Optional	Com::Objsys::Asn1::Runtime::Asn1XerElemInfo, 89		Com::Objsys::Asn1::Runtime::Asn1DerInputStream, 32
Parse	Com::Objsys::Asn1::Runtime::Asn1BerDecodeBuffer, 5		Com::Objsys::Asn1::Runtime::Asn1PerBitFieldList, 37
	Com::Objsys::Asn1::Runtime::XmlSaxParser, 159–161		Com::Objsys::Asn1::Runtime::Asn1PerDecodeTraceHandler, 48
parserFileName	Com::Objsys::Asn1::Runtime::XmlSaxParser, 162		Com::Objsys::Asn1::Runtime::Asn1PerEncodeBuffer, 56
PeekTag	Com::Objsys::Asn1::Runtime::Asn1BerDecodeBuffer, 5		Com::Objsys::Asn1::Runtime::Asn1PerEncodeTraceHandler, 59
Print	Com::Objsys::Asn1::Runtime::Asn1PerBitFieldPrinter, 38		Com::Objsys::Asn1::Runtime::Asn1PerInputStream, 61
	Com::Objsys::Asn1::Runtime::Asn1PerDecodeTraceHandler, 48		Com::Objsys::Asn1::Runtime::Asn1PerOutputStreamTraceHandler, 75
	Com::Objsys::Asn1::Runtime::Asn1PerEncodeTraceHandler, 59		Com::Objsys::Asn1::Runtime::Asn1PerTraceHandler, 78
	Com::Objsys::Asn1::Runtime::Asn1PerOutputStreamTraceHandler, 75		Com::Objsys::Asn1::Runtime::Asn1XerEncodeBuffer, 95
	Com::Objsys::Asn1::Runtime::Asn1PerTraceHandler, 78		Com::Objsys::Asn1::Runtime::Asn1XmlEncodeBuffer, 120
ProcessingInstruction	Com::Objsys::Asn1::Runtime::XmlSaxContentHandler, 143	ResetTrace	Com::Objsys::Asn1::Runtime::Asn1PerOutputStreamTraceHandler, 75
	Com::Objsys::Asn1::Runtime::XmlSaxDefaultHandler, 147	ResolveEntity	Com::Objsys::Asn1::Runtime::XmlSaxDefaultHandler, 147
	Com::Objsys::Asn1::Runtime::XmlSaxParserAdapter, 165		Com::Objsys::Asn1::Runtime::XmlSaxEntityResolver, 149
		ReverseBytes	Com::Objsys::Asn1::Runtime::Asn1PerEncodeBuffer, 56
ReadByte	Com::Objsys::Asn1::Runtime::Asn1BerDecodeBuffer, 5	SetAligned	Com::Objsys::Asn1::Runtime::Asn1PerDecodeBuffer, 46
	Com::Objsys::Asn1::Runtime::Asn1PerDecodeBuffer, 46		Com::Objsys::Asn1::Runtime::Asn1PerEncodeBuffer, 56

SetAttribute
 Com::Objsys::Asn1::Runtime::XmlAttributes, 140
 SetAttributes
 Com::Objsys::Asn1::Runtime::XmlAttributes, 140
 SetBitCount
 Com::Objsys::Asn1::Runtime::Asn1PerTraceHandler, 78
 SetBitCountAndOffset
 Com::Objsys::Asn1::Runtime::Asn1PerBitField, 34
 SetBitOffset
 Com::Objsys::Asn1::Runtime::Asn1PerTraceHandler, 78
 SetBuffer
 Com::Objsys::Asn1::Runtime::Asn1PerDecodeBuffer, 46
 SetColumnNumber
 Com::Objsys::Asn1::Runtime::XmlSaxLocatorImpl, 156
 SetContentHandler
 Com::Objsys::Asn1::Runtime::XmlSaxParser, 161
 SetDocumentHandler
 Com::Objsys::Asn1::Runtime::XmlSaxParser, 161
 SetDocumentLocator
 Com::Objsys::Asn1::Runtime::XmlSaxContentHandler, 143
 Com::Objsys::Asn1::Runtime::XmlSaxDefaultHandler, 147
 Com::Objsys::Asn1::Runtime::XmlSaxParserAdapter, 165
 SetEntityResolver
 Com::Objsys::Asn1::Runtime::XmlSaxParser, 162
 SetErrorHandler
 Com::Objsys::Asn1::Runtime::XmlSaxParser, 162
 SetFullName
 Com::Objsys::Asn1::Runtime::XmlAttributes, 141
 SetInputStream
 Com::Objsys::Asn1::Runtime::Asn1PerDecodeBuffer, 47
 SetLineNumber
 Com::Objsys::Asn1::Runtime::XmlSaxLocatorImpl, 156
 SetLocalName
 Com::Objsys::Asn1::Runtime::XmlAttributes, 141
 SetPublicId
 Com::Objsys::Asn1::Runtime::XmlSaxLocatorImpl, 156
 SetSystemId
 Com::Objsys::Asn1::Runtime::XmlSaxLocatorImpl, 157
 SetType
 Com::Objsys::Asn1::Runtime::XmlAttributes, 141
 SetURI
 Com::Objsys::Asn1::Runtime::XmlAttributes, 141
 SetValue
 Com::Objsys::Asn1::Runtime::XmlAttributes, 141
 SetXSIAttrs
 Com::Objsys::Asn1::Runtime::Asn1XmlEncodeBuffer, 121
 Com::Objsys::Asn1::Runtime::Asn1XmlOutputStream, 128
 Skip
 Com::Objsys::Asn1::Runtime::Asn1BerInputStream, 15
 Com::Objsys::Asn1::Runtime::Asn1DerInputStream, 32
 Com::Objsys::Asn1::Runtime::Asn1PerInputStream, 61
 Com::Objsys::Asn1::Runtime::XmlSaxContentHandler, 143
 Com::Objsys::Asn1::Runtime::XmlSaxDefaultHandler, 147
 Com::Objsys::Asn1::Runtime::XmlSaxParserAdapter, 165
 StartCDATA
 Com::Objsys::Asn1::Runtime::XmlSaxLexicalHandler, 151
 StartDocument
 Com::Objsys::Asn1::Runtime::XmlSaxContentHandler, 144
 Com::Objsys::Asn1::Runtime::XmlSaxDefaultHandler, 147
 Com::Objsys::Asn1::Runtime::XmlSaxParserAdapter, 166
 StartDTD
 Com::Objsys::Asn1::Runtime::XmlSaxLexicalHandler, 151
 StartElement
 Com::Objsys::Asn1::Runtime::Asn1BerMessageDumpHandler, 17
 Com::Objsys::Asn1::Runtime::Asn1TaggedEventHandler, 82
 Com::Objsys::Asn1::Runtime::Asn1XerOpenType::SaxHandler, 132
 Com::Objsys::Asn1::Runtime::XmlSaxContentHandler, 144
 Com::Objsys::Asn1::Runtime::XmlSaxDefaultHandler, 148
 Com::Objsys::Asn1::Runtime::XmlSaxParserAdapter, 166
 StartEntity
 Com::Objsys::Asn1::Runtime::XmlSaxLexicalHandler, 152
 StartPrefixMapping
 Com::Objsys::Asn1::Runtime::XmlSaxContentHandler, 144
 Com::Objsys::Asn1::Runtime::XmlSaxDefaultHandler, 148

Com::Objsys::Asn1::Runtime::XmlSaxParserAdapter, 166	Com::Objsys::Asn1::Runtime::Asn1PerOutputStream, 72
State	Com::Objsys::Asn1::Runtime::Asn1XerEncodeBuffer, 95
Com::Objsys::Asn1::Runtime::Asn1XerEncodeBuffer, 96	Com::Objsys::Asn1::Runtime::Asn1XerOutputStream, 109
Com::Objsys::Asn1::Runtime::Asn1XerEncoder, 98	Com::Objsys::Asn1::Runtime::Asn1XmlEncodeBuffer, 121
Com::Objsys::Asn1::Runtime::Asn1XerOutputStream, 110	Com::Objsys::Asn1::Runtime::Asn1XmlOutputStream, 128
Com::Objsys::Asn1::Runtime::Asn1XerSaxHandler, 113	Com::Objsys::Asn1::Runtime::Asn1PerOutputStream, 73
Com::Objsys::Asn1::Runtime::Asn1XmlEncodeBuffer,WriteByte 121	
Com::Objsys::Asn1::Runtime::Asn1XmlOutputStream, 128	
	XERDATA
TokenizeXsdList	Com::Objsys::Asn1::Runtime::Asn1XerEncoder_ Fields, 99
Com::Objsys::Asn1::Runtime::Asn1XmlUtil, 130	Com::Objsys::Asn1::Runtime::Asn1XerSaxHandler, 113
ToString	XEREND
Com::Objsys::Asn1::Runtime::Asn1BerEncodeBuffer, 12	Com::Objsys::Asn1::Runtime::Asn1XerEncoder_ Fields, 99
Com::Objsys::Asn1::Runtime::Asn1PerEncodeBuffer, 57	Com::Objsys::Asn1::Runtime::Asn1XerSaxHandler, 113
Com::Objsys::Asn1::Runtime::Asn1XerOpenType, 103	XERINDENT
TraceHandler	Com::Objsys::Asn1::Runtime::Asn1XerEncoder_ Fields, 99
Com::Objsys::Asn1::Runtime::Asn1PerDecodeBuffer, 47	XERINIT
Com::Objsys::Asn1::Runtime::Asn1PerEncodeBuffer, 58	Com::Objsys::Asn1::Runtime::Asn1XerEncoder_ Fields, 99
Com::Objsys::Asn1::Runtime::Asn1PerMessageBuffer, 63	Com::Objsys::Asn1::Runtime::Asn1XerSaxHandler, 113
Com::Objsys::Asn1::Runtime::Asn1PerOutputStream, 73	XERSTART
TrimBitString	Com::Objsys::Asn1::Runtime::Asn1XerEncoder_ Fields, 99
Com::Objsys::Asn1::Runtime::Asn1BerEncodeBuffer, 12	Com::Objsys::Asn1::Runtime::Asn1XerSaxHandler, 113
Com::Objsys::Asn1::Runtime::Asn1DerEncodeBuffer, 30	XERUNKNOWN
Uri	Com::Objsys::Asn1::Runtime::Asn1XerSaxHandler, 113
Com::Objsys::Asn1::Runtime::XmlSource, 168	XmlAttribute
Warning	Com::Objsys::Asn1::Runtime::XmlAttributes::XmlAttribute, 134
Com::Objsys::Asn1::Runtime::Asn1XerSaxHandler, 112	XmlAttribute
Com::Objsys::Asn1::Runtime::XmlSaxDefaultHandler, 148	Com::Objsys::Asn1::Runtime::XmlAttributes, 136
Com::Objsys::Asn1::Runtime::XmlSaxErrorHandler, 150	XmlSaxLocatorImpl
Write	Com::Objsys::Asn1::Runtime::XmlSaxLocatorImpl, 155
Com::Objsys::Asn1::Runtime::Asn1BerEncodeBuffer, 12	XmlSaxParser
Com::Objsys::Asn1::Runtime::Asn1PerEncodeBuffer, 57	Com::Objsys::Asn1::Runtime::XmlSaxParser, 159
	XmlSource
	Com::Objsys::Asn1::Runtime::XmlSource, 167